

Guidelines for test developers

How to add recipes

For any test that you want to perform, you write a script located in `test/recipes/`, named `{nn}-test_{name}.t`, where `{nn}` is a two digit number and `{name}` is a unique name of your choice.

Please note that if a test involves a new testing executable, you will need to do some additions in `test/build.info`. Please refer to the section “Changes to `test/build.info`” below.

Naming conventions

A test executable is named `test/{name}test.c`

A test recipe is named `test/recipes/{nn}-test_{name}.t`, where `{nn}` is a two digit number and `{name}` is a unique name of your choice.

The number `{nn}` is (somewhat loosely) grouped as follows:

- 00-04 sanity, internal and essential API tests
- 05-09 individual symmetric cipher algorithms
- 10-14 math (bignum)
- 15-19 individual asymmetric cipher algorithms
- 20-24 openssl commands (some otherwise not tested)
- 25-29 certificate forms, generation and verification
- 30-35 engine and evp
- 60-79 APIs:
 - 60 X509 subsystem
 - 61 BIO subsystem
 - 65 CMP subsystem
 - 70 PACKET layer
- 80-89 "larger" protocols (CA, CMS, OCSP, SSL, TSA)
- 90-98 misc
- 99 most time consuming tests [such as `test_fuzz`]

A recipe that just runs a test executable

A script that just runs a program looks like this:

```
#!/usr/bin/env perl

use OpenSSL::Test::Simple;

simple_test("test_{name}", "{name}test", "{name}");
```

`{name}` is the unique name you have chosen for your test.

The second argument to `simple_test` is the test executable, and `simple_test` expects it to be located in `test/`

For documentation on `OpenSSL::Test::Simple`, do `perldoc util/perl/OpenSSL/Test/Simple.pm`.

A recipe that runs a more complex test

For more complex tests, you will need to read up on `Test::More` and `OpenSSL::Test`. `Test::More` is normally preinstalled, do `man Test::More` for documentation. For `OpenSSL::Test`, do `perldoc util/perl/OpenSSL/Test.pm`.

A script to start from could be this:

```
#!/usr/bin/env perl

use strict;
use warnings;
use OpenSSL::Test;

setup("test_{name}");

plan tests => 2;          # The number of tests being performed

ok(test1, "test1");
ok(test2, "test1");

sub test1
{
    # test feature 1
}

sub test2
{
    # test feature 2
}
```

Changes to test/build.info

Whenever a new test involves a new test executable you need to do the following (at all times, replace `{NAME}` and `{name}` with the name of your test):

- add `{name}` to the list of programs under `PROGRAMS_NO_INST`
- create a three line description of how to build the test, you will have to modify the include paths and source files if you don't want to use the basic test framework:

```
SOURCE[{name}]={name}.c
INCLUDE[{name}]=.. ../include ../apps/include
```

```
DEPEND[{name}]=../libcrypto libtestutil.a
```

Generic form of C test executables

```
#include "testutil.h"

static int my_test(void)
{
    int testresult = 0;           /* Assume the test will fail */
    int observed;

    observed = function();        /* Call the code under test */
    if (!TEST_int_eq(observed, 2)) /* Check the result is correct */
        goto end;               /* Exit on failure - optional */

    testresult = 1;              /* Mark the test case a success */
end:
    cleanup();                   /* Any cleanup you require */
    return testresult;
}

int setup_tests(void)
{
    ADD_TEST(my_test);           /* Add each test separately */
    return 1;                    /* Indicate success */
}
```

You should use the `TEST_xxx` macros provided by `testutil.h` to test all failure conditions. These macros produce an error message in a standard format if the condition is not met (and nothing if the condition is met). Additional information can be presented with the `TEST_info` macro that takes a `printf` format string and arguments. `TEST_error` is useful for complicated conditions, it also takes a `printf` format string and argument. In all cases the `TEST_xxx` macros are guaranteed to evaluate their arguments exactly once. This means that expressions with side effects are allowed as parameters. Thus,

```
if (!TEST_ptr(ptr = OPENSSL_malloc(...)))
```

works fine and can be used in place of:

```
ptr = OPENSSL_malloc(...);
if (!TEST_ptr(ptr))
```

The former produces a more meaningful message on failure than the latter.

Note that the test infrastructure automatically sets up all required environment variables (such as `OPENSSL_MODULES`, `OPENSSL_CONF`, etc.) for the tests. Individual tests may choose to override the default settings as required.