

Bundler

This plugin adds completion for basic bundler commands, as well as aliases and helper functions for an easier experience with bundler.

To use it, add `bundler` to the plugins array in your `zshrc` file:

```
plugins=(... bundler)
```

Aliases

Alias	Command	Description
ba	<code>bundle add</code>	Add gem to the Gemfile and run <code>bundle install</code>
bck	<code>bundle check</code>	Verifies if dependencies are satisfied by installed gems
bcn	<code>bundle clean</code>	Cleans up unused gems in your bundler directory
be	<code>bundle exec</code>	Execute a command in the context of the bundle
bi	<code>bundle install</code> <code>--jobs=<core_count></code>	Install the dependencies specified in your Gemfile (using all cores in bundler $\geq 1.4.0$)
bl	<code>bundle list</code>	List all the gems in the bundle
bo	<code>bundle open</code>	Opens the source directory for a gem in your bundle
bout	<code>bundle outdated</code>	List installed gems with newer versions available
bp	<code>bundle package</code>	Package your needed .gem files into your application
bu	<code>bundle update</code>	Update your gems to the latest available versions

Gem wrapper

The plugin adds a wrapper for common gems, which:

- Looks for a binstub under `./bin/` and executes it if present.
- Calls `bundle exec <gem>` otherwise.

Common gems wrapped by default (by name of the executable):

annotate, cap, capify, cucumber, foodcritic, guard, hanami, irb, jekyll, kitchen, knife, middleman, nanoc, pry, puma, rackup, rainbows, rake, rspec, rubocop, shotgun, sidekiq, spec, spork, spring, strainer, tailor, taps, thin, thor, unicorn and unicorn_rails.

Settings

You can add or remove gems from the list of wrapped commands. Please **use the exact name of the executable** and not the gem name.

Include gems to be wrapped (BUNDLED_COMMANDS) Add this before the plugin list in your `.zshrc`:

```
BUNDLED_COMMANDS=(rubocop)
plugins=(... bundler ...)
```

This will add the wrapper for the `rubocop` gem (i.e. the executable).

Exclude gems from being wrapped (UNBUNDLED_COMMANDS) Add this before the plugin list in your `.zshrc`:

```
UNBUNDLED_COMMANDS=(foreman spin)
plugins=(... bundler ...)
```

This will exclude the `foreman` and `spin` gems (i.e. their executable) from being wrapped.

Excluded gems

These gems should not be called with `bundle exec`. Please see issue #2923 on GitHub for clarification:

- `berks`
- `foreman`
- `mailcatcher`
- `rails`
- `ruby`
- `spin`