

How to write and run benchmarks in Node.js core

Table of contents

- [Prerequisites](#)
 - [HTTP benchmark requirements](#)
 - [HTTPS benchmark requirements](#)
 - [HTTP/2 benchmark requirements](#)
 - [Benchmark analysis requirements](#)
- [Running benchmarks](#)
 - [Running individual benchmarks](#)
 - [Running all benchmarks](#)
 - [Filtering benchmarks](#)
 - [Comparing Node.js versions](#)
 - [Comparing parameters](#)
 - [Running benchmarks on the CI](#)
- [Creating a benchmark](#)
 - [Basics of a benchmark](#)
 - [Creating an HTTP benchmark](#)

Prerequisites

Basic Unix tools are required for some benchmarks. [Git for Windows](#) includes Git Bash and the necessary tools, which need to be included in the global Windows `PATH`.

HTTP benchmark requirements

Most of the HTTP benchmarks require a benchmarker to be installed. This can be either [wrk](#) or [autocannon](#).

`Autocannon` is a Node.js script that can be installed using `npm install -g autocannon`. It will use the Node.js executable that is in the path. In order to compare two HTTP benchmark runs, make sure that the Node.js version in the path is not altered.

`wrk` may be available through one of the available package managers. If not, it can be easily built [from source](#) via `make`.

By default, `wrk` will be used as the benchmarker. If it is not available, `autocannon` will be used in its place. When creating an HTTP benchmark, the benchmarker to be used should be specified by providing it as an argument:

```
node benchmark/run.js --set benchmarker=autocannon http
```

```
node benchmark/http/simple.js benchmarker=autocannon
```

HTTPS benchmark requirements

To run the `https` benchmarks, one of `autocannon` or `wrk` benchmarkers must be used.

```
node benchmark/https/simple.js benchmarker=autocannon
```

HTTP/2 benchmark requirements

To run the `http2` benchmarks, the `h2load` benchmarker must be used. The `h2load` tool is a component of the `nghttp2` project and may be installed from nghttp2.org or built from source.

```
node benchmark/http2/simple.js benchmarker=h2load
```

Benchmark analysis requirements

To analyze the results statistically, you can use either the [node-benchmark-compare](#) tool or the R script

```
benchmark/compare.R .
```

[node-benchmark-compare](#) is a Node.js script that can be installed with `npm install -g node-benchmark-compare`.

To draw comparison plots when analyzing the results, `R` must be installed. Use one of the available package managers or download it from <https://www.r-project.org/>.

The R packages `ggplot2` and `plyr` are also used and can be installed using the R REPL.

```
$ R
install.packages("ggplot2")
install.packages("plyr")
```

If a message states that a CRAN mirror must be selected first, specify a mirror with the `repo` parameter.

```
install.packages("ggplot2", repo="http://cran.us.r-project.org")
```

Of course, use an appropriate mirror based on location. A list of mirrors is [located here](#).

Running benchmarks

Running individual benchmarks

This can be useful for debugging a benchmark or doing a quick performance measure. But it does not provide the statistical information to make any conclusions about the performance.

Individual benchmarks can be executed by simply executing the benchmark script with node.

```
$ node benchmark/buffers/buffer-tostring.js

buffers/buffer-tostring.js n=10000000 len=0 arg=true: 62710590.393305704
buffers/buffer-tostring.js n=10000000 len=1 arg=true: 9178624.591787899
buffers/buffer-tostring.js n=10000000 len=64 arg=true: 7658962.8891432695
buffers/buffer-tostring.js n=10000000 len=1024 arg=true: 4136904.4060201733
buffers/buffer-tostring.js n=10000000 len=0 arg=false: 22974354.231509723
buffers/buffer-tostring.js n=10000000 len=1 arg=false: 11485945.656765845
buffers/buffer-tostring.js n=10000000 len=64 arg=false: 8718280.70650129
buffers/buffer-tostring.js n=10000000 len=1024 arg=false: 4103857.0726124765
```

Each line represents a single benchmark with parameters specified as `${variable}=${value}`. Each configuration combination is executed in a separate process. This ensures that benchmark results aren't affected by

the execution order due to V8 optimizations. **The last number is the rate of operations measured in ops/sec (higher is better).**

Furthermore a subset of the configurations can be specified, by setting them in the process arguments:

```
$ node benchmark/buffers/buffer-tostring.js len=1024

buffers/buffer-tostring.js n=10000000 len=1024 arg=true: 3498295.68561504
buffers/buffer-tostring.js n=10000000 len=1024 arg=false: 3783071.1678948295
```

Running all benchmarks

Similar to running individual benchmarks, a group of benchmarks can be executed by using the `run.js` tool. To see how to use this script, run `node benchmark/run.js`. Again this does not provide the statistical information to make any conclusions.

```
$ node benchmark/run.js assert

assert/deepequal-buffer.js
assert/deepequal-buffer.js method="deepEqual" strict=0 len=100 n=20000:
773,200.4995493788
assert/deepequal-buffer.js method="notDeepEqual" strict=0 len=100 n=20000:
964,411.712953848
...

assert/deepequal-map.js
assert/deepequal-map.js method="deepEqual_primitiveOnly" strict=0 len=500 n=500:
20,445.06368453332
assert/deepequal-map.js method="deepEqual_objectOnly" strict=0 len=500 n=500:
1,393.3481642240833
...

assert/deepequal-object.js
assert/deepequal-object.js method="deepEqual" strict=0 size=100 n=5000:
1,053.1950937538475
assert/deepequal-object.js method="notDeepEqual" strict=0 size=100 n=5000:
9,734.193251965213
...
```

It is possible to execute more groups by adding extra process arguments.

```
$ node benchmark/run.js assert async_hooks
```

Filtering benchmarks

`benchmark/run.js` and `benchmark/compare.js` have `--filter pattern` and `--exclude pattern` options, which can be used to run a subset of benchmarks or to exclude specific benchmarks from the execution, respectively.

```
$ node benchmark/run.js --filter "deepequal-b" assert

assert/deepequal-buffer.js
assert/deepequal-buffer.js method="deepEqual" strict=0 len=100 n=20000:
773,200.4995493788
assert/deepequal-buffer.js method="notDeepEqual" strict=0 len=100 n=20000:
964,411.712953848

$ node benchmark/run.js --exclude "deepequal-b" assert

assert/deepequal-map.js
assert/deepequal-map.js method="deepEqual_primitiveOnly" strict=0 len=500 n=500:
20,445.06368453332
assert/deepequal-map.js method="deepEqual_objectOnly" strict=0 len=500 n=500:
1,393.3481642240833
...

assert/deepequal-object.js
assert/deepequal-object.js method="deepEqual" strict=0 size=100 n=5000:
1,053.1950937538475
assert/deepequal-object.js method="notDeepEqual" strict=0 size=100 n=5000:
9,734.193251965213
...
```

`--filter` and `--exclude` can be repeated to provide multiple patterns.

```
$ node benchmark/run.js --filter "deepequal-b" --filter "deepequal-m" assert

assert/deepequal-buffer.js
assert/deepequal-buffer.js method="deepEqual" strict=0 len=100 n=20000:
773,200.4995493788
assert/deepequal-buffer.js method="notDeepEqual" strict=0 len=100 n=20000:
964,411.712953848

assert/deepequal-map.js
assert/deepequal-map.js method="deepEqual_primitiveOnly" strict=0 len=500 n=500:
20,445.06368453332
assert/deepequal-map.js method="deepEqual_objectOnly" strict=0 len=500 n=500:
1,393.3481642240833

$ node benchmark/run.js --exclude "deepequal-b" --exclude "deepequal-m" assert

assert/deepequal-object.js
assert/deepequal-object.js method="deepEqual" strict=0 size=100 n=5000:
1,053.1950937538475
assert/deepequal-object.js method="notDeepEqual" strict=0 size=100 n=5000:
9,734.193251965213
...

assert/deepequal-prim-and-obj-big-array-set.js
```

```
assert/deepequal-prim-and-objs-big-array-set.js method="deepEqual_Array" strict=0
len=20000 n=25 primitive="string": 865.2977195251661
assert/deepequal-prim-and-objs-big-array-set.js method="notDeepEqual_Array"
strict=0 len=20000 n=25 primitive="string": 827.8297281403861
assert/deepequal-prim-and-objs-big-array-set.js method="deepEqual_Set" strict=0
len=20000 n=25 primitive="string": 28,826.618268696366
...
```

If `--filter` and `--exclude` are used together, `--filter` is applied first, and `--exclude` is applied on the result of `--filter`:

```
$ node benchmark/run.js --filter "bench-" process

process/bench-env.js
process/bench-env.js operation="get" n=1000000: 2,356,946.0770617095
process/bench-env.js operation="set" n=1000000: 1,295,176.3266261867
process/bench-env.js operation="enumerate" n=1000000: 24,592.32231990992
process/bench-env.js operation="query" n=1000000: 3,625,787.2150573144
process/bench-env.js operation="delete" n=1000000: 1,521,131.5742806569

process/bench-hrtime.js
process/bench-hrtime.js type="raw" n=1000000: 13,178,002.113936031
process/bench-hrtime.js type="diff" n=1000000: 11,585,435.712423025
process/bench-hrtime.js type="bigint" n=1000000: 13,342,884.703919787

$ node benchmark/run.js --filter "bench-" --exclude "hrtime" process

process/bench-env.js
process/bench-env.js operation="get" n=1000000: 2,356,946.0770617095
process/bench-env.js operation="set" n=1000000: 1,295,176.3266261867
process/bench-env.js operation="enumerate" n=1000000: 24,592.32231990992
process/bench-env.js operation="query" n=1000000: 3,625,787.2150573144
process/bench-env.js operation="delete" n=1000000: 1,521,131.5742806569
```

Comparing Node.js versions

To compare the effect of a new Node.js version use the `compare.js` tool. This will run each benchmark multiple times, making it possible to calculate statistics on the performance measures. To see how to use this script, run `node benchmark/compare.js`.

As an example on how to check for a possible performance improvement, the [#5134](#) pull request will be used as an example. This pull request *claims* to improve the performance of the `string_decoder` module.

First build two versions of Node.js, one from the master branch (here called `./node-master`) and another with the pull request applied (here called `./node-pr-5134`).

To run multiple compiled versions in parallel you need to copy the output of the build: `cp ./out/Release/node ./node-master`. Check out the following example:

```
$ git checkout master
$ ./configure && make -j4
```

```
$ cp ./out/Release/node ./node-master

$ git checkout pr-5134
$ ./configure && make -j4
$ cp ./out/Release/node ./node-pr-5134
```

The `compare.js` tool will then produce a csv file with the benchmark results.

```
$ node benchmark/compare.js --old ./node-master --new ./node-pr-5134 string_decoder
> compare-pr-5134.csv
```

Tips: there are some useful options of `benchmark/compare.js`. For example, if you want to compare the benchmark of a single script instead of a whole module, you can use the `--filter` option:

```
--new      ./new-node-binary  new node binary (required)
--old      ./old-node-binary  old node binary (required)
--runs     30                 number of samples
--filter   pattern           string to filter benchmark scripts
--set      variable=value    set benchmark variable (can be repeated)
--no-progress                don't show benchmark progress indicator
```

For analysing the benchmark results, use [node-benchmark-compare](#) or the R script `benchmark/compare.R`.

```
$ node-benchmark-compare compare-pr-5134.csv # or cat compare-pr-5134.csv | Rscript
benchmark/compare.R

confidence improvement accuracy (*)      (**)      (***)
string_decoder/string-decoder.js n=2500000 chunkLen=16 inLen=128 encoding='ascii'
***      -3.76 %           ±1.36% ±1.82% ±2.40%
string_decoder/string-decoder.js n=2500000 chunkLen=16 inLen=128 encoding='utf8'
**       -0.81 %           ±0.53% ±0.71% ±0.93%
string_decoder/string-decoder.js n=2500000 chunkLen=16 inLen=32 encoding='ascii'
***      -2.70 %           ±0.83% ±1.11% ±1.45%
string_decoder/string-decoder.js n=2500000 chunkLen=16 inLen=32 encoding='base64-
ascii'          ***      -1.57 %           ±0.83% ±1.11% ±1.46%
...
```

In the output, *improvement* is the relative improvement of the new version, hopefully this is positive. *confidence* tells if there is enough statistical evidence to validate the *improvement*. If there is enough evidence then there will be at least one star (*), more stars is just better. **However if there are no stars, then don't make any conclusions based on the *improvement*.** Sometimes this is fine, for example if no improvements are expected, then there shouldn't be any stars.


A word of caution: Statistics is not a foolproof tool. If a benchmark shows a statistical significant difference, there is a 5% risk that this difference doesn't actually exist. For a single benchmark this is not an issue. But when considering 20 benchmarks it's normal that one of them will show significance, when it shouldn't. A possible solution is to instead consider at least two stars (**) as the threshold, in that case the risk is 1%. If three stars (***) is considered the risk is 0.1%. However this may require more runs to obtain (can be set with `--runs`).

For the statistically minded, the script performs an [independent/unpaired 2-group t-test](#), with the null hypothesis that the performance is the same for both versions. The confidence field will show a star if the p-value is less than 0.05.

The `compare.R` tool can additionally produce a box plot by using the `--plot filename` option. In this case there are 48 different benchmark combinations, and there may be a need to filter the csv file. This can be done while benchmarking using the `--set` parameter (e.g. `--set encoding=ascii`) or by filtering results afterwards using tools such as `sed` or `grep`. In the `sed` case be sure to keep the first line since that contains the header information.

```
$ cat compare-pr-5134.csv | sed '1p;/encoding="'"ascii'"'/!d' | Rscript
benchmark/compare.R --plot compare-plot.png

confidence improvement accuracy (*)      (**)      (***)
string_decoder/string-decoder.js n=2500000 chunkLen=16 inLen=128 encoding='ascii'
***      -3.76 %           ±1.36% ±1.82% ±2.40%
string_decoder/string-decoder.js n=2500000 chunkLen=16 inLen=32 encoding='ascii'
***      -2.70 %           ±0.83% ±1.11% ±1.45%
string_decoder/string-decoder.js n=2500000 chunkLen=16 inLen=4096 encoding='ascii'
***      -4.06 %           ±0.31% ±0.41% ±0.54%
string_decoder/string-decoder.js n=2500000 chunkLen=256 inLen=1024 encoding='ascii'
***      -1.42 %           ±0.58% ±0.77% ±1.01%
...
```

 compare tool boxplot

Comparing parameters

It can be useful to compare the performance for different parameters, for example to analyze the time complexity.

To do this use the `scatter.js` tool, this will run a benchmark multiple times and generate a csv with the results.

To see how to use this script, run `node benchmark/scatter.js`.

```
$ node benchmark/scatter.js benchmark/string_decoder/string-decoder.js > scatter.csv
```

After generating the csv, a comparison table can be created using the `scatter.R` tool. Even more useful it creates an actual scatter plot when using the `--plot filename` option.

```
$ cat scatter.csv | Rscript benchmark/scatter.R --xaxis chunkLen --category encoding
--plot scatter-plot.png --log

aggregating variable: inLen


chunkLen      encoding      rate confidence.interval
      16          ascii 1515855.1          334492.68
      16 base64-ascii  403527.2           89677.70
      16 base64-utf8   322352.8           70792.93
      16      utf16le 1714567.5          388439.81
      16          utf8 1100181.6          254141.32
```

64	ascii	3550402.0	661277.65
64	base64-ascii	1093660.3	229976.34
64	base64-utf8	997804.8	227238.04
64	utf16le	3372234.0	647274.88
64	utf8	1731941.2	360854.04
256	ascii	5033793.9	723354.30
256	base64-ascii	1447962.1	236625.96
256	base64-utf8	1357269.2	231045.70
256	utf16le	4039581.5	655483.16
256	utf8	1828672.9	360311.55
1024	ascii	5677592.7	624771.56
1024	base64-ascii	1494171.7	227302.34
1024	base64-utf8	1399218.9	224584.79
1024	utf16le	4157452.0	630416.28
1024	utf8	1824266.6	359628.52

Because the scatter plot can only show two variables (in this case *chunkLen* and *encoding*) the rest is aggregated. Sometimes aggregating is a problem, this can be solved by filtering. This can be done while benchmarking using the `--set` parameter (e.g. `--set encoding=ascii`) or by filtering results afterwards using tools such as `sed` or `grep` . In the `sed` case be sure to keep the first line since that contains the header information.

```
$ cat scatter.csv | sed -E 'lp;/([^\,]+, )\{3\}128,/!d' | Rscript benchmark/scatter.R -
-axis chunkLen --category encoding --plot scatter-plot.png --log
```

chunkLen	encoding	rate	confidence.interval
16	ascii	1302078.5	71692.27
16	base64-ascii	338669.1	15159.54
16	base64-utf8	281904.2	20326.75
16	utf16le	1381515.5	58533.61
16	utf8	831183.2	33631.01
64	ascii	4363402.8	224030.00
64	base64-ascii	1036825.9	48644.72
64	base64-utf8	780059.3	60994.98
64	utf16le	3900749.5	158366.84
64	utf8	1723710.6	80665.65
256	ascii	8472896.1	511822.51
256	base64-ascii	2215884.6	104347.53
256	base64-utf8	1996230.3	131778.47
256	utf16le	5824147.6	234550.82
256	utf8	2019428.8	100913.36
1024	ascii	8340189.4	598855.08
1024	base64-ascii	2201316.2	111777.68
1024	base64-utf8	2002272.9	128843.11
1024	utf16le	5789281.7	240642.77
1024	utf8	2025551.2	81770.69

 compare tool boxplot

Running benchmarks on the CI

To see the performance impact of a pull request by running benchmarks on the CI, check out [How to: Running core benchmarks on Node.js CI](#).

Creating a benchmark

Basics of a benchmark

All benchmarks use the `require('../common.js')` module. This contains the `createBenchmark(main, configs[, options])` method which will setup the benchmark.

The arguments of `createBenchmark` are:

- `main` {Function} The benchmark function, where the code running operations and controlling timers should go
- `configs` {Object} The benchmark parameters. `createBenchmark` will run all possible combinations of these parameters, unless specified otherwise. Each configuration is a property with an array of possible values. The configuration values can only be strings or numbers.
- `options` {Object} The benchmark options. At the moment only the `flags` option for specifying command line flags is supported.

`createBenchmark` returns a `bench` object, which is used for timing the runtime of the benchmark. Run `bench.start()` after the initialization and `bench.end(n)` when the benchmark is done. `n` is the number of operations performed in the benchmark.

The benchmark script will be run twice:

The first pass will configure the benchmark with the combination of parameters specified in `configs`, and WILL NOT run the `main` function. In this pass, no flags except the ones directly passed via commands when running the benchmarks will be used.

In the second pass, the `main` function will be run, and the process will be launched with:

- The flags passed into `createBenchmark` (the third argument)
- The flags in the command passed when the benchmark was run

Beware that any code outside the `main` function will be run twice in different processes. This could be troublesome if the code outside the `main` function has side effects. In general, prefer putting the code inside the `main` function if it's more than just declaration.

```
'use strict';
const common = require('../common.js');
const { SlowBuffer } = require('buffer');

const configs = {
  // Number of operations, specified here so they show up in the report.
  // Most benchmarks just use one value for all runs.
  n: [1024],
  type: ['fast', 'slow'], // Custom configurations
  size: [16, 128, 1024] // Custom configurations
};

const options = {
  // Add --expose-internals in order to require internal modules in main
```

```

    flags: ['--zero-fill-buffers']
  };

  // `main` and `configs` are required, `options` is optional.
  const bench = common.createBenchmark(main, configs, options);

  // Any code outside main will be run twice,
  // in different processes, with different command line arguments.

  function main(conf) {
    // Only flags that have been passed to createBenchmark
    // earlier when main is run will be in effect.
    // In order to benchmark the internal modules, require them here. For example:
    // const URL = require('internal/url').URL

    // Start the timer
    bench.start();

    // Do operations here
    const BufferConstructor = conf.type === 'fast' ? Buffer : SlowBuffer;

    for (let i = 0; i < conf.n; i++) {
      new BufferConstructor(conf.size);
    }

    // End the timer, pass in the number of operations
    bench.end(conf.n);
  }

```

Creating an HTTP benchmark

The `bench` object returned by `createBenchmark` implements `http(options, callback)` method. It can be used to run external tool to benchmark HTTP servers.

```

'use strict';

const common = require('../common.js');

const bench = common.createBenchmark(main, {
  kb: [64, 128, 256, 1024],
  connections: [100, 500],
  duration: 5
});

function main(conf) {
  const http = require('http');
  const len = conf.kb * 1024;
  const chunk = Buffer.alloc(len, 'x');
  const server = http.createServer((req, res) => {
    res.end(chunk);
  });
}

```

```
server.listen(common.PORT, () => {
  bench.http({
    connections: conf.connections,
  }, () => {
    server.close();
  });
});
}
```

Supported options keys are:

- `port` - defaults to `common.PORT`
- `path` - defaults to `/`
- `connections` - number of concurrent connections to use, defaults to 100
- `duration` - duration of the benchmark in seconds, defaults to 10
- `benchmarker` - benchmarker to use, defaults to the first available http benchmarker