

tmux

This plugin provides aliases for tmux, the terminal multiplexer. To use it add `tmux` to the `plugins` array in your `zshrc` file.

```
plugins=(... tmux)
```

The plugin also supports the following:

- determines if tmux is installed or not, if not, prompts user to install tmux
- determines if the terminal supports the 256 colors or not, sets the appropriate configuration variable
- sets the correct local config file to use

Aliases

Alias	Command	Description
<code>ta</code>	<code>tmux attach -t</code>	Attach new tmux session to already running named session
<code>tad</code>	<code>tmux attach -d -t</code>	Detach named tmux session
<code>ts</code>	<code>tmux new-session -s</code>	Create a new named tmux session
<code>tl</code>	<code>tmux list-sessions</code>	Displays a list of running tmux sessions
<code>tksv</code>	<code>tmux kill-server</code>	Terminate all running tmux sessions
<code>tkss</code>	<code>tmux kill-session -t</code>	Terminate named running tmux session
<code>tmux</code>	<code>_zsh_tmux_plugin_run</code>	Start a new tmux session
<code>tmuxconf</code>	<code>\$EDITOR</code> <code>\$ZSH_TMUX_CONFIG</code>	Open <code>.tmux.conf</code> file with an editor

Configuration Variables

Variable	Description
<code>ZSH_TMUX_AUTOSTART</code>	Automatically starts tmux (default: false)
<code>ZSH_TMUX_AUTOSTART_ONCE</code>	Autostart only if tmux hasn't been started previously (default: true)
<code>ZSH_TMUX_AUTOCONNECT</code>	Automatically connect to a previous session if it exits (default: true)
<code>ZSH_TMUX_AUTOQUIT</code>	Automatically closes terminal once tmux exits (default: <code>ZSH_TMUX_AUTOSTART</code>)
<code>ZSH_TMUX_FIXTERM</code>	Sets <code>\$TERM</code> to 256-color term or not based on current terminal support
<code>ZSH_TMUX_ITERM2</code>	Sets the <code>-CC</code> option for iTerm2 tmux integration (default: false)
<code>ZSH_TMUX_FIXTERM_WITHOUT_256COLOR</code>	Sets <code>\$TERM</code> for non 256-color terminals (default: <code>screen</code>)

Variable	Description
ZSH_TMUX_FIXTERM_WITH_256COLOR	Use for 256-color terminals (default: <code>screen-256color</code>)
ZSH_TMUX_CONFIG	Set the configuration path (default: <code>\$HOME/.tmux.conf</code>)
ZSH_TMUX_UNICODE	Set <code>tmux -u</code> option to support unicode
ZSH_TMUX_DEFAULT_SESSION_NAME	Set <code>tmux</code> default session name when autostart is enabled