

# FE\_READ\_BER

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\[linux-master] [Documentation] [userspace-api] [media] [dvb] fe-read-ber.rst, line 2)**

Unknown directive type "c:namespace".

```
.. c:namespace:: DTV.fe
```

## Name

FE\_READ\_BER

**Attention!**

This ioctl is deprecated.

## Synopsis

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\[linux-master] [Documentation] [userspace-api] [media] [dvb] fe-read-ber.rst, line 20)**

Unknown directive type "c:macro".

```
.. c:macro:: FE_READ_BER
```

```
int ioctl(int fd, FE_READ_BER, uint32_t *ber)
```

## Arguments

fd

File descriptor returned by `c:func:open()`.

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\[linux-master] [Documentation] [userspace-api] [media] [dvb] fe-read-ber.rst, line 28); [backlink](#)**

Unknown interpreted text role "c:func".

ber

The bit error rate is stored into \*ber.

## Description

This ioctl call returns the bit error rate for the signal currently received/demodulated by the front-end. For this command, read-only access to the device is sufficient.

## Return Value

On success 0 is returned.

On error -1 is returned, and the `errno` variable is set appropriately.

Generic error codes are described at the [ref:Generic Error Codes <gen-errors>](#) chapter.

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\[linux-master] [Documentation] [userspace-api] [media] [dvb] fe-read-ber.rst, line 48); [backlink](#)**

Unknown interpreted text role "ref".

