

ioctl VIDIOC_G_AUDIO, VIDIOC_S_AUDIO

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 2)

Unknown directive type "c:namespace".

```
.. c:namespace:: V4L
```

Name

VIDIOC_G_AUDIO - VIDIOC_S_AUDIO - Query or select the current audio input and its attributes

Synopsis

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 18)

Unknown directive type "c:macro".

```
.. c:macro:: VIDIOC_G_AUDIO
```

```
int ioctl(int fd, VIDIOC_G_AUDIO, struct v4l2_audio *argp)
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 22)

Unknown directive type "c:macro".

```
.. c:macro:: VIDIOC_S_AUDIO
```

```
int ioctl(int fd, VIDIOC_S_AUDIO, const struct v4l2_audio *argp)
```

Arguments

fd

File descriptor returned by `c:func:open()`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 30); [backlink](#)

Unknown interpreted text role "c:func".

argp

Pointer to struct `c:type:v4l2_audio`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 33); [backlink](#)

Unknown interpreted text role "c:type".

Description

To query the current audio input applications zero out the `reserved` array of a struct `c:type:v4l2_audio` and call the `ref:VIDIOC_G_AUDIO <VIDIOC_G_AUDIO>` `ioctl` with a pointer to this structure. Drivers fill the rest of the structure or return an `EINVAL` error code when the device has no audio inputs, or none which combine with the current video input.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 38); [backlink](#)

Unknown interpreted text role "c:type".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 38); [backlink](#)

Unknown interpreted text role "ref".

Audio inputs have one writable property, the audio mode. To select the current audio input *and* change the audio mode, applications initialize the `index` and `mode` fields, and the `reserved` array of a struct `c:type:'v4l2_audio'` structure and call the `ref:'VIDIOC_S_AUDIO <VIDIOC_G_AUDIO>'` ioctl. Drivers may switch to a different audio mode if the request cannot be satisfied. However, this is a write-only ioctl, it does not return the actual new audio mode.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 44); [backlink](#)

Unknown interpreted text role "c:type".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 44); [backlink](#)

Unknown interpreted text role "ref".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 52)

Unknown directive type "tabularcolumns".

```
.. tabularcolumns:: |p{4.4cm}|p{4.4cm}|p{8.5cm}|
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 54)

Unknown directive type "c:type".

```
.. c:type:: v4l2_audio
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 56)

Unknown directive type "flat-table".

```
.. flat-table:: struct v4l2_audio
   :header-rows: 0
   :stub-columns: 0
   :widths:      1 1 2

   * - u32
     - ``index``
     - Identifies the audio input, set by the driver or application.
   * - u8
     - ``name`` [32]
     - Name of the audio input, a NUL-terminated ASCII string, for
       example: "Line In". This information is intended for the user,
       preferably the connector label on the device itself.
   * - u32
     - ``capability``
     - Audio capability flags, see :ref:`audio-capability`.
   * - u32
```

- ``mode``
- Audio mode flags set by drivers and applications (on :ref:`VIDIOC_S_AUDIO` <VIDIOC_G_AUDIO>` ioctl), see :ref:`audio-mode`.
- * - u32
- ``reserved``\ [2]
- Reserved for future extensions. Drivers and applications must set the array to zero.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 82)

Unknown directive type "tabularcolumns".

```
.. tabularcolumns:: |p{6.6cm}|p{2.2cm}|p{8.5cm}|
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 86)

Unknown directive type "flat-table".

```
.. flat-table:: Audio Capability Flags
   :header-rows: 0
   :stub-columns: 0
   :widths:      3 1 4

   * - ``V4L2_AUDCAP_STEREO``
     - 0x00001
     - This is a stereo input. The flag is intended to automatically
       disable stereo recording etc. when the signal is always monaural.
       The API provides no means to detect if stereo is *received*,
       unless the audio input belongs to a tuner.
   * - ``V4L2_AUDCAP_AVL``
     - 0x00002
     - Automatic Volume Level mode is supported.
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 102)

Unknown directive type "tabularcolumns".

```
.. tabularcolumns:: |p{6.6cm}|p{2.2cm}|p{8.5cm}|
```

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-api) (media) (v4l)vidioc-g-audio.rst, line 106)

Unknown directive type "flat-table".

```
.. flat-table:: Audio Mode Flags
   :header-rows: 0
   :stub-columns: 0
   :widths:      3 1 4

   * - ``V4L2_AUDMODE_AVL``
     - 0x00001
     - AVL mode is on.
```

Return Value

On success 0 is returned, on error -1 and the `errno` variable is set appropriately. The generic error codes are described at the :ref:`Generic Error Codes` <gen-errors>` chapter.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master) (Documentation) (userspace-

[api\) \(media\) \(v4l\)vidioc-g-audio.rst, line 118](#); [backlink](#)

Unknown interpreted text role "ref".

EINVAL

No audio inputs combine with the current video input, or the number of the selected audio input is out of bounds or it does not combine.