tmux

This plugin provides aliases for tmux, the terminal multiplexer. To use it add tmux to the plugins array in your zshrc file.

```
plugins=(... tmux)
```

The plugin also supports the following:

- determines if tmux is installed or not, if not, prompts user to install tmux
- determines if the terminal supports the 256 colors or not, sets the appropriate configuration variable
- sets the correct local config file to use

Aliases

Alias	Command	Description
ta	tmux attach -t	Attach new tmux session to already running named session
tad	tmux attach -d -t	Detach named tmux session
ts	tmux new-session -s	Create a new named tmux session
tl	tmux list-sessions	Displays a list of running tmux sessions
tksv	tmux kill-server	Terminate all running tmux sessions
tkss	tmux kill-session -t	Terminate named running tmux session
tmux	_zsh_tmux_plugin_run	Start a new tmux session
tmuxconf	\$EDITOR \$ZSH_TMUX_CONFIG	Open .tmux.conf file with an editor

Configuration Variables

Variable	Description	
ZSH_TMUX_AUTOSTART	Automatically starts tmux (default: false)	
ZSH_TMUX_AUTOSTART_ONCE	Autostart only if tmux hasn't been started previously (default: true)	
ZSH_TMUX_AUTOCONNECT	Automatically connect to a previous session if it exits (default: true)	
ZSH_TMUX_AUTOQUIT	Automatically closes terminal once tmux exits (default: ZSH_TMUX_AUTOSTART)	
ZSH_TMUX_FIXTERM	Sets \$TERM to 256-color term or not based on current terminal support	
ZSH_TMUX_ITERM2	Sets the -cc option for iTerm2 tmux integration (default: false)	
ZSH_TMUX_FIXTERM_WITHOUT_256COLOR	STERM to use for non 256-color terminals (default: screen)	
ZSH_TMUX_FIXTERM_WITH_256COLOR	\$TERM to use for 256-color terminals (default: screen-256color	
ZSH_TMUX_CONFIG	Set the configuration path (default: \$HOME/.tmux.conf)	

ZSH_TMUX_UNICODE	Set tmux -u option to support unicode
ZSH_TMUX_DEFAULT_SESSION_NAME	Set tmux default session name when autostart is enabled