## **Background color**

Similar to the contextual text color classes, set the background of an element to any contextual class. Background utilities **do not set** color , so in some cases you'll want to use .text-\* [color utilities]({{< docsref "/utilities/colors" >}}).

```
{{< example >}} {{< colors.inline >}} {{- range (index $.Site.Data "theme-colors") }}
.bg-{{ .name }}
{{- end -}} {{< /colors.inline >}}
.bg-body
.bg-white
.bg-transparent
{{< /example >}}
```

# **Background gradient**

By adding a .bg-gradient class, a linear gradient is added as background image to the backgrounds. This gradient starts with a semi-transparent white which fades out to the bottom.

```
Do you need a gradient in your custom CSS? Just add background-image: var(--bs-gradient); .

{{< markdown >}} {{< colors.inline >}} {{- range (index $.Site.Data "theme-colors") }}

.bg-{{ .name }}.bg-gradient

{{- end -}} {{< /colors.inline >}} {{< /markdown >}}
```

## **Opacity**

Added in v5.1.0

As of v5.1.0, background-color utilities are generated with Sass using CSS variables. This allows for real-time color changes without compilation and dynamic alpha transparency changes.

#### How it works

Consider our default .bg-success utility.

```
.bg-success {
   --bs-bg-opacity: 1;
   background-color: rgba(var(--bs-success-rgb), var(--bs-bg-opacity)) !important;
}
```

We use an RGB version of our --bs-success (with the value of 25, 135, 84) CSS variable and attached a second CSS variable, --bs-bg-opacity, for the alpha transparency (with a default value 1 thanks to a local CSS variable). That means anytime you use .bg-success now, your computed color value is rgba(25, 135, 84, 1). The local CSS variable inside each .bg-\* class avoids inheritance issues so nested instances of the utilities don't automatically have a modified alpha transparency.

## **Example**

```
To change that opacity, override --bs-bg-opacity via custom styles or inline styles. {{< example >}}
```

```
This is default success background
This is 50% opacity success background
{{< /example >}}
Or, choose from any of the .bg-opacity utilities:
{{< example >}}
This is default success background
This is 75% opacity success background
This is 50% opacity success background
This is 25% opacity success background
This is 10% opacity success background
{{< /example >}}
```

### Sass

In addition to the following Sass functionality, consider reading about our included [CSS custom properties]({{< docsref "/customize/css-variables" >}}) (aka CSS variables) for colors and more.

### **Variables**

Most background-color utilities are generated by our theme colors, reassigned from our generic color palette variables.

```
{{< scss-docs name="color-variables" file="scss/_variables.scss" >}}

{{< scss-docs name="theme-color-variables" file="scss/_variables.scss" >}}

{{< scss-docs name="variable-gradient" file="scss/_variables.scss" >}}

Grayscale colors are also available, but only a subset are used to generate any utilities.

{{< scss-docs name="gray-color-variables" file="scss/_variables.scss" >}}
```

#### Map

Theme colors are then put into a Sass map so we can loop over them to generate our utilities, component modifiers, and more.

```
{{< scss-docs name="theme-colors-map" file="scss/_variables.scss" >}}
```

Grayscale colors are also available as a Sass map. This map is not used to generate any utilities.

```
{{< scss-docs name="gray-colors-map" file="scss/_variables.scss" >}}
```

RGB colors are generated from a separate Sass map:

```
\{\{< scss-docs\ name="theme-colors-rgb"\ file="scss/\_variables.scss"\ >\}\}
```

And background color opacities build on that with their own map that's consumed by the utilities API:

```
{{< scss-docs name="utilities-bg-colors" file="scss/_variables.scss" >}}
```

#### **Mixins**

No mixins are used to generate our background utilities, but we do have some additional mixins for other situations where you'd like to create your own gradients.

```
{{< scss-docs name="gradient-bg-mixin" file="scss/mixins/_gradients.scss" >}}
{{< scss-docs name="gradient-mixins" file="scss/mixins/_gradients.scss" >}}
```

### **Utilities API**

Background utilities are declared in our utilities API in  $scss\_utilities.scss$ . [Learn how to use the utilities API.]({{< docsref "/utilities/api#using-the-api" >}})

{{< scss-docs name="utils-bg-color" file="scss/\_utilities.scss" >}}