Pre-trained Models

We provide a large collection of baselines and checkpoints for NLP pre-trained models.

How to Load Pretrained Models

How to Initialize from Checkpoint

Note: TF-HUB/Savedmodel is the preferred way to distribute models as it is self-contained. Please consider using TF-HUB for finetuning tasks first.

If you use the <u>NLP training library</u>, you can specify the checkpoint path link directly when launching your job. For example, to initialize the model from the checkpoint, you can specify --

```
params_override=task.init_checkpoint=PATH_TO_INIT_CKPT as:
```

```
python3 train.py \
--params_override=task.init_checkpoint=PATH_TO_INIT_CKPT
```

How to load TF-HUB SavedModel

Finetuning tasks such as question answering (SQuAD) and sentence prediction (GLUE) support loading a model from TF-HUB. These built-in tasks support a specific task.hub_module_url parameter. To set this parameter, replace --params_override=task.init_checkpoint=... with --params_override=task.hub_module_url=TF_HUB_URL , like below:

```
python3 train.py \
   --params_override=task.hub_module_url=https://tfhub.dev/tensorflow/bert_en_uncased_L-
12_H-768_A-12/3
```

BERT

Public BERT pre-trained models released by the BERT authors.

We released both checkpoints and tf.hub modules as the pretrained models for fine-tuning. They are TF 2.x compatible and are converted from the checkpoints released in TF 1.x official BERT repository google-research/bert in order to keep consistent with BERT paper.

Checkpoints

Model	Configuration	Training Data	Checkpoint & Vocabulary	TF-HUB SavedModels
BERT-base uncased	uncased_L-12_H-	Wiki +	uncased L-12 H-	BERT-Base, Uncased
English	768_A-12	Books	768 A-12	
BERT-base cased English	cased_L-12_H- 768_A-12	Wiki + Books	<u>cased L-12 H-</u> <u>768 A-12</u>	BERT-Base, Cased
BERT-large uncased	uncased_L-24_H-	Wiki +	uncased L-24 H-	BERT-Large, Uncased
English	1024_A-16	Books	1024 A-16	
BERT-large cased	cased_L-24_H-	Wiki +	cased L-24 H-	BERT-Large, Cased
English	1024_A-16	Books	1024 A-16	

BERT-large, Uncased	wwm_uncased_L-	Wiki +	wwm uncased L-	BERT-Large, Uncased (Whole Word Masking)
(Whole Word Masking)	24_H-1024_A-16	Books	24 H-1024 A-16	
BERT-large, Cased	wwm_cased_L-	Wiki +	<u>wwm_cased_L-</u>	BERT-Large, Cased (Whole Word Masking)
(Whole Word Masking)	24_H-1024_A-16	Books	<u>24_H-1024_A-16</u>	
BERT-base MultiLingual	multi_cased_L-	Wiki +	multi cased L-	BERT-Base,
	12_H-768_A-12	Books	12 H-768 A-12	Multilingual Cased
BERT-base Chinese	chinese_L-12_H- 768_A-12	Wiki + Books	<u>chinese L-12 H-</u> <u>768 A-12</u>	BERT-Base, Chinese

You may explore more in the TF-Hub BERT collection: https://tfhub.dev/google/collections/bert/1

BERT variants

We also have pretrained BERT models with variants in both network architecture and training methodologies. These models achieve higher downstream accuracy scores.

Model	Configuration	Training Data	TF-HUB SavedModels	Comment
BERT-base talking heads + ggelu	uncased_L- 12_H-768_A-12	Wiki + Books	talkheads ggelu base	BERT-base trained with talking heads attention and gated GeLU.
BERT-large talking heads + ggelu	uncased_L- 24_H-1024_A- 16	Wiki + Books	talkheads ggelu large	BERT-large trained with talking heads attention and gated GeLU.
LAMBERT-large uncased English	uncased_L- 24_H-1024_A- 16	Wiki + Books	<u>lambert</u>	BERT trained with LAMB and techniques from RoBERTa.

ALBERT

The academic paper that describes ALBERT in detail and provides full results on a number of tasks can be found here: https://arxiv.org/abs/1909.11942.

We released both checkpoints and tf.hub modules as the pretrained models for fine-tuning. They are TF 2.x compatible and are converted from the ALBERT v2 checkpoints released in the TF 1.x official ALBERT repository google-research/albert in order to be consistent with the ALBERT paper.

Our current released checkpoints are exactly the same as the TF 1.x official ALBERT repository.

Checkpoints

Model	Training Data	Checkpoint & Vocabulary	TF-HUB SavedModels
ALBERT-base English	Wiki + Books	ALBERT Base	https://tfhub.dev/tensorflow/albert_en_base/3
ALBERT-large	Wiki +	ALBERT Large	https://tfhub.dev/tensorflow/albert en large/3

English	Books		
ALBERT-xlarge English	Wiki + Books	ALBERT XLarge	https://tfhub.dev/tensorflow/albert_en_xlarge/3
ALBERT-xxlarge English	Wiki + Books	ALBERT XXLarge	https://tfhub.dev/tensorflow/albert_en_xxlarge/3

ELECTRA

ELECTRA, which stands for " Efficiently Learning an Encoder that Classifies Token Replacements Accurately", is an efficient language pretraining method. In a nutshell, ELECTRA contains two transformer models, one called "generator" and the other called "discriminator". Given a masked sequence, the generator replaces words in masked positions with randomly generated words. The discriminator then takes the corrupted sentence as input and predicts whether each word is replaced by the generator or not. During the pretraining stage, ELECTRA jointly learns two models (i.e., trains the generator using masked language modeling (MLM) task, and trains the discriminator using replaced token detection (RTD) task). At the fine-tuning stage, the generator is discard and the discriminator is used for downstream tasks (e.g., GLUE and SQuAD tasks).

Checkpoints

The checkpoints are re-trained with the Electra code in this repository.

Model	Training Data	Checkpoint & Vocabulary
ELECTRA-small English	Wiki + Books	ELECTRA Small: the vocabulary is the same as BERT uncased English.
ELECTRA-base English	Wiki + Books	ELECTRA Base: the vocabulary is the same as BERT uncased English.