

NavMenu

Menu that provides navigation for your website.

Top bar

Top bar NavMenu can be used in a variety of scenarios.

By default Menu is vertical, but you can change it to horizontal by setting the mode prop to 'horizontal'. In addition, you can use the submenu component to create a second level menu. Menu provides background-color, text-color and active-text-color to customize the colors.

```
<el-menu :default-active="activeIndex" class="el-menu-demo" mode="horizontal" @select="handleSelect">
  <el-menu-item index="1">Processing Center</el-menu-item>
  <el-submenu index="2">
    <template slot="title">Workspace</template>
    <el-menu-item index="2-1">item one</el-menu-item>
    <el-menu-item index="2-2">item two</el-menu-item>
    <el-menu-item index="2-3">item three</el-menu-item>
    <el-submenu index="2-4">
      <template slot="title">item four</template>
      <el-menu-item index="2-4-1">item one</el-menu-item>
      <el-menu-item index="2-4-2">item two</el-menu-item>
      <el-menu-item index="2-4-3">item three</el-menu-item>
    </el-submenu>
  </el-submenu>
  <el-menu-item index="3" disabled>Info</el-menu-item>
  <el-menu-item index="4"><a href="https://www.ele.me" target="_blank">Orders</a></el-menu-item>
</el-menu>
<div class="line"></div>
<el-menu
  :default-active="activeIndex2"
  class="el-menu-demo"
  mode="horizontal"
  @select="handleSelect"
  background-color="#545c64"
  text-color="#fff"
  active-text-color="#ffd04b">
  <el-menu-item index="1">Processing Center</el-menu-item>
  <el-submenu index="2">
    <template slot="title">Workspace</template>
    <el-menu-item index="2-1">item one</el-menu-item>
    <el-menu-item index="2-2">item two</el-menu-item>
    <el-menu-item index="2-3">item three</el-menu-item>
    <el-submenu index="2-4">
      <template slot="title">item four</template>
```

```

      <el-menu-item index="2-4-1">item one</el-menu-item>
      <el-menu-item index="2-4-2">item two</el-menu-item>
      <el-menu-item index="2-4-3">item three</el-menu-item>
    </el-submenu>
  </el-submenu>
  <el-menu-item index="3" disabled>Info</el-menu-item>
  <el-menu-item index="4"><a href="https://www.ele.me" target="_blank">Orders</a></el-menu-item>
</el-menu>

<script>
  export default {
    data() {
      return {
        activeIndex: '1',
        activeIndex2: '1'
      };
    },
    methods: {
      handleSelect(key, keyPath) {
        console.log(key, keyPath);
      }
    }
  }
</script>
:::

```

Side bar

Vertical NavMenu with sub-menus.

:::demo You can use the el-menu-item-group component to create a menu group, and the name of the group is determined by the title prop or a named slot.

```

<el-row class="tac">
  <el-col :span="12">
    <h5>Default colors</h5>
    <el-menu
      default-active="2"
      class="el-menu-vertical-demo"
      @open="handleOpen"
      @close="handleClose">
      <el-submenu index="1">
        <template slot="title">
          <i class="el-icon-location"></i>
          <span>Navigator One</span>
        </template>

```

```

    <el-menu-item-group title="Group One">
      <el-menu-item index="1-1">item one</el-menu-item>
      <el-menu-item index="1-2">item one</el-menu-item>
    </el-menu-item-group>
    <el-menu-item-group title="Group Two">
      <el-menu-item index="1-3">item three</el-menu-item>
    </el-menu-item-group>
    <el-submenu index="1-4">
      <template slot="title">item four</template>
      <el-menu-item index="1-4-1">item one</el-menu-item>
    </el-submenu>
  </el-submenu>
  <el-menu-item index="2">
    <i class="el-icon-menu"></i>
    <span>Navigator Two</span>
  </el-menu-item>
  <el-menu-item index="3" disabled>
    <i class="el-icon-document"></i>
    <span>Navigator Three</span>
  </el-menu-item>
  <el-menu-item index="4">
    <i class="el-icon-setting"></i>
    <span>Navigator Four</span>
  </el-menu-item>
</el-menu>
</el-col>
<el-col :span="12">
  <h5>Custom colors</h5>
  <el-menu
    default-active="2"
    class="el-menu-vertical-demo"
    @open="handleOpen"
    @close="handleClose"
    background-color="#545c64"
    text-color="#fff"
    active-text-color="#ffd04b">
    <el-submenu index="1">
      <template slot="title">
        <i class="el-icon-location"></i>
        <span>Navigator One</span>
      </template>
      <el-menu-item-group title="Group One">
        <el-menu-item index="1-1">item one</el-menu-item>
        <el-menu-item index="1-2">item one</el-menu-item>
      </el-menu-item-group>
      <el-menu-item-group title="Group Two">

```

```

        <el-menu-item index="1-3">item three</el-menu-item>
      </el-menu-item-group>
      <el-submenu index="1-4">
        <template slot="title">item four</template>
        <el-menu-item index="1-4-1">item one</el-menu-item>
      </el-submenu>
    </el-submenu>
    <el-menu-item index="2">
      <i class="el-icon-menu"></i>
      <span>Navigator Two</span>
    </el-menu-item>
    <el-menu-item index="3" disabled>
      <i class="el-icon-document"></i>
      <span>Navigator Three</span>
    </el-menu-item>
    <el-menu-item index="4">
      <i class="el-icon-setting"></i>
      <span>Navigator Four</span>
    </el-menu-item>
  </el-menu>
</el-col>
</el-row>

```

```

<script>
  export default {
    methods: {
      handleOpen(key, keyPath) {
        console.log(key, keyPath);
      },
      handleClose(key, keyPath) {
        console.log(key, keyPath);
      }
    }
  }
</script>

```

```

:::

```

Collapse

Vertical NavMenu could be collapsed.

```

<el-radio-group v-model="isCollapse" style="margin-bottom: 20px;">
  <el-radio-button :label="false">expand</el-radio-button>
  <el-radio-button :label="true">collapse</el-radio-button>
</el-radio-group>
<el-menu default-active="2" class="el-menu-vertical-demo" @open="handleOpen" @close="handleClose">

```

```

<el-submenu index="1">
  <template slot="title">
    <i class="el-icon-location"></i>
    <span slot="title">Navigator One</span>
  </template>
  <el-menu-item-group>
    <span slot="title">Group One</span>
    <el-menu-item index="1-1">item one</el-menu-item>
    <el-menu-item index="1-2">item two</el-menu-item>
  </el-menu-item-group>
  <el-menu-item-group title="Group Two">
    <el-menu-item index="1-3">item three</el-menu-item>
  </el-menu-item-group>
  <el-submenu index="1-4">
    <span slot="title">item four</span>
    <el-menu-item index="1-4-1">item one</el-menu-item>
  </el-submenu>
</el-submenu>
<el-menu-item index="2">
  <i class="el-icon-menu"></i>
  <span slot="title">Navigator Two</span>
</el-menu-item>
<el-menu-item index="3" disabled>
  <i class="el-icon-document"></i>
  <span slot="title">Navigator Three</span>
</el-menu-item>
<el-menu-item index="4">
  <i class="el-icon-setting"></i>
  <span slot="title">Navigator Four</span>
</el-menu-item>
</el-menu>

<style>
.el-menu-vertical-demo:not(.el-menu--collapse) {
  width: 200px;
  min-height: 400px;
}
</style>

<script>
export default {
  data() {
    return {
      isCollapse: true
    };
  },

```

```

    methods: {
      handleOpen(key, keyPath) {
        console.log(key, keyPath);
      },
      handleClose(key, keyPath) {
        console.log(key, keyPath);
      }
    }
  }
</script>

```

Menu Attribute

| Attribute | Description | Type | Accepted Values | Default |
|-------------------|---|---------|-----------------------|----------|
| mode | menu display mode | string | horizontal / vertical | vertical |
| collapse | whether the menu is collapsed (available only in vertical mode) | boolean | — | false |
| background-color | background color of Menu (hex format) | string | — | #ffff |
| text-color | text color of Menu (hex format) | string | — | #303133 |
| active-text-color | text color of currently active menu item (hex format) | string | — | #409EFF |
| default-active | index of currently active menu | string | — | — |

| Attribute | Description | Type | Accepted Values | Default |
|---------------------|---|---------|-----------------|---------|
| default-openeds | array that contains indexes of currently active sub-menus | Array | — | — |
| unique-opened | whether only one sub-menu can be active | boolean | — | false |
| menu-trigger | how sub-menus are triggered, only works when <code>mode</code> is 'horizontal' | string | hover / click | hover |
| router | whether <code>vue-router</code> mode is activated. If true, index will be used as 'path' to activate the route action | boolean | — | false |
| collapse-transition | whether to enable the collapse transition | boolean | — | true |

Menu Methods

| Methods Name | Description | Parameters |
|--------------|---------------------------|---------------------------------------|
| open | open a specific sub-menu | index: index of the sub-menu to open |
| close | close a specific sub-menu | index: index of the sub-menu to close |

Menu Events

| Event Name | Description | Parameters |
|------------|---|---|
| select | callback function when menu is activated | index: index of activated menu, indexPath: index path of activated menu |
| open | callback function when sub-menu expands | index: index of expanded sub-menu, indexPath: index path of expanded sub-menu |
| close | callback function when sub-menu collapses | index: index of collapsed sub-menu, indexPath: index path of collapsed sub-menu |

Menu-Item Events

| Event Name | Description | Parameters |
|------------|---|------------------------|
| click | callback function when menu-item is clicked | el: menu-item instance |

SubMenu Attribute

| Attribute | Description | Type | Accepted Values | Default |
|--------------|--------------------------------------|--------|-----------------|---------|
| index | unique identification | string | — | — |
| popper-class | custom class name for the popup menu | string | — | — |
| show-timeout | timeout before showing a sub-menu | number | — | 300 |
| hide-timeout | timeout before hiding a sub-menu | number | — | 300 |

| Attribute | Description | Type | Accepted Values | Default |
|-----------------------|--|---------|-----------------|---|
| disabled | whether the sub-menu is disabled | boolean | — | false |
| popper-append-to-body | whether to append the popup menu to body. If the positioning of the menu is wrong, you can try setting this prop | boolean | - | level one Submenu: true / other Submenus: false |

Menu-Item Attribute

| Attribute | Description | Type | Accepted Values | Default |
|-----------|-----------------------|-------------|-----------------|---------|
| index | unique identification | string/null | — | null |
| route | Vue Router object | object | — | — |
| disabled | whether disabled | boolean | — | false |

Menu-Group Attribute

| Attribute | Description | Type | Accepted Values | Default |
|-----------|-------------|--------|-----------------|---------|
| title | group title | string | — | — |