Arch Linux plugin

This plugin adds some aliases and functions to work with Arch Linux.

To use it, add `archlinux` to the plugins array in your zshrc file:

`plugins=(... archlinux)`

Features

Pacman

Alias	Command	Description
pacin	`sudo pacman -S`	Install packages from the repositories
pacins	`sudo pacman -U`	Install a package from a local file
pacinsd	`sudo pacman -S --asdeps`	Install packages as dependencies of another package
paclean	`sudo pacman -Sc`	Clean out old and unused caches and packages
pacloc	`pacman -Qi`	Display information about a package in the local database
paclocs	`pacman -Qs`	Search for packages in the local database
paclr	`sudo pacman -Scc`	Remove all files from the cache
paclsorphans	`sudo pacman -Qdt`	List all orphaned packages
pacmir	`sudo pacman -Syy`	Force refresh of all package lists after updating mirrorlist
pacre	`sudo pacman -R`	Remove packages, keeping its settings and dependencies
pacrem	`sudo pacman -Rns`	Remove packages, including its settings and dependencies
pacrep	`pacman -Si`	Display information about a package in the repositories
pacreps	`pacman -Ss`	Search for packages in the repositories
pacrmorphans	`sudo pacman -Rs $(pacman -Qtdq)`	Delete all orphaned packages
pacupd	`sudo pacman -Sy`	Update and refresh local package, ABS and AUR databases
pacupg	`sudo pacman -Syu`	Sync with repositories before upgrading packages
pacfileupg	`sudo pacman -Fy`	Download fresh package databases from the server
pacfiles	`pacman -F`	Search package file names for matching strings
pacls	`pacman -Ql`	List files in a package
pacown	`pacman -Qo`	Show which package owns a file

Alias	Command	Description
upgrade[1]	`sudo pacman -Syu`	Sync with repositories before upgrading packages

Function	Description
pacdisowned	List all disowned files in your system
paclist	List all explicitly installed packages with a description
pacmanallkeys	Get all keys for developers and trusted users
pacmansignkeys	Locally trust all keys passed as parameters
pacweb	Open the website of an ArchLinux package

Note: paclist used to print packages with a description which are (1) explicitly installed and (2) available for upgrade. Due to flawed scripting, it also printed all packages if no upgrades were available. Use `pacman -Que` instead.

AUR helpers

Aura

Alias	Command	Description
auclean	`sudo aura -Sc`	Clean out old and unused caches and packages
auclr	`sudo aura -Scc`	Remove all files from the cache
auin	`sudo aura -S`	Install packages from the repositories
aurin	`sudo aura -A`	Install packages from the repositories
auins	`sudo aura -U`	Install a package from a local file
auinsd	`sudo aura -S --asdeps`	Install packages as dependencies of another package (repositories only)
aurinsd	`sudo aura -A --asdeps`	Install packages as dependencies of another package (AUR only)
auloc	`aura -Qi`	Display information about a package in the local database
aulocs	`aura -Qs`	Search for packages in the local database
auls	`aura -Qql`	List all files owned by a given package
aulst	`aura -Qe`	List installed packages including from AUR (tagged as "local")
aumir	`sudo aura -Syy`	Force refresh of all package lists after updating mirrorlist
aurph	`sudo aura -Oj`	Remove orphans using aura
auown	`aura -Qqo`	Search for packages that own the specified file(s)

Alias	Command	Description
aure	`sudo aura -R`	Remove packages, keeping its settings and dependencies
aurem	`sudo aura -Rns`	Remove packages, including its settings and unneeded dependencies
aurep	`aura -Si`	Display information about a package in the repositories
aurrep	`aura -Ai`	Display information about a package from AUR
aureps	`aura -As --both`	Search for packages in the repositories and AUR
auras	`aura -As --both`	Same as above
auupd	`sudo aura -Sy`	Update and refresh local package, ABS and AUR databases
auupg	`sudo sh -c "aura -Syu && aura -Au"`	Sync with repositories before upgrading all packages (from AUR too)
ausu	`sudo sh -c "aura -Syu --no-confirm && aura -Au --no-confirm"`	Same as `auupg`, but without confirmation
upgrades	`sudo aura -Syu`	Sync with repositories before upgrading packages

Function	Description
auownloc *file*	Display information about a package that owns the specified file(s)
auownls *file*	List all files owned by a package that owns the specified file(s)

Pacaur

Alias	Command	Description
pacclean	`pacaur -Sc`	Clean out old and unused caches and packages
pacclr	`pacaur -Scc`	Remove all files from the cache
pain	`pacaur -S`	Install packages from the repositories
pains	`pacaur -U`	Install a package from a local file
painsd	`pacaur -S --asdeps`	Install packages as dependencies of another package
paloc	`pacaur -Qi`	Display information about a package in the local database
palocs	`pacaur -Qs`	Search for packages in the local database
palst	`pacaur -Qe`	List installed packages including from AUR (tagged as "local")

Alias	Command	Description
pamir	`pacaur -Syy`	Force refresh of all package lists after updating mirrorlist
paorph	`pacaur -Qtd`	Remove orphans using pacaur
pare	`pacaur -R`	Remove packages, keeping its settings and dependencies
parem	`pacaur -Rns`	Remove packages, including its settings and unneeded dependencies
parep	`pacaur -Si`	Display information about a package in the repositories
pareps	`pacaur -Ss`	Search for packages in the repositories
paupd	`pacaur -Sy`	Update and refresh local package, ABS and AUR databases
paupg	`pacaur -Syua`	Sync with repositories before upgrading all packages (from AUR too)
pasu	`pacaur -Syua --no-confirm`	Same as `paupg`, but without confirmation
upgrade[1]	`pacaur -Syu`	Sync with repositories before upgrading packages

Trizen

Alias	Command	Description
trconf	`trizen -C`	Fix all configuration files with vimdiff
trclean	`trizen -Sc`	Clean out old and unused caches and packages
trclr	`trizen -Scc`	Remove all files from the cache
trin	`trizen -S`	Install packages from the repositories
trins	`trizen -U`	Install a package from a local file
trinsd	`trizen -S --asdeps`	Install packages as dependencies of another package
trloc	`trizen -Qi`	Display information about a package in the local database
trlocs	`trizen -Qs`	Search for packages in the local database
trlst	`trizen -Qe`	List installed packages including from AUR (tagged as "local")
trmir	`trizen -Syy`	Force refresh of all package lists after updating mirrorlist
trorph	`trizen -Qtd`	Remove orphans using yaourt
trre	`trizen -R`	Remove packages, keeping its settings and dependencies
trrem	`trizen -Rns`	Remove packages, including its settings and unneeded dependencies

Alias	Command	Description
trrep	`trizen -Si`	Display information about a package in the repositories
trreps	`trizen -Ss`	Search for packages in the repositories
trupd	`trizen -Sy`	Update and refresh local package, ABS and AUR databases
trupg	`trizen -Syua`	Sync with repositories before upgrading all packages (from AUR too)
trsu	`trizen -Syua --no-confirm`	Same as `trupg`, but without confirmation
upgrade[1]	`trizen -Syu`	Sync with repositories before upgrading packages

Yay

Alias	Command	Description
yaconf	`yay -Pg`	Print current configuration
yaclean	`yay -Sc`	Clean out old and unused caches and packages
yaclr	`yay -Scc`	Remove all files from the cache
yain	`yay -S`	Install packages from the repositories
yains	`yay -U`	Install a package from a local file
yainsd	`yay -S --asdeps`	Install packages as dependencies of another package
yaloc	`yay -Qi`	Display information about a package in the local database
yalocs	`yay -Qs`	Search for packages in the local database
yalst	`yay -Qe`	List installed packages including from AUR (tagged as "local")
yamir	`yay -Syy`	Force refresh of all package lists after updating mirrorlist
yaorph	`yay -Qtd`	Remove orphans using yay
yare	`yay -R`	Remove packages, keeping its settings and dependencies
yarem	`yay -Rns`	Remove packages, including its settings and unneeded dependencies
yarep	`yay -Si`	Display information about a package in the repositories
yareps	`yay -Ss`	Search for packages in the repositories
yaupd	`yay -Sy`	Update and refresh local package, ABS and AUR databases
yaupg	`yay -Syu`	Sync with repositories before upgrading packages

Alias	Command	Description
yasu	`yay -Syu --no-confirm`	Same as `yaupg`, but without confirmation
upgrade[1]	`yay -Syu`	Sync with repositories before upgrading packages

---

[1] The `upgrade` alias is set for all package managers. Its value will depend on whether the package manager is installed, checked in the following order:

1. `yay`
2. `trizen`
3. `pacaur`
4. `aura`
5. `pacman`

Contributors

- Benjamin Boudreau - dreurmail@gmail.com
- Celso Miranda - contacto@celsomiranda.net
- ratijas (ivan tkachenko) - me@ratijas.tk
- Juraj Fiala - doctorjellyface@riseup.net
- KhasMek - Boushh@gmail.com
- Majora320 (Moses Miller) - Majora320@gmail.com
- Martin Putniorz - mputniorz@gmail.com
- MatthR3D - matthr3d@gmail.com
- ornicar - thibault.duplessis@gmail.com
- Ybalrid (Arthur Brainville) - ybalrid@ybalrid.info
- Jeff M. Hubbard - jeffmhubbard@gmail.com
- K. Harishankar(harishnkr) - hari2menon1234@gmail.com