

Support Vector Machines

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 10)

Unknown directive type "currentmodule".

```
.. currentmodule:: sklearn.svm
```

Support vector machines (SVMs) are a set of supervised learning methods used for [ref`classification <svm_classification>`](#), [ref`regression <svm_regression>`](#) and [ref`outliers detection <svm_outlier_detection>`](#).

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 12); [backlink](#)

Unknown interpreted text role "ref".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 12); [backlink](#)

Unknown interpreted text role "ref".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 12); [backlink](#)

Unknown interpreted text role "ref".

The advantages of support vector machines are:

- Effective in high dimensional spaces.
- Still effective in cases where number of dimensions is greater than the number of samples.
- Uses a subset of training points in the decision function (called support vectors), so it is also memory efficient.
- Versatile: different [ref`svm kernels`](#) can be specified for the decision function. Common kernels are provided, but it is also possible to specify custom kernels.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 27); [backlink](#)

Unknown interpreted text role "ref".

The disadvantages of support vector machines include:

- If the number of features is much greater than the number of samples, avoid over-fitting in choosing [ref`svm kernels`](#) and regularization term is crucial.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 33); [backlink](#)

Unknown interpreted text role "ref".

- SVMs do not directly provide probability estimates, these are calculated using an expensive five-fold cross-validation (see [ref`Scores and probabilities <scores_probabilities>`](#), below).

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 37); [backlink](#)

Unknown interpreted text role "ref".

The support vector machines in scikit-learn support both dense (`numpy.ndarray` and convertible to that by `numpy.asarray`) and

sparse (any `scipy.sparse`) sample vectors as input. However, to use an SVM to make predictions for sparse data, it must have been fit on such data. For optimal performance, use C-ordered `numpy.ndarray` (dense) or `scipy.sparse.csr_matrix` (sparse) with `dtype=float64`.

Classification

`:class:'SVC'`, `:class:'NuSVC'` and `:class:'LinearSVC'` are classes capable of performing binary and multi-class classification on a dataset.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 54); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 54); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 54); [backlink](#)

Unknown interpreted text role "class".

`:class:'SVC'` and `:class:'NuSVC'` are similar methods, but accept slightly different sets of parameters and have different mathematical formulations (see section [ref:'svm_mathematical_formulation'](#)). On the other hand, `:class:'LinearSVC'` is another (faster) implementation of Support Vector Classification for the case of a linear kernel. Note that `:class:'LinearSVC'` does not accept parameter `kernel`, as this is assumed to be linear. It also lacks some of the attributes of `:class:'SVC'` and `:class:'NuSVC'`, like `support_`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 63); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 63); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 63); [backlink](#)

Unknown interpreted text role "ref".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 63); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 63); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 63); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 63); [backlink](#)

Unknown interpreted text role "class".

As other classifiers, `:class:'SVC'`, `:class:'NuSVC'` and `:class:'LinearSVC'` take as input two arrays: an array X of shape $(n_samples, n_features)$ holding the training samples, and an array y of class labels (strings or integers), of shape $(n_samples)$:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 72); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 72); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 72); [backlink](#)

Unknown interpreted text role "class".

```
>>> from sklearn import svm
>>> X = [[0, 0], [1, 1]]
>>> y = [0, 1]
>>> clf = svm.SVC()
>>> clf.fit(X, y)
SVC()
```

After being fitted, the model can then be used to predict new values:

```
>>> clf.predict([[2., 2.]])
array([1])
```

SVMs decision function (detailed in the [ref:'svm_mathematical_formulation'](#)) depends on some subset of the training data, called the support vectors. Some properties of these support vectors can be found in attributes `support_vectors_`, `support_` and `n_support_`:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 90); [backlink](#)

Unknown interpreted text role "ref".

```
>>> # get support vectors
>>> clf.support_vectors_
array([[0., 0.],
       [1., 1.]])
>>> # get indices of support vectors
>>> clf.support_
array([0, 1]...)
>>> # get number of support vectors for each class
>>> clf.n_support_
array([1, 1]...)
```

Examples:

- [ref:'sphx_glr_auto_examples_svm_plot_separating_hyperplane.py'](#),

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 108); [backlink](#)

Unknown interpreted text role "ref".

- [ref:'sphx_glr_auto_examples_svm_plot_svm_nonlinear.py'](#)

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 109); [backlink](#)

Unknown interpreted text role "ref".

- [ref:'sphx_glr_auto_examples_svm_plot_svm_anova.py'](#),

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 110); [backlink](#)

Unknown interpreted text role "ref".

Multi-class classification

`:class:'SVC'` and `:class:'NuSVC'` implement the "one-versus-one" approach for multi-class classification. In total, $n_classes * (n_classes - 1) / 2$ classifiers are constructed and each one trains data from two classes. To provide a consistent interface with other classifiers, the `decision_function_shape` option allows to monotonically transform the results of the "one-versus-one" classifiers to a "one-vs-rest" decision function of shape $(n_samples, n_classes)$.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 117); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 117); [backlink](#)

Unknown interpreted text role "class".

```
>>> X = [[0], [1], [2], [3]]
>>> Y = [0, 1, 2, 3]
>>> clf = svm.SVC(decision_function_shape='ovo')
>>> clf.fit(X, Y)
SVC(decision_function_shape='ovo')
>>> dec = clf.decision_function([[1]])
>>> dec.shape[1] # 4 classes: 4*3/2 = 6
6
>>> clf.decision_function_shape = "ovr"
>>> dec = clf.decision_function([[1]])
>>> dec.shape[1] # 4 classes
4
```

On the other hand, `:class:'LinearSVC'` implements "one-vs-the-rest" multi-class strategy, thus training $n_classes$ models.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 139); [backlink](#)

Unknown interpreted text role "class".

```
>>> lin_clf = svm.LinearSVC()
>>> lin_clf.fit(X, Y)
LinearSVC()
>>> dec = lin_clf.decision_function([[1]])
>>> dec.shape[1]
4
```

See [ref:'svm_mathematical_formulation'](#) for a complete description of the decision function.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 149); [backlink](#)

Unknown interpreted text role "ref".

Note that the `:class:'LinearSVC'` also implements an alternative multi-class strategy, the so-called multi-class SVM formulated by Crammer and Singer [16], by using the option `multi_class='crammer_singer'`. In practice, one-vs-rest classification is usually preferred, since the results are mostly similar, but the runtime is significantly less.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 152); [backlink](#)

Unknown interpreted text role "class".

For "one-vs-rest" `:class:'LinearSVC'` the attributes `coef_` and `intercept_` have the shape $(n_classes, n_features)$ and $(n_classes,)$ respectively. Each row of the coefficients corresponds to one of the $n_classes$ "one-vs-rest" classifiers and similar

for the intercepts, in the order of the "one" class.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 158); [backlink](#)

Unknown interpreted text role "class".

In the case of "one-vs-one" `:class:'SVC'` and `:class:'NuSVC'`, the layout of the attributes is a little more involved. In the case of a linear kernel, the attributes `coef_` and `intercept_` have the shape $(n_classes * (n_classes - 1) / 2, n_features)$ and $(n_classes * (n_classes - 1) / 2)$ respectively. This is similar to the layout for `:class:'LinearSVC'` described above, with each row now corresponding to a binary classifier. The order for classes 0 to n is "0 vs 1", "0 vs 2", ... "0 vs n", "1 vs 2", "1 vs 3", "1 vs n", ... "n-1 vs n".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 164); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 164); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 164); [backlink](#)

Unknown interpreted text role "class".

The shape of `dual_coef_` is $(n_classes-1, n_SV)$ with a somewhat hard to grasp layout. The columns correspond to the support vectors involved in any of the $n_classes * (n_classes - 1) / 2$ "one-vs-one" classifiers. Each support vector v has a dual coefficient in each of the $n_classes - 1$ classifiers comparing the class of v against another class. Note that some, but not all, of these dual coefficients, may be zero. The $n_classes - 1$ entries in each column are these dual coefficients, ordered by the opposing class.

This might be clearer with an example: consider a three class problem with class 0 having three support vectors v_0^0, v_1^0, v_2^0 and class 1 and 2 having two support vectors v_0^1, v_1^1 and v_0^2, v_1^2 respectively. For each support vector v_j^i , there are two dual coefficients. Let's call the coefficient of support vector v_j^i in the classifier between classes i and k $\alpha_j^{i,k}$. Then `dual_coef_` looks like this:

$\alpha_0^{0,1}$	$\alpha_1^{0,1}$	$\alpha_2^{0,1}$	$\alpha_0^{1,0}$	$\alpha_1^{1,0}$	$\alpha_0^{2,0}$	$\alpha_1^{2,0}$
$\alpha_0^{0,2}$	$\alpha_1^{0,2}$	$\alpha_2^{0,2}$	$\alpha_0^{1,2}$	$\alpha_1^{1,2}$	$\alpha_0^{2,1}$	$\alpha_1^{2,1}$
Coefficients for SVs of class 0			Coefficients for SVs of class 1		Coefficients for SVs of class 2	

Examples:

- `ref`sphx_glr_auto_examples_svm_plot_iris_svc.py``,

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 204); [backlink](#)

Unknown interpreted text role "ref".

Scores and probabilities

The `decision_function` method of `:class:'SVC'` and `:class:'NuSVC'` gives per-class scores for each sample (or a single score per sample in the binary case). When the constructor option `probability` is set to `True`, class membership probability estimates (from the methods `predict_proba` and `predict_log_proba`) are enabled. In the binary case, the probabilities are calibrated using Platt scaling [9]; logistic regression on the SVM's scores, fit by an additional cross-validation on the training data. In the multiclass case, this is extended as per [10].

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 211); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 211); [backlink](#)

Unknown interpreted text role "class".

Note

The same probability calibration procedure is available for all estimators via the :class:`~sklearn.calibration.CalibratedClassifierCV` (see [ref`calibration`](#)). In the case of :class:`SVC` and :class:`NuSVC`, this procedure is builtin in `libsvm` which is used under the hood, so it does not rely on scikit-learn's :class:`~sklearn.calibration.CalibratedClassifierCV`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 222); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 222); [backlink](#)

Unknown interpreted text role "ref".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 222); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 222); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 222); [backlink](#)

Unknown interpreted text role "class".

The cross-validation involved in Platt scaling is an expensive operation for large datasets. In addition, the probability estimates may be inconsistent with the scores:

- the "argmax" of the scores may not be the argmax of the probabilities
- in binary classification, a sample may be labeled by `predict` as belonging to the positive class even if the output of `predict_proba` is less than 0.5; and similarly, it could be labeled as negative even if the output of `predict_proba` is more than 0.5.

Platt's method is also known to have theoretical issues. If confidence scores are required, but these do not have to be probabilities, then it is advisable to set `probability=False` and use `decision_function` instead of `predict_proba`.

Please note that when `decision_function_shape='ovr'` and `n_classes > 2`, unlike `decision_function`, the `predict` method does not try to break ties by default. You can set `break_ties=True` for the output of `predict` to be the same as `np.argmax(clf.decision_function(...), axis=1)`, otherwise the first class among the tied classes will always be returned; but have in mind that it comes with a computational cost. See [ref`sphx_glr_auto_examples_svm_plot_svm_tie_breaking.py`](#) for an example on tie breaking.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 244); [backlink](#)

Unknown interpreted text role "ref".

Unbalanced problems

In problems where it is desired to give more importance to certain classes or certain individual samples, the parameters `class_weight` and `sample_weight` can be used.

`:class:'SVC'` (but not `:class:'NuSVC'`) implements the parameter `class_weight` in the `fit` method. It's a dictionary of the form `{class_label : value}`, where `value` is a floating point number > 0 that sets the parameter `C` of class `class_label` to $C * \text{value}$. The figure below illustrates the decision boundary of an unbalanced problem, with and without weight correction.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 260); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 260); [backlink](#)

Unknown interpreted text role "class".



`:class:'SVC'`, `:class:'NuSVC'`, `:class:'SVR'`, `:class:'NuSVR'`, `:class:'LinearSVC'`, `:class:'LinearSVR'` and `:class:'OneClassSVM'` implement also weights for individual samples in the `fit` method through the `sample_weight` parameter. Similar to `class_weight`, this sets the parameter `C` for the i -th example to $C * \text{sample_weight}[i]$, which will encourage the classifier to get these samples right. The figure below illustrates the effect of sample weighting on the decision boundary. The size of the circles is proportional to the sample weights:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 273); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 273); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 273); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 273); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 273); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 273); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 273); [backlink](#)

Unknown interpreted text role "class".



Examples:

- `ref:sphx_glr_auto_examples_svm_plot_separating_hyperplane_unbalanced.py`

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 289); [backlink](#)

Unknown interpreted text role "ref".

- `ref:sphx_glr_auto_examples_svm_plot_weighted_samples.py`,

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 290); [backlink](#)

Unknown interpreted text role "ref".

Regression

The method of Support Vector Classification can be extended to solve regression problems. This method is called Support Vector Regression.

The model produced by support vector classification (as described above) depends only on a subset of the training data, because the cost function for building the model does not care about training points that lie beyond the margin. Analogously, the model produced by Support Vector Regression depends only on a subset of the training data, because the cost function ignores samples whose prediction is close to their target.

There are three different implementations of Support Vector Regression: `:class:'SVR'`, `:class:'NuSVR'` and `:class:'LinearSVR'`. `:class:'LinearSVR'` provides a faster implementation than `:class:'SVR'` but only considers the linear kernel, while `:class:'NuSVR'` implements a slightly different formulation than `:class:'SVR'` and `:class:'LinearSVR'`. See `ref:svm_implementation_details` for further details.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 309); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 309); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 309); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 309); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 309); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 309); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 309); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 309); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 309); [backlink](#)

Unknown interpreted text role "ref".

As with classification classes, the fit method will take as argument vectors X, y, only that in this case y is expected to have floating point values instead of integer values:

```
>>> from sklearn import svm
>>> X = [[0, 0], [2, 2]]
>>> y = [0.5, 2.5]
>>> regr = svm.SVR()
>>> regr.fit(X, y)
SVR()
>>> regr.predict([[1, 1]])
array([1.5])
```

Examples:

- `ref`sphx_glr_auto_examples_svm_plot_svm_regression.py``

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 332); [backlink](#)

Unknown interpreted text role "ref".

Density estimation, novelty detection

The class `:class:`OneClassSVM`` implements a One-Class SVM which is used in outlier detection.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 339); [backlink](#)

Unknown interpreted text role "class".

See `ref`outlier_detection`` for the description and usage of OneClassSVM.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 342); [backlink](#)

Unknown interpreted text role "ref".

Complexity

Support Vector Machines are powerful tools, but their compute and storage requirements increase rapidly with the number of training vectors. The core of an SVM is a quadratic programming problem (QP), separating support vectors from the rest of the training data.

The QP solver used by the `libsvm`-based implementation scales between $O(n_{\text{features}} \times n_{\text{samples}}^2)$ and $O(n_{\text{features}} \times n_{\text{samples}}^3)$

depending on how efficiently the `libsvm` cache is used in practice (dataset dependent). If the data is very sparse n_{features} should be replaced by the average number of non-zero features in a sample vector.

For the linear case, the algorithm used in `:class:`LinearSVC`` by the `liblinear` implementation is much more efficient than its `libsvm`-based `:class:`SVC`` counterpart and can scale almost linearly to millions of samples and/or features.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 358); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 358); [backlink](#)

Tips on Practical Use

- **Avoiding data copy:** For `:class:'SVC'`, `:class:'SVR'`, `:class:'NuSVC'` and `:class:'NuSVR'`, if the data passed to certain methods is not C-ordered contiguous and double precision, it will be copied before calling the underlying C implementation. You can check whether a given numpy array is C-contiguous by inspecting its `flags` attribute.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 368); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 368); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 368); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 368); [backlink](#)

Unknown interpreted text role "class".

For `:class:'LinearSVC'` (and `:class:'LogisticRegression<sklearn.linear_model.LogisticRegression>'`) any input passed as a numpy array will be copied and converted to the [liblinear](#) internal sparse data representation (double precision floats and int32 indices of non-zero components). If you want to fit a large-scale linear classifier without copying a dense numpy C-contiguous double precision array as input, we suggest to use the `:class:'SGDClassifier<sklearn.linear_model.SGDClassifier>'` class instead. The objective function can be configured to be almost the same as the `:class:'LinearSVC'` model.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 374); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 374); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 374); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 374); [backlink](#)

Unknown interpreted text role "class".

- **Kernel cache size:** For `:class:'SVC'`, `:class:'SVR'`, `:class:'NuSVC'` and `:class:'NuSVR'`, the size of the kernel

cache has a strong impact on run times for larger problems. If you have enough RAM available, it is recommended to set `cache_size` to a higher value than the default of 200(MB), such as 500(MB) or 1000(MB).

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 385); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 385); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 385); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 385); [backlink](#)

Unknown interpreted text role "class".

- **Setting C:** `c` is 1 by default and it's a reasonable default choice. If you have a lot of noisy observations you should decrease it: decreasing `C` corresponds to more regularization.

`:class:'LinearSVC'` and `:class:'LinearSVR'` are less sensitive to `c` when it becomes large, and prediction results stop improving after a certain threshold. Meanwhile, larger `c` values will take more time to train, sometimes up to 10 times longer, as shown in [\[1\]](#).

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 396); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 396); [backlink](#)

Unknown interpreted text role "class".

- Support Vector Machine algorithms are not scale invariant, so **it is highly recommended to scale your data**. For example, scale each attribute on the input vector X to $[0,1]$ or $[-1,+1]$, or standardize it to have mean 0 and variance 1. Note that the *same* scaling must be applied to the test vector to obtain meaningful results. This can be done easily by using a `:class:`~sklearn.pipeline.Pipeline``:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 401); [backlink](#)

Unknown interpreted text role "class".

```
>>> from sklearn.pipeline import make_pipeline
>>> from sklearn.preprocessing import StandardScaler
>>> from sklearn.svm import SVC

>>> clf = make_pipeline(StandardScaler(), SVC())
```

See section [:ref:`preprocessing`](#) for more details on scaling and normalization.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc]

[modules]svm.rst, line 414); [backlink](#)

Unknown interpreted text role "ref".

- Regarding the *shrinking* parameter, quoting [12]: *We found that if the number of iterations is large, then shrinking can shorten the training time. However, if we loosely solve the optimization problem (e.g., by using a large stopping tolerance), the code without using shrinking may be much faster*
- Parameter `nu` in `:class:'NuSVC'`/`:class:'OneClassSVM'`/`:class:'NuSVR'` approximates the fraction of training errors and support vectors.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 425); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 425); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 425); [backlink](#)

Unknown interpreted text role "class".

- In `:class:'SVC'`, if the data is unbalanced (e.g. many positive and few negative), set `class_weight='balanced'` and/or try different penalty parameters `C`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 428); [backlink](#)

Unknown interpreted text role "class".

- Randomness of the underlying implementations:** The underlying implementations of `:class:'SVC'` and `:class:'NuSVC'` use a random number generator only to shuffle the data for probability estimation (when `probability` is set to `True`). This randomness can be controlled with the `random_state` parameter. If `probability` is set to `False` these estimators are not random and `random_state` has no effect on the results. The underlying `:class:'OneClassSVM'` implementation is similar to the ones of `:class:'SVC'` and `:class:'NuSVC'`. As no probability estimation is provided for `:class:'OneClassSVM'`, it is not random.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 432); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 432); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 432); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc]

[modules]svm.rst, line 432); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc]
[modules]svm.rst, line 432); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc]
[modules]svm.rst, line 432); [backlink](#)

Unknown interpreted text role "class".

The underlying `:class:`LinearSVC`` implementation uses a random number generator to select features when fitting the model with a dual coordinate descent (i.e when `dual` is set to `True`). It is thus not uncommon to have slightly different results for the same input data. If that happens, try with a smaller *tol* parameter. This randomness can also be controlled with the `random_state` parameter. When `dual` is set to `False` the underlying implementation of `:class:`LinearSVC`` is not random and `random_state` has no effect on the results.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc]
[modules]svm.rst, line 442); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc]
[modules]svm.rst, line 442); [backlink](#)

Unknown interpreted text role "class".

- Using L1 penalization as provided by `LinearSVC(penalty='l1', dual=False)` yields a sparse solution, i.e. only a subset of feature weights is different from zero and contribute to the decision function. Increasing `C` yields a more complex model (more features are selected). The `C` value that yields a "null" model (all weights equal to zero) can be calculated using `:func:`l1_min_c``.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc]
[modules]svm.rst, line 451); [backlink](#)

Unknown interpreted text role "func".

Kernel functions

The *kernel function* can be any of the following:

- linear: $\langle x, x' \rangle$.
- polynomial: $(\gamma \langle x, x' \rangle + r)^d$, where d is specified by parameter `degree`, r by `coef0`.
- rbf: $\exp(-\gamma \|x - x'\|^2)$, where γ is specified by parameter `gamma`, must be greater than 0.
- sigmoid $\tanh(\gamma \langle x, x' \rangle + r)$, where r is specified by `coef0`.

Different kernels are specified by the *kernel* parameter:

```
>>> linear_svc = svm.SVC(kernel='linear')
>>> linear_svc.kernel
'linear'
>>> rbf_svc = svm.SVC(kernel='rbf')
>>> rbf_svc.kernel
'rbf'
```

Parameters of the RBF Kernel

When training an SVM with the *Radial Basis Function* (RBF) kernel, two parameters must be considered: `C` and `gamma`. The parameter `C`, common to all SVM kernels, trades off misclassification of training examples against simplicity of the decision surface. A

low `C` makes the decision surface smooth, while a high `C` aims at classifying all training examples correctly. `gamma` defines how much influence a single training example has. The larger `gamma` is, the closer other examples must be to be affected.

Proper choice of `C` and `gamma` is critical to the SVM's performance. One is advised to use

`class:~sklearn.model_selection.GridSearchCV` with `C` and `gamma` spaced exponentially far apart to choose good values.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 497); [backlink](#)

Unknown interpreted text role "class".

Examples:

- `ref`sphx_glr_auto_examples_svm_plot_rbf_parameters.py``

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 503); [backlink](#)

Unknown interpreted text role "ref".

- `ref`sphx_glr_auto_examples_svm_plot_svm_nonlinear.py``

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 504); [backlink](#)

Unknown interpreted text role "ref".

Custom Kernels

You can define your own kernels by either giving the kernel as a python function or by precomputing the Gram matrix.

Classifiers with custom kernels behave the same way as any other classifiers, except that:

- Field `support_vectors_` is now empty, only indices of support vectors are stored in `support_`
- A reference (and not a copy) of the first argument in the `fit()` method is stored for future reference. If that array changes between the use of `fit()` and `predict()` you will have unexpected results.

Using Python functions as kernels

You can use your own defined kernels by passing a function to the `kernel` parameter.

Your kernel must take as arguments two matrices of shape `(n_samples_1, n_features)`, `(n_samples_2, n_features)` and return a kernel matrix of shape `(n_samples_1, n_samples_2)`.

The following code defines a linear kernel and creates a classifier instance that will use that kernel:

```
>>> import numpy as np
>>> from sklearn import svm
>>> def my_kernel(X, Y):
...     return np.dot(X, Y.T)
...
>>> clf = svm.SVC(kernel=my_kernel)
```

Examples:

- `ref`sphx_glr_auto_examples_svm_plot_custom_kernel.py``

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 546); [backlink](#)

Unknown interpreted text role "ref".

Using the Gram matrix

You can pass pre-computed kernels by using the `kernel='precomputed'` option. You should then pass Gram matrix instead of `X` to the `fit` and `predict` methods. The kernel values between *all* training vectors and the test vectors must be provided:

```
>>> import numpy as np
>>> from sklearn.datasets import make_classification
>>> from sklearn.model_selection import train_test_split
```

```
>>> from sklearn import svm
>>> X, y = make_classification(n_samples=10, random_state=0)
>>> X_train, X_test, y_train, y_test = train_test_split(X, y, random_state=0)
>>> clf = svm.SVC(kernel='precomputed')
>>> # linear kernel computation
>>> gram_train = np.dot(X_train, X_train.T)
>>> clf.fit(gram_train, y_train)
SVC(kernel='precomputed')
>>> # predict on training examples
>>> gram_test = np.dot(X_test, X_train.T)
>>> clf.predict(gram_test)
array([0, 1, 0])
```

Mathematical formulation

A support vector machine constructs a hyper-plane or set of hyper-planes in a high or infinite dimensional space, which can be used for classification, regression or other tasks. Intuitively, a good separation is achieved by the hyper-plane that has the largest distance to the nearest training data points of any class (so-called functional margin), since in general the larger the margin the lower the generalization error of the classifier. The figure below shows the decision function for a linearly separable problem, with three samples on the margin boundaries, called "support vectors":



In general, when the problem isn't linearly separable, the support vectors are the samples *within* the margin boundaries.

We recommend [13] and [14] as good references for the theory and practicalities of SVMs.

SVC

Given training vectors $x_i \in \mathbb{R}^p$, $i=1, \dots, n$, in two classes, and a vector $y \in \{1, -1\}^n$, our goal is to find $w \in \mathbb{R}^p$ and $b \in \mathbb{R}$ such that the prediction given by $\text{sign}(w^T \phi(x) + b)$ is correct for most samples.

SVC solves the following primal problem:

$$\min_{w, b, \zeta} \frac{1}{2} w^T w + C \sum_{i=1}^n \zeta_i$$

subject to $y_i(w^T \phi(x_i) + b) \geq 1 - \zeta_i$,

$$\zeta_i \geq 0, i = 1, \dots, n$$

Intuitively, we're trying to maximize the margin (by minimizing $\|w\|^2 = w^T w$), while incurring a penalty when a sample is misclassified or within the margin boundary. Ideally, the value $y_i(w^T \phi(x_i) + b)$ would be ≥ 1 for all samples, which indicates a perfect prediction. But problems are usually not always perfectly separable with a hyperplane, so we allow some samples to be at a distance ζ_i from their correct margin boundary. The penalty term C controls the strength of this penalty, and as a result, acts as an inverse regularization parameter (see note below).

The dual problem to the primal is

$$\min_{\alpha} \frac{1}{2} \alpha^T Q \alpha - e^T \alpha$$

subject to $y^T \alpha = 0$

$$0 \leq \alpha_i \leq C, i = 1, \dots, n$$

where e is the vector of all ones, and Q is an n by n positive semidefinite matrix, $Q_{ij} \equiv y_i y_j K(x_i, x_j)$, where $K(x_i, x_j) = \phi(x_i)^T \phi(x_j)$ is the kernel. The terms α_i are called the dual coefficients, and they are upper-bounded by C . This dual representation highlights the fact that training vectors are implicitly mapped into a higher (maybe infinite) dimensional space by the function ϕ : see [kernel trick](#).

Once the optimization problem is solved, the output of `term`decision_function`` for a given sample x becomes:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules] svm.rst, line 645); [backlink](#)

Unknown interpreted text role "term".

$$\sum_{i \in SV} y_i \alpha_i K(x_i, x) + b,$$

and the predicted class correspond to its sign. We only need to sum over the support vectors (i.e. the samples that lie within the margin) because the dual coefficients α_i are zero for the other samples.

These parameters can be accessed through the attributes `dual_coef_` which holds the product $y_i \alpha_i$, `support_vectors_` which holds the support vectors, and `intercept_` which holds the independent term b

Note

While SVM models derived from `libsvm` and `liblinear` use `C` as regularization parameter, most other estimators use `alpha`. The exact equivalence between the amount of regularization of two models depends on the exact objective function optimized by the model. For example, when the estimator used is `~sklearn.linear_model.Ridge` regression, the relation between them is given as $C = \frac{1}{\alpha}$.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 661); [backlink](#)

Unknown interpreted text role "class".

LinearSVC

The primal problem can be equivalently formulated as

$$\min_{w, b} \frac{1}{2} w^T w + C \sum_{i=1} \max(0, 1 - y_i(w^T \phi(x_i) + b)),$$

where we make use of the [hinge loss](#). This is the form that is directly optimized by `~sklearn.linear_model.LinearSVC`, but unlike the dual form, this one does not involve inner products between samples, so the famous kernel trick cannot be applied. This is why only the linear kernel is supported by `~sklearn.linear_model.LinearSVC` (ϕ is the identity function).

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 677); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 677); [backlink](#)

Unknown interpreted text role "class".

NuSVC

The ν -SVC formulation [\[15\]](#) is a reparameterization of the C-SVC and therefore mathematically equivalent.

We introduce a new parameter ν (instead of C) which controls the number of support vectors and *margin errors*: $\nu \in (0, 1]$ is an upper bound on the fraction of margin errors and a lower bound of the fraction of support vectors. A margin error corresponds to a sample that lies on the wrong side of its margin boundary: it is either misclassified, or it is correctly classified but does not lie beyond the margin.

SVR

Given training vectors $x_i \in \mathbb{R}^p$, $i=1, \dots, n$, and a vector $y \in \mathbb{R}^n$ ε -SVR solves the following primal problem:

$$\min_{w, b, \zeta, \zeta^*} \frac{1}{2} w^T w + C \sum_{i=1}^n (\zeta_i + \zeta_i^*)$$

$$\text{subject to } y_i - w^T \phi(x_i) - b \leq \varepsilon + \zeta_i,$$

$$w^T \phi(x_i) + b - y_i \leq \varepsilon + \zeta_i^*,$$

$$\zeta_i, \zeta_i^* \geq 0, i = 1, \dots, n$$

Here, we are penalizing samples whose prediction is at least ε away from their true target. These samples penalize the objective by ζ_i or ζ_i^* , depending on whether their predictions lie above or below the ε tube.

The dual problem is

$$\min_{\alpha, \alpha^*} \frac{1}{2} (\alpha - \alpha^*)^T Q (\alpha - \alpha^*) + \varepsilon e^T (\alpha + \alpha^*) - y^T (\alpha - \alpha^*)$$

$$\text{subject to } e^T (\alpha - \alpha^*) = 0$$

$$0 \leq \alpha_i, \alpha_i^* \leq C, i = 1, \dots, n$$

where e is the vector of all ones, Q is an n by n positive semidefinite matrix, $Q_{ij} \equiv K(x_i, x_j) = \phi(x_i)^T \phi(x_j)$ is the kernel. Here training vectors are implicitly mapped into a higher (maybe infinite) dimensional space by the function ϕ .

The prediction is:

$$\sum_{i \in SV} (\alpha_i - \alpha_i^*) K(x_i, x) + b$$

These parameters can be accessed through the attributes `dual_coef_` which holds the difference $\alpha_i - \alpha_i^*$, `support_vectors_` which holds the support vectors, and `intercept_` which holds the independent term b

LinearSVR

The primal problem can be equivalently formulated as

$$\min_{w, b} \frac{1}{2} w^T w + C \sum_{i=1} \max(0, |y_i - (w^T \phi(x_i) + b)| - \varepsilon),$$

where we make use of the epsilon-insensitive loss, i.e. errors of less than ε are ignored. This is the form that is directly optimized by `class: LinearSVR`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main] [doc] [modules]svm.rst, line 757); [backlink](#)

Unknown interpreted text role "class".

Implementation details

Internally, we use [libsvm](#) [12] and [liblinear](#) [11] to handle all computations. These libraries are wrapped using C and Cython. For a description of the implementation and details of the algorithms used, please refer to their respective papers.

References:

- [9] Platt "Probabilistic outputs for SVMs and comparisons to regularized likelihood methods".
- [10] Wu, Lin and Weng "Probability estimates for multi-class classification by pairwise coupling", JMLR 5:975-1005, 2004.
- [11] (1,2) Fan, Rong-En, et al., "LIBLINEAR: A library for large linear classification.", Journal of machine learning research 9.Aug (2008): 1871-1874.
- [12] (1,2) Chang and Lin, LIBSVM: A Library for Support Vector Machines.
- [13] Bishop, [Pattern recognition and machine learning](#), chapter 7 Sparse Kernel Machines
- [14] [.doi: "A Tutorial on Support Vector Regression" <10.1023/B:STCO.0000035301.49549.88>](#) Alex J. Smola,

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\[scikit-learn-main][doc][modules]svm.rst, line 798); [backlink](#)

Unknown interpreted text role "doi".

- [15] Schölkopf et. al [New Support Vector Algorithms](#)
- [16] Crammer and Singer [On the Algorithmic Implementation of Multiclass Kernel-based Vector Machines](#), JMLR 2001.