Registry Plugin

The registry plugin allows users to search the Windows registry.

Special functions (differ from the regular functions)

- Support full base keys and short base keys (e.g. HKLM for HKEY_LOCALE_MACHINE).
- Show count of subkeys and count of values in the second result line.
- Search for value names and value data inside a registry key (syntax: [RegistryKey]\\[ValueName] and [RegistryKey]\\[ValueData])

The Windows Registry

The registry contains all settings for the Windows operating system and many settings of the installed (Windows only) programs.

Note: Linux and macOS program ports typical store the settings in it's own configuration files and not in the Windows registry.

For more information about the Windows registry, see the official documentation.

For advanced information about the Windows registry, see Windows registry information for advanced users.

Score

The score is currently not set on the results.

Important for developers

General

 The assembly name is cached into _assemblyName (to avoid to many calls of Assembly.GetExecutingAssembly())

Results

- All results override the visible search result via QueryTextDisplay to avoid problems with short registry base keys (e.g. HKLM).
- The length of a Title and Subtitle is automatic truncated, when it is to long.

Microsoft.Plugin.Registry project

Important plugin values (meta-data)

| Name | Value | |
|---------------|-------|--|
| ActionKeyword | : | |

| Name | Value |
|--------------------|--|
| ExecuteFileName ID | Microsoft.PowerToys.Run.Plugin.Registry.dll 303417D927BF4C97BCFFC78A123BE0C8 |

Interfaces used by this plugin

The plugin use only these interfaces (all inside the Main.cs):

- Wox.Plugin.IPlugin
- Wox.Plugin.IContextMenu
- Wox.Plugin.IPluginI18n
- System.IDisposable

${\bf Program\ files}$

| File | Content |
|-----------------------------------|---|
| Classes\RegistryEntry.c | :sWrapper class for a registry key with a possible |
| | exception on access |
| Constants\KeyName.cs | Static used short registry key names (to avoid code |
| • | and string doubling) |
| Constants\MaxTextLength | Countain all maximum text lengths (for truncating) |
| Enumeration\TruncateSid | Constain the possible truncate sides |
| Helper\ContextMenuHelpe | erAldsfunctions to build the context menu (for each |
| - | result entry) |
| <pre>Helper\QueryHelper.cs</pre> | All functions to analyze the search query |
| | :sAll functions to search into the Windows registry |
| | (via Win32.Registry) |
| <pre>Helper\ResultHelper.cs</pre> | All functions to convert internal results into WOX |
| _ | results |
| <pre>Helper\ValueHelper.cs</pre> | All functions to convert values into human readable |
| | values |
| <pre>Images\reg.dark.png</pre> | Symbol for the results for the dark theme |
| <pre>Images\reg.light.png</pre> | Symbol for the results for the light theme |
| Properties\Resources.De | shigneharesatain all translatable keys |
| Properties\Resources.re | skile that contain all translatable strings in the |
| | neutral language |
| GlobalSuppressions.cs | Code suppressions (no real file, linked via *.csproj) |
| Main.cs | Main class, the only place that implement the |
| | WOX interfaces |
| plugin.json | All meta-data for this plugin |
| StyleCop.json | Code style (no real file, linked via *.csproj) |

Important project values (*.csproj)

Name Value

 $TargetFramewom \verb+ket6.0-windows (.NET 5) or \verb+net6.0-windows 10.0.18362.0$

(OS version specific)

LangVersion 8.0 (mean C# 8.0)

Platforms x64 Nullable true

Output ..\..\x64\Debug\modules\launcher\Plugins\Microsoft.Plugin.Registry\

RootNamespacMicrosoft.PowerToys.Run.Plugin.Registry AssemblyNameMicrosoft.PowerToys.Run.Plugin.Registry

Project dependencies

Packages

| Package | Version |
|---------------------------------------|---------|
| Microsoft.CodeAnalysis.FxCopAnalyzers | 3.3.0 |
| StyleCop.Analyzers | 1.1.118 |

Projects

- Wox.Infrastructure
- Wox.Plugin