

## Lando ZSH (lando-zsh)

This plugin adds aliases for using various languages and frameworks with Lando for Docker. It will only run within lando-driven project directories.

To use it, add `lando` to the plugins array in your zshrc file:

```
plugins=(... lando)
```

### ALIASES:

Alias	Description
<code>artisan</code>	<code>lando artisan</code>
<code>composer</code>	<code>lando composer</code>
<code>drush</code>	<code>lando drush</code>
<code>gulp</code>	<code>lando gulp</code>
<code>npm</code>	<code>lando npm</code>
<code>wp</code>	<code>lando wp</code>
<code>yarn</code>	<code>lando yarn</code>

### How It Works:

This plugin removes the requirement to type `lando` before a command. It utilizes the lando version of supported commands run within directories with the following criteria: - The `.lando.yml` file is found in the current directory or any parent directory within `$LANDO_ZSH_SITES_DIRECTORY`. - The current directory is within `$LANDO_ZSH_SITES_DIRECTORY` but is not `$LANDO_ZSH_SITES_DIRECTORY` itself.

### Settings:

- `LANDO_ZSH_SITES_DIRECTORY`: The plugin will stop searching through parents for `CONFIG_FILE` once it hits this directory.
- `LANDO_ZSH_CONFIG_FILE`: The plugin will check to see if this provided file exists to check for presence of Lando.

### Author:

- Author: Joshua Bedford
- URL: <https://github.com/joshuabedford/lando-zsh>