next/script

Examples

Google Tag Manager

Google Analytics

Facebook Pixel

 Clerk

Segment Analytics

Version History

Version	Changes
v11.0.0	next/script introduced.

Note: This is API documentation for the Script Component. For a feature overview and usage information for scripts in Next.js, please see Script Optimization.

Optional Props

$\operatorname{\mathbf{src}}$

A path string specifying the URL of an external script. This can be either an absolute external URL or an internal path.

strategy

The loading strategy of the script.

strategy	Description
beforeInteractive	Load script before the page becomes interactive
afterInteractive	Load script immediately after the page becomes
	interactive
lazyOnload	Load script during browser idle time
worker	Load script in a web worker

Note: worker is an experimental strategy that can only be used when enabled in next.config.js. See Off-loading Scripts To A Web Worker.

onLoad

A method that returns additional JavaScript that should be executed after the script has finished loading.

Note: onLoad can't be used with the beforeInteractive loading strategy.

The following is an example of how to use the onLoad property:

```
import { useState } from 'react'
import Script from 'next/script'
export default function Home() {
  const [stripe, setStripe] = useState(null)
  return (
    <>
      <Script
        id="stripe-js"
        src="https://js.stripe.com/v3/"
        onLoad={() => {
          setStripe({ stripe: window.Stripe('pk_test_12345') })
        }}
     />
   </>
 )
}
```