```
+++ title = "Folder Permissions HTTP API" description = "Grafana Folder Permissions HTTP API" keywords = ["grafana", "http", "documentation", "api", "folder", "permission", "permissions", "acl"] aliases = ["/docs/grafana/latest/http_api/dashboardpermissions/"] +++
```

# **Folder Permissions API**

This API can be used to update/get the permissions for a folder.

Permissions with folderId=-1 are the default permissions for users with the Viewer and Editor roles. Permissions can be set for a user, a team or a role (Viewer or Editor). Permissions cannot be set for Admins - they always have access to everything.

The permission levels for the permission field:

- 1 = View
- 2 = Edit
- 4 = Admin

## Get permissions for a folder

```
GET /api/folders/:uid/permissions
```

Gets all existing permissions for the folder with the given uid.

#### **Example request:**

```
GET /api/folders/nErXDvCkzz/permissions HTTP/1.1
Accept: application/json
Content-Type: application/json
Authorization: Bearer eyJrIjoiTOtTcG1pUlY2RnVKZTFVaDFsNFZXdE9ZWmNrMkZYbk
```

### **Example Response**

```
HTTP/1.1 200 OK
Content-Type: application/json; charset=UTF-8
Content-Length: 551
[
    "id": 1,
    "folderId": -1,
    "created": "2017-06-20T02:00:00+02:00",
    "updated": "2017-06-20T02:00:00+02:00",
    "userId": 0,
    "userLogin": "",
    "userEmail": "",
    "teamId": 0,
    "team": "",
    "role": "Viewer",
    "permission": 1,
    "permissionName": "View",
```

```
"uid": "nErXDvCkzz",
    "title": "",
    "slug": "",
    "isFolder": false,
    "url": ""
  },
    "id": 2,
   "dashboardId": -1,
    "created": "2017-06-20T02:00:00+02:00",
    "updated": "2017-06-20T02:00:00+02:00",
    "userId": 0,
    "userLogin": "",
    "userEmail": "",
    "teamId": 0,
    "team": "",
    "role": "Editor",
    "permission": 2,
    "permissionName": "Edit",
    "uid": "",
    "title": "",
    "slug": "",
   "isFolder": false,
   "url": ""
  }
]
```

#### Status Codes:

- **200** Ok
- 401 Unauthorized
- 403 Access denied
- 404 Folder not found

# Update permissions for a folder

```
POST /api/folders/:uid/permissions
```

Updates permissions for a folder. This operation will remove existing permissions if they're not included in the request.

### **Example request:**

```
{
    "role": "Editor",
    "permission": 2
},

{
    "teamId": 1,
    "permission": 1
},

{
    "userId": 11,
    "permission": 4
}

}
```

## JSON body schema:

• items - The permission items to add/update. Items that are omitted from the list will be removed.

### Example response:

```
HTTP/1.1 200 OK
Content-Type: application/json; charset=UTF-8
Content-Length: 35

{"message":"Folder permissions updated","id":1,"title":"Department ABC"}
```

### Status Codes:

- 200 Ok
- 401 Unauthorized
- 403 Access denied
- 404 Dashboard not found