

## nvm plugin

This plugin adds autocompletions for nvm — a Node.js version manager. It also automatically sources nvm, so you don't need to do it manually in your `.zshrc`.

To use it, add nvm to the plugins array of your zshrc file:

```
plugins=(... nvm)
```

## Settings

If you installed nvm in a directory other than `$HOME/.nvm`, set and export `NVM_DIR` to be the directory where you installed nvm.

These settings should go in your zshrc file, before Oh My Zsh is sourced:

- **NVM\_HOMEBREW**: if you installed nvm via Homebrew, in a directory other than `/usr/local/opt/nvm`, you can set `NVM_HOMEBREW` to be the directory where you installed it. For example, on Apple Silicon-based Macs, Homebrew is installed in `/opt/homebrew`. To get the directory where nvm has been installed, regardless of chip architecture, use `NVM_HOMEBREW=$(brew --prefix nvm)`.
- **NVM\_LAZY**: if you want the plugin to defer the load of nvm to speed-up the start of your zsh session, set `NVM_LAZY` to 1. This will use the `--no-use` parameter when loading nvm, and will create a function for `node`, `npm`, `yarn`, and the command(s) specified by `NVM_LAZY_CMD`, so when you call either of them, nvm will load with `nvm use default`.
- **NVM\_LAZY\_CMD**: if you want additional command(s) to trigger lazy loading of nvm, set `NVM_LAZY_CMD` to the command or an array of the commands.
- **NVM\_AUTOLOAD**: if `NVM_AUTOLOAD` is set to 1, the plugin will automatically load a node version when it finds a `.nvmrc` file in the current working directory indicating which node version to load.