

Examples

Alerts are available for any length of text, as well as an optional close button. For proper styling, use one of the eight **required** contextual classes (e.g., `.alert-success`). For inline dismissal, use the [alerts JavaScript plugin](#).

```
{{< example >}} {{< alerts.inline >}} {{- range (index $.Site.Data "theme-colors") }}
```

A simple `{{ .name }}` alert—check it out!

```
{{- end -}} {{< /alerts.inline >}} {{< /example >}}
```

```
{{< callout info >}} {{< partial "callout-warning-color-assistive-technologies.md" >}} {{< /callout >}}
```

Live example

Click the button below to show an alert (hidden with inline styles to start), then dismiss (and destroy) it with the built-in close button.

```
{{< example >}}
```

Show live alert

```
{{< /example >}}
```

We use the following JavaScript to trigger our live alert demo:

```
var alertPlaceholder = document.getElementById('liveAlertPlaceholder')
var alertTrigger = document.getElementById('liveAlertBtn')

function alert(message, type) {
  var wrapper = document.createElement('div')
  wrapper.innerHTML = '<div class="alert alert-' + type + ' alert-dismissible"
role="alert">' + message + '<button type="button" class="btn-close" data-bs-
dismiss="alert" aria-label="Close"></button></div>'

  alertPlaceholder.append(wrapper)
}

if (alertTrigger) {
  alertTrigger.addEventListener('click', function () {
    alert('Nice, you triggered this alert message!', 'success')
  })
}
```

Link color

Use the `.alert-link` utility class to quickly provide matching colored links within any alert.

```
{{< example >}} {{< alerts.inline >}} {{- range (index $.Site.Data "theme-colors") }}
```

A simple `{{ .name }}` alert with [an example link](#). Give it a click if you like.

```
{{ end -}} {{< /alerts.inline >}} {{< /example >}}
```

Additional content

Alerts can also contain additional HTML elements like headings, paragraphs and dividers.

```
{{< example >}}
```

Well done!

Aww yeah, you successfully read this important alert message. This example text is going to run a bit longer so that you can see how spacing within an alert works with this kind of content.

Whenever you need to, be sure to use margin utilities to keep things nice and tidy.

```
{{< /example >}}
```

Icons

Similarly, you can use [flexbox utilities]({{< docsref "/utilities/flex" >}}) and [Bootstrap Icons]({{< param icons >}}) to create alerts with icons. Depending on your icons and content, you may want to add more utilities or custom styles.

```
{{< example >}}
```



An example alert with an icon

```
{{< /example >}}
```

Need more than one icon for your alerts? Consider using more Bootstrap Icons and making a local SVG sprite like so to easily reference the same icons repeatedly.

```
{{< example >}}
```



An example alert with an icon



An example success alert with an icon



An example warning alert with an icon



An example danger alert with an icon

```
{{< /example >}}
```

Dismissing

Using the alert JavaScript plugin, it's possible to dismiss any alert inline. Here's how:

- Be sure you've loaded the alert plugin, or the compiled Bootstrap JavaScript.
- Add a [close button]({{< docsref "/components/close-button" >}}) and the `.alert-dismissible` class, which adds extra padding to the right of the alert and positions the close button.
- On the close button, add the `data-bs-dismiss="alert"` attribute, which triggers the JavaScript functionality. Be sure to use the `<button>` element with it for proper behavior across all devices.
- To animate alerts when dismissing them, be sure to add the `.fade` and `.show` classes.

You can see this in action with a live demo:

```
{{< example >}}
```

Holy guacamole! You should check in on some of those fields below.

```
{{< /example >}}
```

```
{{< callout warning >}}
```

When an alert is dismissed, the element is completely removed from the page structure. If a keyboard user dismisses the alert using the close button, their focus will suddenly be lost and, depending on the

browser, reset to the start of the page/document. For this reason, we recommend including additional JavaScript that listens for the `closed.bs.alert` event and programmatically sets `focus()` to the most appropriate location in the page. If you're planning to move focus to a non-interactive element that normally does not receive focus, make sure to add `tabindex="-1"` to the element. {{< /callout >}}

Sass

Variables

```
{{< scss-docs name="alert-variables" file="scss/_variables.scss" >}}
```

Variant mixin

Used in combination with `$theme-colors` to create contextual modifier classes for our alerts.

```
{{< scss-docs name="alert-variant-mixin" file="scss/mixins/_alert.scss" >}}
```

Loop

Loop that generates the modifier classes with the `alert-variant()` mixin.

```
{{< scss-docs name="alert-modifiers" file="scss/_alert.scss" >}}
```

JavaScript behavior

Initialize

Initialize elements as alerts

```
var alertList = document.querySelectorAll('.alert')
var alerts = [].slice.call(alertList).map(function (element) {
  return new bootstrap.Alert(element)
})
```

{{< callout info >}} For the sole purpose of dismissing an alert, it isn't necessary to initialize the component manually via the JS API. By making use of `data-bs-dismiss="alert"`, the component will be initialized automatically and properly dismissed.

See the [triggers](#) section for more details. {{< /callout >}}

Triggers

```
{{% js-dismiss "alert" %}}
```

Note that closing an alert will remove it from the DOM.

Methods

Method	Description
close	Closes an alert by removing it from the DOM. If the <code>.fade</code> and <code>.show</code> classes are present on the element, the alert will fade out before it is removed.
dispose	Destroys an element's alert. (Removes stored data on the DOM element)

getInstance	Static method which allows you to get the alert instance associated to a DOM element, you can use it like this: <code>bootstrap.Alert.getInstance(alert)</code>
getOrCreateInstance	Static method which returns an alert instance associated to a DOM element or create a new one in case it wasn't initialized. You can use it like this: <code>bootstrap.Alert.getOrCreateInstance(element)</code>

```
var alertNode = document.querySelector('.alert')
var alert = bootstrap.Alert.getInstance(alertNode)
alert.close()
```

Events

Bootstrap's alert plugin exposes a few events for hooking into alert functionality.

Event	Description
close.bs.alert	Fires immediately when the <code>close</code> instance method is called.
closed.bs.alert	Fired when the alert has been closed and CSS transitions have completed.

```
var myAlert = document.getElementById('myAlert')
myAlert.addEventListener('closed.bs.alert', function () {
  // do something, for instance, explicitly move focus to the most appropriate
  element,
  // so it doesn't get lost/reset to the start of the page
  // document.getElementById('...').focus()
})
```