format-stale-output

Format the output of actions/stale into something you can pass to pullreminders/slack-action as blocks.

Inputs

staled-issues-prs

Comes from actions/stale.

closed-issues-prs

Comes from actions/stale.

Outputs

blocks

Something you can directly pass to pullreminders/slackaction like:

```
- name: Slack Report Closed Issues
  uses: pullreminders/slack-action@v1.0.7
  env:
    SLACK_BOT_TOKEN: ${{ secrets.SLACK_TOKEN }}
  with:
    args: '{\"channel\": \"${{ secrets.SLACK_STALE_CHANNEL_ID }}\", \"text\": \"\", \"blocks
```

Example Usage

```
name: Stale Bot
on:
 schedule:
   - cron: "0 */12 * * *"
jobs:
 stale:
   runs-on: ubuntu-latest
   steps:
      - uses: actions/stale@v4
       name: stale
       id: stale
        with:
          days-before-stale: 20
          days-before-close: 40
      - name: Format Stale Output
        id: format-stale-output
        uses: ./.github/actions/format-stale-output
        with:
```

```
staled-issues-prs: ${{ steps.stale.outputs.staled-issues-prs }}
  closed-issues-prs: ${{ steps.stale.outputs.closed-issues-prs }}
- name: Slack Report Closed Issues
  uses: pullreminders/slack-action@v1.0.7
  env:
    SLACK_BOT_TOKEN: ${{ secrets.SLACK_TOKEN }}
  with:
    args: '{\"channel\": \"${{ secrets.SLACK_STALE_CHANNEL_ID }}\", \"text\": \"\", \"
```

Building this Action

Use ${\tt Qvercel/ncc}$ to compile this action. You can run ${\tt npm}$ run build in this directory to run the command.