

Operator	Flowable	Observable	Maybe	Single	Completable
all	✓	✓	○ (1)	○ (1)	○ (2)
amb	✓	✓	✓	✓	✓
ambArray	✓	✓	✓	✓	✓
ambWith	✓	✓	✓	✓	✓
andThen	○ (3)	○ (3)	○ (3)	○ (3)	✓
any	✓	✓	○ (1)	○ (1)	○ (2)
blockingAwait	○ (4)	○ (4)	○ (5)	○ (5)	✓
blockingFirst	✓	✓	○ (6)	○ (6)	○ (7)
blockingForEach	✓	✓	○ (8)	○ (8)	○ (8)
blockingGet	○ (4)	○ (4)	✓	✓	○ (7)
blockingIterable	✓	✓	○ (6)	○ (6)	○ (7)
blockingLast	✓	✓	○ (6)	○ (6)	○ (7)



























































blockingLatest			 (6)	 (6)	 (7)
blockingMostRecent			 (6)	 (6)	 (7)
blockingNext			 (6)	 (6)	 (7)
blockingSingle			 (6)	 (6)	 (7)
blockingStream			 (6)	 (6)	 (7)
blockingSubscribe					
buffer			 (9)	 (10)	 (11)
cache					
cacheWithInitialCapacity			 (12)	 (12)	 (12)
cast					 (2)
collect			 (13)	 (14)	 (15)
collectInto			 (13)	 (14)	 (15)
combineLatest			 (16)	 (16)	 (17)
combineLatestArray			 (18)	 (18)	 (19)
combineLatestArrayDelayError					

			(18)	(18)	(20)
combineLatestDelayError			(16)	(16)	(21)
complete	(22)	(22)	(22)	(23)	
compose					
concat					
concatArray					
concatArrayDelayError					
concatArrayEager					(24)
concatArrayEagerDelayError					(25)
concatDelayError					
concatEager					(26)
concatEagerDelayError					(27)
concatMap					(28)
concatMapCompletable					(28)
concatMapCompletableDelayError			(29)	(29)	(28)

concatMapDelayError	✓	✓	○ (30)	○ (30)	○ (28)
concatMapEager	✓	✓	○ (31)	○ (31)	○ (28)
concatMapEagerDelayError	✓	✓	○ (31)	○ (31)	○ (28)
concatMapIterable	✓	✓	○ (32)	○ (32)	○ (28)
concatMapMaybe	✓	✓	○ (33)	✓	○ (28)
concatMapMaybeDelayError	✓	✓	○ (34)	○ (34)	○ (28)
concatMapSingle	✓	✓	✓	○ (35)	○ (28)
concatMapSingleDelayError	✓	✓	○ (36)	○ (36)	○ (28)
concatMapStream	✓	✓	○ (37)	○ (37)	○ (28)
concatWith	✓	✓	✓	✓	✓
contains	✓	✓	✓	✓	○ (2)
count	✓	✓	✓	○ (38)	○ (39)
create	✓	✓	✓	✓	✓
debounce	✓	✓	○ (40)	○ (40)	○ (41)
defaultIfEmpty	✓	✓	✓	○ (23)	○ (42)

defer					
delay					
delaySubscription					
dematerialize					 <a href="#">(41)</a>
distinct			 <a href="#">(43)</a>	 <a href="#">(43)</a>	 <a href="#">(41)</a>
distinctUntilChanged			 <a href="#">(43)</a>	 <a href="#">(43)</a>	 <a href="#">(41)</a>
doAfterNext			 <a href="#">(44)</a>	 <a href="#">(44)</a>	 <a href="#">(2)</a>
doAfterSuccess	 <a href="#">(45)</a>	 <a href="#">(45)</a>			 <a href="#">(41)</a>
doAfterTerminate					
doFinally					
doOnCancel		 <a href="#">(46)</a>	 <a href="#">(46)</a>	 <a href="#">(46)</a>	 <a href="#">(46)</a>
doOnComplete				 <a href="#">(47)</a>	
doOnDispose	 <a href="#">(48)</a>				
doOnEach			 <a href="#">(49)</a>	 <a href="#">(49)</a>	 <a href="#">(41)</a>
doOnError					

doOnEvent	 (50)	 (50)			
doOnLifecycle					
doOnNext			 (51)	 (51)	 (41)
doOnRequest		 (52)	 (52)	 (52)	 (52)
doOnSubscribe					
doOnSuccess	 (53)	 (53)			 (41)
doOnTerminate					
elementAt			 (54)	 (55)	 (41)
elementAtOrElse			 (56)	 (55)	 (41)
empty				 (23)	 (57)
error					
filter					 (41)
first			 (58)	 (59)	 (42)
firstElement			 (60)	 (61)	 (2)

firstOnError			 <a href="#">(60)</a>	 <a href="#">(61)</a>	 <a href="#">(62)</a>
firstOnErrorStage			 <a href="#">(63)</a>	 <a href="#">(63)</a>	 <a href="#">(64)</a>
firstStage			 <a href="#">(63)</a>	 <a href="#">(63)</a>	 <a href="#">(63)</a>
flatMap					 <a href="#">(28)</a>
flatMapCompletable					 <a href="#">(28)</a>
flatMapIterable			 <a href="#">(32)</a>	 <a href="#">(32)</a>	 <a href="#">(28)</a>
flatMapMaybe			 <a href="#">(65)</a>		 <a href="#">(28)</a>
flatMapObservable	 <a href="#">(66)</a>	 <a href="#">(67)</a>			 <a href="#">(28)</a>
flatMapPublisher	 <a href="#">(67)</a>	 <a href="#">(68)</a>			 <a href="#">(28)</a>
flatMapSingle				 <a href="#">(65)</a>	 <a href="#">(28)</a>
flatMapStream			 <a href="#">(37)</a>	 <a href="#">(37)</a>	 <a href="#">(28)</a>
flattenAsFlowable	 <a href="#">(69)</a>	 <a href="#">(69)</a>			 <a href="#">(28)</a>
flattenAsObservable	 <a href="#">(69)</a>	 <a href="#">(69)</a>			 <a href="#">(28)</a>
flattenStreamAsFlowable	 <a href="#">(70)</a>	 <a href="#">(70)</a>			 <a href="#">(28)</a>
flattenStreamAsObservable	 <a href="#">(70)</a>	 <a href="#">(70)</a>			 <a href="#">(28)</a>

forEach			 (71)	 (71)	 (71)
forEachWhile			 (71)	 (71)	 (71)
fromAction				 (23)	
fromArray			 (72)	 (73)	 (74)
fromCallable					
fromCompletable				 (75)	 (76)
fromCompletionStage					
fromFuture					
fromIterable			 (72)	 (73)	 (74)
fromMaybe			 (76)		
fromObservable		 (76)			
fromOptional				 (73)	 (74)
fromPublisher					
fromRunnable				 (23)	
fromSingle					



				(76)	
fromStream			(72)	(73)	(74)
fromSupplier					
generate			(77)	(77)	(77)
groupBy			(78)	(78)	(79)
groupJoin			(78)	(78)	(80)
hide					
ignoreElement	(81)	(81)			(2)
ignoreElements			(82)	(82)	(2)
interval			(83)	(83)	(83)
intervalRange			(83)	(83)	(83)
isEmpty				(59)	(2)
join			(84)	(84)	(80)
just					(2)
last			(58)	(59)	(42)

lastElement			 (60)	 (61)	 (2)
lastOnError			 (60)	 (61)	 (62)
lastOnErrorStage			 (63)	 (63)	 (64)
lastStage			 (63)	 (63)	 (63)
lift					
map					 (28)
mapOptional					 (28)
materialize					
merge					
mergeArray					
mergeArrayDelayError					
mergeDelayError					
mergeWith					
never					
observeOn					

ofType					 (85)
onBackpressureBuffer		 (52)	 (52)	 (52)	 (52)
onBackpressureDrop		 (52)	 (52)	 (52)	 (52)
onBackpressureLatest		 (52)	 (52)	 (52)	 (52)
onErrorComplete					
onErrorResumeNext					
onErrorResumeWith					
onErrorReturn					
onErrorReturnItem					
onTerminateDetach					
parallel		 (86)	 (86)	 (86)	 (86)
publish			 (87)	 (88)	 (89)
range			 (90)	 (90)	 (74)
rangeLong			 (90)	 (90)	 (74)
rebatchRequests					

		(52)	(52)	(52)	(52)
reduce			(91)	(91)	(92)
reduceWith			(91)	(91)	(92)
repeat					
repeatUntil					
repeatWhen					
replay			(87)	(88)	(89)
retry					
retryUntil					
retryWhen					
safeSubscribe					
sample			(60)	(60)	(41)
scan			(91)	(91)	(92)
scanWith			(91)	(91)	(92)
sequenceEqual					

serialize			 (93)	 (93)	 (93)
share			 (87)	 (88)	 (89)
single			 (58)	 (59)	 (42)
singleElement			 (60)	 (61)	 (2)
singleOnError			 (60)	 (61)	 (62)
singleOnErrorStage			 (63)	 (63)	 (64)
singleStage			 (63)	 (63)	 (63)
skip			 (60)	 (60)	 (60)
skipLast			 (60)	 (60)	 (60)
skipUntil			 (94)	 (94)	 (94)
skipWhile			 (95)	 (95)	 (2)
sorted			 (78)	 (78)	 (78)
startWith					
startWithArray			 (96)	 (96)	 (96)
startWithItem			 (97)	 (97)	 (97)

startWithIterable			 (98)	 (98)	 (98)
subscribe					
subscribeOn					
subscribeWith					
switchIfEmpty				 (23)	 (99)
switchMap			 (100)	 (100)	 (28)
switchMapCompletable			 (100)	 (100)	 (28)
switchMapCompletableDelayError			 (100)	 (100)	 (28)
switchMapDelayError			 (100)	 (100)	 (28)
switchMapMaybe			 (100)	 (100)	 (28)
switchMapMaybeDelayError			 (100)	 (100)	 (28)
switchMapSingle			 (100)	 (100)	 (28)
switchMapSingleDelayError			 (100)	 (100)	 (28)
switchOnNext					
switchOnNextDelayError					

take			 <a href="#">(60)</a>	 <a href="#">(60)</a>	 <a href="#">(60)</a>
takeLast			 <a href="#">(60)</a>	 <a href="#">(60)</a>	 <a href="#">(60)</a>
takeUntil					
takeWhile			 <a href="#">(95)</a>	 <a href="#">(95)</a>	 <a href="#">(2)</a>
test					
throttleFirst			 <a href="#">(40)</a>	 <a href="#">(40)</a>	 <a href="#">(41)</a>
throttleLast			 <a href="#">(40)</a>	 <a href="#">(40)</a>	 <a href="#">(41)</a>
throttleLatest			 <a href="#">(40)</a>	 <a href="#">(40)</a>	 <a href="#">(41)</a>
throttleWithTimeout			 <a href="#">(40)</a>	 <a href="#">(40)</a>	 <a href="#">(41)</a>
timeInterval					 <a href="#">(41)</a>
timeout					
timer					
timestamp					 <a href="#">(41)</a>
to					

toCompletionStage	<input type="radio"/> (101)	<input type="radio"/> (101)	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
toFlowable	<input type="radio"/> (102)	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
toFuture	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
toList	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/> (13)	<input type="radio"/> (14)	<input type="radio"/> (15)
toMap	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/> (13)	<input type="radio"/> (14)	<input type="radio"/> (15)
toMaybe	<input type="radio"/> (103)	<input type="radio"/> (103)	<input type="radio"/> (102)	<input checked="" type="radio"/>	<input checked="" type="radio"/>
toMultimap	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/> (13)	<input type="radio"/> (14)	<input type="radio"/> (15)
toObservable	<input checked="" type="radio"/>	<input type="radio"/> (102)	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
toSingle	<input type="radio"/> (104)	<input type="radio"/> (104)	<input checked="" type="radio"/>	<input type="radio"/> (102)	<input checked="" type="radio"/>
toSingleDefault	<input type="radio"/> (105)	<input type="radio"/> (105)	<input type="radio"/> (106)	<input type="radio"/> (102)	<input checked="" type="radio"/>
toSortedList	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/> (13)	<input type="radio"/> (14)	<input type="radio"/> (15)
unsafeCreate	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
unsubscribeOn	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
using	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input checked="" type="radio"/>
window	<input checked="" type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/> (107)	<input type="radio"/> (108)	<input type="radio"/> (109)



withLatestFrom			(16)	(16)	(17)
wrap	(110)				
zip					(111)
zipArray					(112)
zipWith					(113)
<b>237 operators</b>	<b>216</b>	<b>210</b>	<b>118</b>	<b>108</b>	<b>84</b>

## Notes

- <sup>1</sup> Use [contains\(\)](#) .
- <sup>2</sup> Always empty.
- <sup>3</sup> Use [concatWith](#) .
- <sup>4</sup> Use [blockingFirst\(\)](#) , [blockingSingle\(\)](#) or [blockingLast\(\)](#) .
- <sup>5</sup> Use [blockingGet\(\)](#) .
- <sup>6</sup> At most one element to get. Use [blockingGet\(\)](#) .
- <sup>7</sup> No elements to get. Use [blockingAwait\(\)](#) .
- <sup>8</sup> Use [blockingSubscribe\(\)](#) .
- <sup>9</sup> Use [map\(\)](#) and [switchIfEmpty\(\)](#) to transform into a list/collection.
- <sup>10</sup> Use [map\(\)](#) to transform into a list/collection.
- <sup>11</sup> Always empty. Use [andThen\(\)](#) to bring in a list/collection.
- <sup>12</sup> At most one element to store. Use [cache\(\)](#) .
- <sup>13</sup> At most one element to collect. Use [map\(\)](#) and [switchIfEmpty\(\)](#) to transform into a list/collection.
- <sup>14</sup> One element to collect. Use [map\(\)](#) to transform into a list/collection.
- <sup>15</sup> Always empty. Use [andThen\(\)](#) to bring in a collection.
- <sup>16</sup> At most one element per source. Use [zip\(\)](#) .
- <sup>17</sup> Always empty. Use [merge\(\)](#) .
- <sup>18</sup> At most one element per source. Use [zipArray\(\)](#) .
- <sup>19</sup> Always empty. Use [mergeArray\(\)](#) .
- <sup>20</sup> Always empty. Use [mergeArrayDelayError\(\)](#) .
- <sup>21</sup> Always empty. Use [mergeDelayError\(\)](#) .
- <sup>22</sup> Use [empty\(\)](#) .
- <sup>23</sup> Never empty.
- <sup>24</sup> No items to keep ordered. Use [mergeArray\(\)](#) .

- 25 No items to keep ordered. Use [mergeArrayDelayError\(\)](#) .
- 26 No items to keep ordered. Use [merge\(\)](#) .
- 27 No items to keep ordered. Use [mergeDelayError\(\)](#) .
- 28 Always empty thus no items to map.
- 29 Either the upstream fails (thus no inner) or the mapped-in source, but never both. Use [concatMapCompletable\(\)](#) .
- 30 Either the upstream fails (thus no inner) or the mapped-in source, but never both. Use [concatMap\(\)](#) .
- 31 At most one item to map. Use [concatMap\(\)](#) .
- 32 At most one item. Use [flattenAsFlowable\(\)](#) or [flattenAsObservable\(\)](#) .
- 33 Use [concatMap\(\)](#) .
- 34 Either the upstream fails (thus no inner) or the mapped-in source, but never both. Use [concatMapMaybe\(\)](#) .
- 35 Use [concatMap\(\)](#) .
- 36 Either the upstream fails (thus no inner) or the mapped-in source, but never both. Use [concatMapSingle\(\)](#) .
- 37 At most one item. Use [flattenStreamAsFlowable\(\)](#) or [flattenStreamAsObservable\(\)](#) .
- 38 Never empty thus always 1.
- 39 Always empty thus always 0.
- 40 At most one item signaled so no subsequent items to work with.
- 41 Always empty thus no items to work with.
- 42 Always empty. Use [andThen\(\)](#) to chose the follow-up sequence.
- 43 At most one item, always distinct.
- 44 Different terminology. Use [doAfterSuccess\(\)](#) .
- 45 Different terminology. Use [doAfterNext\(\)](#) .
- 46 Different terminology. Use [doOnDispose\(\)](#) .
- 47 Always succeeds or fails, there is no `onComplete` signal.
- 48 Different terminology. Use [doOnCancel\(\)](#) .
- 49 At most one item. Use [doOnEvent\(\)](#) .
- 50 Use [doOnEach\(\)](#) .
- 51 Different terminology. Use [doOnSuccess\(\)](#) .
- 52 Backpressure related and not supported outside `Flowable` .
- 53 Different terminology. Use [doOnNext\(\)](#) .
- 54 At most one item with index 0. Use [defaultIfEmpty\(\)](#) .
- 55 Always one item with index 0.
- 56 At most one item with index 0. Use [toSingle\(\)](#) .
- 57 Use [complete\(\)](#) .
- 58 At most one item. Use [defaultIfEmpty\(\)](#) .
- 59 Always one item.
- 60 At most one item, would be no-op.
- 61 Always one item, would be no-op.
- 62 Always empty. Use [andThen\(\)](#) and [error\(\)](#) .
- 63 At most one item. Use [toCompletionStage\(\)](#) .
- 64 Always empty. Use [andThen\(\)](#) , [error\(\)](#) and [toCompletionStage\(\)](#) .
- 65 Use [flatMap\(\)](#) .
- 66 Not supported. Use [flatMap\(\)](#) and [toFlowable\(\)](#) .

- 67 Use [flatMap](#) .
- 68 Not supported. Use [flatMap](#) and [toObservable\(\)](#) .
- 69 Use [flatMapIterable\(\)](#) .
- 70 Use [flatMapStream\(\)](#) .
- 71 Use [subscribe\(\)](#) .
- 72 At most one item. Use [just\(\)](#) or [empty\(\)](#) .
- 73 Always one item. Use [just\(\)](#) .
- 74 Always empty. Use [complete\(\)](#) .
- 75 Always error.
- 76 Use [wrap\(\)](#) .
- 77 Use [fromSupplier\(\)](#) .
- 78 At most one item.
- 79 Always empty thus no items to group.
- 80 Always empty thus no items to join.
- 81 Use [ignoreElements\(\)](#) .
- 82 Use [ignoreElement\(\)](#) .
- 83 At most one item. Use [timer\(\)](#) .
- 84 At most one item. Use [zip\(\)](#) .
- 85 Always empty thus no items to filter.
- 86 Needs backpressure thus not supported outside `Flowable` .
- 87 Connectable sources not supported outside `Flowable` and `Observable` . Use a `MaybeSubject` .
- 88 Connectable sources not supported outside `Flowable` and `Observable` . Use a `SingleSubject` .
- 89 Connectable sources not supported outside `Flowable` and `Observable` . Use a `ConnectableSubject` .
- 90 At most one item. Use [just\(\)](#) .
- 91 At most one item. Use [map\(\)](#) .
- 92 Always empty thus no items to reduce.
- 93 At most one signal type.
- 94 At most one item. Use [takeUntil\(\)](#) .
- 95 At most one item. Use [filter\(\)](#) .
- 96 Use [startWith\(\)](#) and [fromArray\(\)](#) of `Flowable` or `Observable` .
- 97 Use [startWith\(\)](#) and [just\(\)](#) of another reactive type.
- 98 Use [startWith\(\)](#) and [fromIterable\(\)](#) of `Flowable` or `Observable` .
- 99 Always empty. Use [defaultIfEmpty\(\)](#) .
- 100 At most one item. Use [flatMap\(\)](#) .
- 101 Use [firstStage](#) , [lastStage](#) or [singleStage](#) .
- 102 Would be no-op.
- 103 Use [firstElement](#) , [lastElement](#) or [singleElement](#) .
- 104 Use [firstOnError](#) , [lastOnError](#) or [singleOnError](#) .
- 105 Use [first](#) , [last](#) or [single](#) .
- 106 Use [defaultIfEmpty\(\)](#) .
- 107 Use [map\(\)](#) and [switchIfEmpty\(\)](#) to transform into a nested source.
- 108 Use [map\(\)](#) to transform into a nested source.

109 Always empty. Use `andThen()` to bring in a nested source.

110 Use `fromPublisher()` .

111 Use `merge()` .

112 Use `mergeArray()` .

113 Use `mergeWith()` .

### **Under development**

*Currently, all intended operators are implemented.*