

Radio

Single selection among multiple options.

Basic usage

Radio should not have too many options. Otherwise, use the Select component instead.

:::demo Creating a radio component is easy, you just need to bind a variable to Radio's `v-model`. It equals to the value of `label` of the chosen radio. The type of `label` is String, Number or Boolean.

```
<template>
  <el-radio v-model="radio" label="1">Option A</el-radio>
  <el-radio v-model="radio" label="2">Option B</el-radio>
</template>

<script>
  export default {
    data () {
      return {
        radio: '1'
      };
    }
  }
</script>

:::
```

Disabled

`disabled` attribute is used to disable the radio.

:::demo You just need to add the `disabled` attribute.

```
<template>
  <el-radio disabled v-model="radio" label="disabled">Option A</el-radio>
  <el-radio disabled v-model="radio" label="selected and disabled">Option B</el-radio>
</template>

<script>
  export default {
    data () {
      return {
        radio: 'selected and disabled'
      };
    }
  }
}
```

```

    }
  </script>
  ...

```

Radio button group

Suitable for choosing from some mutually exclusive options.

:::demo Combine `el-radio-group` with `el-radio` to display a radio group. Bind a variable with `v-model` of `el-radio-group` element and set label value in `el-radio`. It also provides `change` event with the current value as its parameter.

```

<el-radio-group v-model="radio">
  <el-radio :label="3">Option A</el-radio>
  <el-radio :label="6">Option B</el-radio>
  <el-radio :label="9">Option C</el-radio>
</el-radio-group>

<script>
  export default {
    data () {
      return {
        radio: 3
      };
    }
  }
</script>
  ...

```

Button style

Radio with button styles.

:::demo You just need to change `el-radio` element into `el-radio-button` element. We also provide `size` attribute.

```

<template>
  <div>
    <el-radio-group v-model="radio1">
      <el-radio-button label="New York"></el-radio-button>
      <el-radio-button label="Washington"></el-radio-button>
      <el-radio-button label="Los Angeles"></el-radio-button>
      <el-radio-button label="Chicago"></el-radio-button>
    </el-radio-group>
  </div>
  <div style="margin-top: 20px">
    <el-radio-group v-model="radio2" size="medium">

```

```

        <el-radio-button label="New York" ></el-radio-button>
        <el-radio-button label="Washington"></el-radio-button>
        <el-radio-button label="Los Angeles"></el-radio-button>
        <el-radio-button label="Chicago"></el-radio-button>
    </el-radio-group>
</div>
<div style="margin-top: 20px">
    <el-radio-group v-model="radio3" size="small">
        <el-radio-button label="New York"></el-radio-button>
        <el-radio-button label="Washington" disabled ></el-radio-button>
        <el-radio-button label="Los Angeles"></el-radio-button>
        <el-radio-button label="Chicago"></el-radio-button>
    </el-radio-group>
</div>
<div style="margin-top: 20px">
    <el-radio-group v-model="radio4" disabled size="mini">
        <el-radio-button label="New York"></el-radio-button>
        <el-radio-button label="Washington"></el-radio-button>
        <el-radio-button label="Los Angeles"></el-radio-button>
        <el-radio-button label="Chicago"></el-radio-button>
    </el-radio-group>
</div>
</template>

<script>
export default {
  data () {
    return {
      radio1: 'New York',
      radio2: 'New York',
      radio3: 'New York',
      radio4: 'New York'
    };
  }
}
</script>

:::

```

With borders

:::demo The `border` attribute adds a border to Radios.

```

<template>
  <div>
    <el-radio v-model="radio1" label="1" border>Option A</el-radio>
    <el-radio v-model="radio1" label="2" border>Option B</el-radio>
  </div>
</template>

```

```

</div>
<div style="margin-top: 20px">
  <el-radio v-model="radio2" label="1" border size="medium">Option A</el-radio>
  <el-radio v-model="radio2" label="2" border size="medium">Option B</el-radio>
</div>
<div style="margin-top: 20px">
  <el-radio-group v-model="radio3" size="small">
    <el-radio label="1" border>Option A</el-radio>
    <el-radio label="2" border disabled>Option B</el-radio>
  </el-radio-group>
</div>
<div style="margin-top: 20px">
  <el-radio-group v-model="radio4" size="mini" disabled>
    <el-radio label="1" border>Option A</el-radio>
    <el-radio label="2" border>Option B</el-radio>
  </el-radio-group>
</div>
</template>

<script>
export default {
  data () {
    return {
      radio1: '1',
      radio2: '1',
      radio3: '1',
      radio4: '1'
    }
  }
}
</script>
:::

```

Radio Attributes

Attribute	Description	Type	Accepted Values	Default
value / v-model	binding value	string / number / boolean	—	—
label	the value of Radio	string / number / boolean	—	—

Attribute	Description	Type	Accepted Values	Default
disabled	whether Radio is disabled	boolean	—	false
border	whether to add a border around Radio	boolean	—	false
size	size of the Radio, only works when border is true	string	medium / small / mini	—
name	native ‘name’ attribute	string	—	—

Radio Events

Event Name	Description	Parameters
change	triggers when the bound value changes	the label value of the chosen radio

Radio-group Attributes

Attribute	Description	Type	Accepted Values	Default
value / v-model	binding value	string / number / boolean	—	—
size	the size of radio buttons or bordered radios	string	medium / small / mini	—
disabled	whether the nesting radios are disabled	boolean	—	false
text-color	font color when button is active	string	—	#ffff

Attribute	Description	Type	Accepted Values	Default
fill	border and background color when button is active	string	—	#409EFF

Radio-group Events

Event Name	Description	Parameters
change	triggers when the bound value changes	the label value of the chosen radio

Radio-button Attributes

Attribute	Description	Type	Accepted Values	Default
label	the value of radio	string / number	—	—
disabled	whether radio is disabled	boolean	—	false
name	native 'name' attribute	string	—	—