

## :mod:`email`: Examples

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library)email.examples.rst, line 3); [backlink](#)**

Unknown interpreted text role "mod".

Here are a few examples of how to use the `:mod:`email`` package to read, write, and send simple email messages, as well as more complex MIME messages.

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library)email.examples.rst, line 6); [backlink](#)**

Unknown interpreted text role "mod".

First, let's see how to create and send a simple text message (both the text content and the addresses may contain unicode characters):

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library)email.examples.rst, line 12)**

Unknown directive type "literalinclude".

```
.. literalinclude:: ../includes/email-simple.py
```

Parsing [RFC 822](#) headers can easily be done by the using the classes from the `:mod:`~email.parser`` module:

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library)email.examples.rst, line 15); [backlink](#)**

Unknown interpreted text role "mod".

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library)email.examples.rst, line 18)**

Unknown directive type "literalinclude".

```
.. literalinclude:: ../includes/email-headers.py
```

Here's an example of how to send a MIME message containing a bunch of family pictures that may be residing in a directory:

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library)email.examples.rst, line 24)**

Unknown directive type "literalinclude".

```
.. literalinclude:: ../includes/email-mime.py
```

Here's an example of how to send the entire contents of a directory as an email message: [\[1\]](#)

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library)email.examples.rst, line 30)**

Unknown directive type "literalinclude".

```
.. literalinclude:: ../includes/email-dir.py
```

Here's an example of how to unpack a MIME message like the one above, into a directory of files:

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library)email.examples.rst, line 36)**

Unknown directive type "literalinclude".

```
.. literalinclude:: ../includes/email-unpack.py
```

Here's an example of how to create an HTML message with an alternative plain text version. To make things a bit more interesting, we include a related image in the html part, and we save a copy of what we are going to send to disk, as well as sending it.

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library)email.examples.rst, line 44)**

Unknown directive type "literalinclude".

```
.. literalinclude:: ../includes/email-alternative.py
```

If we were sent the message from the last example, here is one way we could process it:

**System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library)email.examples.rst, line 50)**

Unknown directive type "literalinclude".

```
.. literalinclude:: ../includes/email-read-alternative.py
```

Up to the prompt, the output from the above is:

**System Message: WARNING/2 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\library\ (cpython-main) (Doc) (library)email.examples.rst, line 54)**

Cannot analyze code. No Pygments lexer found for "none".

```
.. code-block:: none
```

```
To: Penelope Pussycat <penelope@example.com>, Fabrette Pussycat <fabrette@example.com>
From: PepÃ© Le Pew <pepe@example.com>
Subject: Ayons asperges pour le dÃ©jeuner
```

```
Salut!
```

```
Cela ressemble Ã  un excellent recipie[1] dÃ©jeuner.
```

## Footnotes

[1] Thanks to Matthew Dixon Cowles for the original inspiration and examples.