

cec ioctl()

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\cec\[linux-master] [Documentation] [userspace-api] [media] [cec] cec-func-ioctl.rst, line 2)

Unknown directive type "c:namespace".

.. c:namespace:: CEC

Name

cec-ioctl - Control a cec device

Synopsis

```
#include <sys/ioctl.h>
```

```
int ioctl(int fd, int request, void *argp)
```

Arguments

fd

File descriptor returned by `c:func:'open()'`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\cec\[linux-master] [Documentation] [userspace-api] [media] [cec] cec-func-ioctl.rst, line 28); [backlink](#)

Unknown interpreted text role "c:func".

request

CEC ioctl request code as defined in the cec.h header file, for example `ref:'CEC_ADAP_G_CAPS <CEC_ADAP_G_CAPS>'`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\cec\[linux-master] [Documentation] [userspace-api] [media] [cec] cec-func-ioctl.rst, line 31); [backlink](#)

Unknown interpreted text role "ref".

argp

Pointer to a request-specific structure.

Description

The `c:func:'ioctl()'` function manipulates cec device parameters. The argument `fd` must be an open file descriptor.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\cec\[linux-master] [Documentation] [userspace-api] [media] [cec] cec-func-ioctl.rst, line 40); [backlink](#)

Unknown interpreted text role "c:func".

The `ioctl request` code specifies the cec function to be called. It has encoded in it whether the argument is an input, output or read/write parameter, and the size of the argument `argp` in bytes.

Macros and structures definitions specifying cec ioctl requests and their parameters are located in the cec.h header file. All cec ioctl requests, their respective function and parameters are specified in `ref:'cec-user-func'`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\cec\[linux-master] [Documentation] [userspace-

[api](#) [[media](#)] [[cec](#)] [cec-func-ioctl.rst, line 47](#)); [backlink](#)

Unknown interpreted text role "ref".

Return Value

On success 0 is returned, on error -1 and the `errno` variable is set appropriately. The generic error codes are described at the [ref: Generic Error Codes <gen-errors>](#) chapter.

System Message: ERROR/3 ([D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\cec\linux-master](#)] [[Documentation](#)] [[userspace-api](#)] [[media](#)] [[cec](#)] [cec-func-ioctl.rst, line 55](#)); [backlink](#)

Unknown interpreted text role "ref".

Request-specific error codes are listed in the individual requests descriptions.

When an ioctl that takes an output or read/write parameter fails, the parameter remains unmodified.