

npm-restart

Synopsis

`npm restart [-- <args>]`

Description

This restarts a project. It is equivalent to running `npm run-script restart`.

If the current project has a `"restart"` script specified in `package.json`, then the following scripts will be run:

1. `prerestart`
2. `restart`
3. `postrestart`

If it does *not* have a `"restart"` script specified, but it does have `stop` and/or `start` scripts, then the following scripts will be run:

1. `prerestart`
2. `prestop`
3. `stop`
4. `poststop`
5. `prestart`
6. `start`
7. `poststart`
8. `postrestart`

Configuration

`ignore-scripts`

- Default: `false`
- Type: Boolean

If true, npm does not run scripts specified in `package.json` files.

Note that commands explicitly intended to run a particular script, such as `npm start`, `npm stop`, `npm restart`, `npm test`, and `npm run-script` will still run their intended script if `ignore-scripts` is set, but they will *not* run any pre- or post-scripts.

script-shell

- Default: `‘/bin/sh’` on POSIX systems, `‘cmd.exe’` on Windows
- Type: null or String

The shell to use for scripts run with the `npm exec`, `npm run` and `npm init <pkg>` commands.

See Also

- `npm run-script`
- `npm scripts`
- `npm test`
- `npm start`
- `npm stop`
- `npm restart`