ioctl FE_DISEQC_RECV_SLAVE_REPLY

> **System Message: ERROR/3 (`D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\(linux-master)(Documentation)(userspace-api)(media)(dvb)fe-diseqc-recv-slave-reply.rst`, line 2)**
>
> Unknown directive type "c:namespace".
>
> ```
>     .. c:namespace:: DTV.fe
> ```

Name

FE_DISEQC_RECV_SLAVE_REPLY - Receives reply from a DiSEqC 2.0 command

Synopsis

> **System Message: ERROR/3 (`D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\(linux-master)(Documentation)(userspace-api)(media)(dvb)fe-diseqc-recv-slave-reply.rst`, line 18)**
>
> Unknown directive type "c:macro".
>
> ```
>     .. c:macro:: FE_DISEQC_RECV_SLAVE_REPLY
> ```

```
int ioctl(int fd, FE_DISEQC_RECV_SLAVE_REPLY, struct dvb_diseqc_slave_reply *argp)
```

Arguments

`fd`

> File descriptor returned by :c:func:`open()`.
>
> > **System Message: ERROR/3 (`D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\(linux-master)(Documentation)(userspace-api)(media)(dvb)fe-diseqc-recv-slave-reply.rst`, line 26); *backlink***
> >
> > Unknown interpreted text role "c:func".

`argp`

> pointer to struct :c:type:`dvb_diseqc_slave_reply`.
>
> > **System Message: ERROR/3 (`D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\(linux-master)(Documentation)(userspace-api)(media)(dvb)fe-diseqc-recv-slave-reply.rst`, line 29); *backlink***
> >
> > Unknown interpreted text role "c:type".

Description

Receives reply from a DiSEqC 2.0 command.

The received message is stored at the buffer pointed by `argp`.

Return Value

On success 0 is returned.

On error -1 is returned, and the `errno` variable is set appropriately.

Generic error codes are described at the :ref:`Generic Error Codes <gen-errors>` chapter.