example.js

```
function getTemplate(templateName, callback) {
    require(["../require.context/templates/"+templateName], function(tmpl) {
        callback(tmpl());
    });
}
getTemplate("a", function(a) {
    console.log(a);
});
getTemplate("b", function(b) {
    console.log(b);
});
```

dist/output.js

```
▶ /* webpack runtime code */
```

```
var __webpack_exports__ = {};
/*!******************
 !*** ./example.js ***!
 \********
/*! unknown exports (runtime-defined) */
/*! runtime requirements: __webpack_require__.e, __webpack_require__.oe,
__webpack_require__, __webpack_require__.* */
function getTemplate(templateName, callback) {
    __webpack_require__.e(/*! AMD require */ 577).then(function() { var
__WEBPACK_AMD_REQUIRE_ARRAY__ = [__webpack_require__(1)("./"+templateName)];
(function(tmpl) {
       callback(tmpl());
   }).apply(null, __WEBPACK_AMD_REQUIRE_ARRAY__);}).catch(__webpack_require__.oe);
getTemplate("a", function(a) {
   console.log(a);
getTemplate("b", function(b) {
  console.log(b);
/*****/ })()
```

dist/577.output.js

```
(self["webpackChunk"] = self["webpackChunk"] || []).push([[577],[
/* 0 */,
/* 1 */
!*** ../require.context/templates/ sync ^\.\/.*$ ***!
 /*! default exports */
/*! exports [not provided] [no usage info] */
/*! runtime requirements: module, __webpack_require__.o, __webpack_require__ */
/***/ ((module, unused webpack exports, webpack require ) => {
var map = {
   "./a": 2,
   "./a.js": 2,
   "./b": 3,
   "./b.is": 3,
   "./c": 4,
   "./c.js": 4
};
function webpackContext(req) {
  var id = webpackContextResolve(req);
   return __webpack_require__(id);
}
function webpackContextResolve(req) {
   if(! webpack require .o(map, req)) {
      var e = new Error("Cannot find module '" + req + "'");
      e.code = 'MODULE NOT FOUND';
      throw e;
   return map[req];
webpackContext.keys = function webpackContextKeys() {
   return Object.keys(map);
webpackContext.resolve = webpackContextResolve;
module.exports = webpackContext;
webpackContext.id = 1;
/***/ }),
/* 2 */
!*** ../require.context/templates/a.js ***!
 \**************
/*! unknown exports (runtime-defined) */
/*! runtime requirements: module */
/*! CommonJS bailout: module.exports is used directly at 1:0-14 */
/***/ ((module) => {
module.exports = function() {
```

```
return "This text was generated by template A";
/***/ }),
/* 3 */
/*!**************************
 !*** ../require.context/templates/b.js ***!
 /*! unknown exports (runtime-defined) */
/*! runtime requirements: module */
/*! CommonJS bailout: module.exports is used directly at 1:0-14 */
/***/ ((module) => {
module.exports = function() {
  return "This text was generated by template B";
/***/ }),
/* 4 */
/*!**************************
 !*** ../require.context/templates/c.js ***!
 /*! unknown exports (runtime-defined) */
/*! runtime requirements: module */
/*! CommonJS bailout: module.exports is used directly at 1:0-14 ^{*}/
/***/ ((module) => {
module.exports = function() {
  return "This text was generated by template C";
/***/ })
]]);
```

Info

Unoptimized

```
dependent modules 240 bytes [dependent] 3 modules
../require.context/templates/ sync ^\.\/.*$ 217 bytes [built] [code generated]
    [no exports]
    [used exports unknown]
    amd require context ./example.js 2:1-4:3
webpack 5.51.1 compiled successfully
```

Production mode

```
asset output.js 1.82 KiB [emitted] [minimized] (name: main)
asset 577.output.js 609 bytes [emitted] [minimized]
chunk (runtime: main) output.js (main) 251 bytes (javascript) 4.98 KiB (runtime)
[entry] [rendered]
 > ./example.js main
 runtime modules 4.98 KiB 6 modules
  ./example.js 251 bytes [built] [code generated]
   [no exports used]
   entry ./example.js main
chunk (runtime: main) 577.output.js 457 bytes [rendered]
  > ./example.js 2:1-4:3
 dependent modules 240 bytes [dependent] 3 modules
  ../require.context/templates/ sync ^{...} 217 bytes [built] [code generated]
    [no exports]
   amd require context ./example.js 2:1-4:3
webpack 5.51.1 compiled successfully
```