

Here are the frequently asked questions about Ant Design and antd that you should look up before you ask in the community or create a new issue. We also maintain a [FAQ issues label](#) for common github issues.

---

### **Will you provide Sass/Stylus(etc.) style files in addition to the Less style files currently included?**

There is currently no plan to add support for Sass/Stylus(etc.) style files, but using tools on Google you can easily convert the provided Less files to your desired style format.

### **Select Dropdown DatePicker TimePicker Popover Popconfirm disappears when I click another popup component inside it. How do I resolve this?**

This is an old bug that has been fixed since `v3.11.x`. If you're using an older version, you can use `<Select getPopupContainer={trigger => trigger.parentElement}>` to render a component inside Popover. (Or other `getXxxContainer props`)

<https://ant.design/components/select/#Select-props>

Related issue: [#3487](#) [#3438](#)

### **How do I prevent Select Dropdown DatePicker TimePicker Popover Popconfirm scrolling with the page?**

Use `<Select getPopupContainer={trigger => trigger.parentElement}>` ([API reference](#)) to render a component inside the scroll area. If you need to config this globally in your application, try `<ConfigProvider getPopupContainer={trigger => trigger.parentElement}>` ([API reference](#))

And make sure that `parentElement` is `position: relative` or `position: absolute`.

Related issue: [#3487](#) [#3438](#)

### **How do I modify the default theme of Ant Design?**

See: <https://ant.design/docs/react/customize-theme>.

### **How do I modify Menu / Button (etc.)'s style?**

While you can override a component's style, we don't recommend doing so. antd is not only a set of React components, but also a design specification as well.

### **How do I replace Moment.js with Day.js to reduce bundle size?**

Please refer to [Replace Moment.js](#).

### **It doesn't work when I change defaultValue dynamically.**

The `defaultXxxx` (e.g. `defaultValue`) of `Input / Select` (etc...) only works on the first render. It is a specification of React. Please read [React's documentation](#).

### **Why does modifying props in mutable way not trigger a component update?**

antd use shallow compare of props to optimize performance. You should always pass the new object when updating the state. Please ref [React's document](#)

**After I set the `value` of an `Input / Select` (etc.) component, the value cannot be changed by user's action.**

Try `onChange` to change `value`, and please read [React's documentation](#).

**Components are not vertically aligned when placed in single row.**

Try [Space](#) component to make them aligned.

**`antd` overrides my global styles**

Yes, `antd` is designed to help you develop a complete background application. To do so, we override some global styles for styling convenience, and currently these cannot be removed or changed. More info at <https://github.com/ant-design/ant-design/issues/4331>.

Alternatively, follow the instructions in [How to avoid modifying global styles?](#)

**I cannot install `antd` and `antd`'s dependencies in mainland China.**

To potentially solve this, try [cnpm](#).

**I set `dependencies.antd` as the git repository in `package.json`, but it doesn't work.**

Please install `antd` with either `npm` or `yarn`.

**`message` and `notification` is lower case, but other components are capitalized. Is this a typo?**

No, `message` is just a function, not a React Component, thus it is not a typo that it is in lower case.

**`antd` doesn't work well in mobile.**

Please check [Ant Design Mobile](#) as a possible solution, as `antd` has not been optimized to work well on mobile. You can also try the [react-component](#) repositories which start with 'm-' 'rn-', which are also designed for mobile.

**Does `antd` supply standalone files like 'React'?**

Yes, you can [import `antd` with script tag](#), but we recommend using `npm` to import `antd`, as it is simple and easy to maintain.

**I can't visit `icon` in my network environment.**

You should deploy the iconfont files to your network by following this [example](#). [#1070](#)

After 3.9.x [we will also switch to using svg icons](#), so you won't need to deploy iconfont locally anymore as well.

**How do I extend `antd`'s components?**

If you need some features which should not be included in `antd`, try to extend `antd`'s component with [HOC](#). [more](#)

**How do I fix dynamic styles while using a Content Security Policy (CSP)?**

You can configure `nonce` by [ConfigProvider](#).

## When I set `mode` to `DatePicker / RangePicker`, why can I not select a year or month anymore?

In a real world development, you may need a `YearPicker`, `MonthRangePicker` or `WeekRangePicker`. You are trying to add `mode` to `DatePicker / RangePicker` expected to implement those pickers. However, the `DatePicker / RangePicker` cannot be selected and the panels won't close now.

- Reproduction link: <https://codesandbox.io/s/dank-brook-v1csy>
- Same issues: [#15572](#), [#16436](#), [#11938](#), [#11735](#), [#11586](#), [#10425](#), [#11053](#)

Like [the explanation](#) explains, this is because `<DatePicker mode="year" />` does not equal the `YearPicker`, nor is `<RangePicker mode="month" />` equal to `MonthRangePicker`. The `mode` property was added to support [showing time picker panel in DatePicker](#) in antd 3.0, which simply controls the displayed panel, and won't change the original date picking behavior of `DatePicker / RangePicker` (for instance you will still need to click date cell to finish selection in a `DatePicker`, whatever the `mode` is).

Likewise, `disabledDate` [cannot work on year/month panels](#) of `<DatePicker mode="year/month" />`, but only on cells of date panel.

### Workaround

You can refer to [this article](#) or [this article](#), using `mode` and `onPanelChange` to encapsulate a `YearPicker` or `MonthRangePicker` for your needs.

Or you can simply upgrade to [antd@4.0](#), in which we [added more XxxPickers](#) to meet those requirements, and `disabledDate` could be effect on those pickers too.

## message/notification/Modal.confirm lost styles when set `prefixCls` on `ConfigProvider`?

Static methods like `message/notification/Modal.confirm` are not using the same render tree as `<Button />`, but rendered to independent DOM node created by `ReactDOM.render`, which cannot access React context from `ConfigProvider`. Consider two solutions here:




1. Replace original usages with [message.useMessage](#), [notification.useNotification](#) and [Modal.useModal](#).
2. Use `ConfigProvider.config` to config `prefixCls` globally.

```
ConfigProvider.config({
  prefixCls: 'ant',
});
```

## Why shouldn't I use component internal props or state with ref?

You should only access the API by official doc with ref. Directly access internal `props` or `state` is not recommended which will make your code strong coupling with current version. Any refactor will break your code like refactor with [Hooks](#) version, delete or rename internal `props` or `state`, adjust internal node constructor, etc.

## How to spell Ant Design correctly?

-  **Ant Design**: Capitalized with space, for the design language.
-  **antd**: all lowercase, for the React UI library.
-  **ant.design**: For ant.design website url.

Here are some typical wrong examples:

- ✗ AntD
- ✗ antD
- ✗ Antd
- ✗ ant design
- ✗ AntDesign
- ✗ antdesign
- ✗ Antdesign

**Do you guys have any channel or website for submitting monetary donations, like through PayPal or Alipay?**

<https://opencollective.com/ant-design>

---

## Errors and Warnings

Here are some errors & warnings that you may encounter while using antd, although most of these are not actual bugs of antd itself.

### Adjacent JSX elements must be wrapped in an enclosing tag

Check out [this answer from StackOverflow](#), along with also reading [React's documentation](#) to solve this.

### React.createElement: type should not be null, undefined, boolean, or number. It should be a string (for DOM elements) or a ReactClass (for composite components)

Please make sure that you import `antd` 's components correctly. Read the corresponding documentation of the `antd` 's version which you use, and pay attention to typos.

### rm is not recognized as an internal or external command

Please read [this issue](#), or try Linux/Unix.

### Failed propType: Invalid prop `AAA` of type `BBB` supplied to `CCC` , expected `DDD` . Check the render method of `EEE` .

Please read the corresponding documentation of the `antd` 's version which you are currently using, and make sure that you pass values with correct type to `antd` 's components,

### Unknown option: xxx/package.json.presets

Check out [this answer from Stack Overflow](#).

### Invariant Violation: findComponentRoot(...): Unable to find element.

You may have imported `React` twice. Set `React` & `ReactDOM` as external, if you are using webpack, see [#525](#). If you are using others (browserify, etc...), please read their documentation and find options which can set `React` & `ReactDOM` as external.