## Generating Yaml Docs For Your Own cobra.Command

Generating yaml files from a cobra command is incredibly easy. An example is as follows:

```
package main

import (
    "log"

    "github.com/spf13/cobra"
    "github.com/spf13/cobra/doc"
)

func main() {
    cmd := &cobra.Command{
        Use: "test",
        Short: "my test program",
    }
    err := doc.GenYamlTree(cmd, "/tmp")
    if err != nil {
        log.Fatal(err)
    }
}
```

That will get you a Yaml document /tmp/test.yaml

## Generate yaml docs for the entire command tree

This program can actually generate docs for the kubectl command in the kubernetes project

```
package main

import (
    "io/ioutil"
    "log"
    "os"

    "k8s.io/kubernetes/pkg/kubectl/cmd"
    cmdutil "k8s.io/kubernetes/pkg/kubectl/cmd/util"

    "github.com/spf13/cobra/doc"
)

func main() {
```

```
kubectl := cmd.NewKubectlCommand(cmdutil.NewFactory(nil), os.Stdin, ioutil.Discard, iout
err := doc.GenYamlTree(kubectl, "./")
if err != nil {
    log.Fatal(err)
}
```

This will generate a whole series of files, one for each command in the tree, in the directory specified (in this case "./")

## Generate yaml docs for a single command

You may wish to have more control over the output, or only generate for a single command, instead of the entire command tree. If this is the case you may prefer to GenYaml instead of GenYamlTree

```
out := new(bytes.Buffer)
doc.GenYaml(cmd, out)
```

This will write the yaml doc for ONLY "cmd" into the out, buffer.

## Customize the output

Both GenYaml and GenYamlTree have alternate versions with callbacks to get some control of the output:

The filePrepender will prepend the return value given the full filepath to the rendered Yaml file. A common use case is to add front matter to use the generated documentation with Hugo:

```
const fmTemplate = `---
date: %s
title: "%s"
slug: %s
url: %s
---
filePrepender := func(filename string) string {
    now := time.Now().Format(time.RFC3339)
    name := filepath.Base(filename)
```

```
base := strings.TrimSuffix(name, path.Ext(name))
   url := "/commands/" + strings.ToLower(base) + "/"
   return fmt.Sprintf(fmTemplate, now, strings.Replace(base, "_", " ", -1), base, url)
}
The linkHandler can be used to customize the rendered internal links to the commands, given a filename:
linkHandler := func(name string) string {
   base := strings.TrimSuffix(name, path.Ext(name))
   return "/commands/" + strings.ToLower(base) + "/"
}
```