Radio Interface

This interface is intended for AM and FM (analog) radio receivers and transmitters.

Conventionally V4L2 radio devices are accessed through character device special files named /dev/radio and /dev/radio0 to /dev/radio63 with major number 81 and minor numbers 64 to 127.

Querying Capabilities

Devices supporting the radio interface set the V4L2_CAP_RADIO and V4L2_CAP_TUNER or V4L2_CAP_MODULATOR flag in the capabilities field of struct :c:type:`v4l2_capability` returned by the :ref:`VIDIOC_QUERYCAP` ioctl. Other combinations of capability flags are reserved for future extensions.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\(linux-master) (Documentation) (userspace-api) (media) (v41) dev-radio.rst, line 20); backlink

Unknown interpreted text role "c:type".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\(linux-master) (Documentation) (userspace-api) (media) (v41) dev-radio.rst, line 20); backlink

Unknown interpreted text role "ref".

Supplemental Functions

Radio devices can support ref`controls <control>`, and must support the ref`tuner or modulator <tuner>` ioctls.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\(linux-master) (Documentation) (userspace-api) (media) (v41) dev-radio.rst, line 31); backlink

Unknown interpreted text role 'ref'.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\(linux-master) (Documentation) (userspace-api) (media) (v41) dev-radio.rst, line 31); backlink

Unknown interpreted text role "ref".

They do not support the video input or output, audio input or output, video standard, cropping and scaling, compression and streaming parameter, or overlay ioctls. All other ioctls and I/O methods are reserved for future extensions.

Programming

Radio devices may have a couple audio controls (as discussed in ref. control) such as a volume control, possibly custom controls. Further all radio devices have one tuner or modulator (these are discussed in ref. tuner) with index number zero to select the radio frequency and to determine if a monaural or FM stereo program is received/emitted. Drivers switch automatically between AM and FM depending on the selected frequency. The ref. VIDIOC G_TUNER < VIDIOC G_TUNER>` or ref. VIDIOC G_MODULATOR < VIDIOC G_MODULATOR>` ioctl reports the supported frequency range.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\(linux-master) (Documentation) (userspace-api) (media) (v41) dev-radio.rst, line 43); backlink

Unknown interpreted text role 'ref'.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\(linux-master) (Documentation) (userspace-api) (media) (v41) dev-radio.rst, line 43); backlink

Unknown interpreted text role "ref".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\(linux-master) (Documentation) (userspace-api) (media) (v41) dev-radio.rst, line 43); backlink

Unknown interpreted text role 'ref'.

 $System\,Message: ERROR/3~(\texttt{D:\noboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\ (linux-master)~(Documentation)~(userspace-api)~(media)~(v41)~dev-radio.rst, line~43); backlink$

Unknown interpreted text role 'ref'.