DPAA2 MAC / PHY support

Overview

The DPAA2 MAC / PHY support consists of a set of APIs that help DPAA2 network drivers (dpaa2-eth, dpaa2-ethsw) interract with the PHY library.

DPAA2 Software Architecture

Among other DPAA2 objects, the fsl-mc bus exports DPNI objects (abstracting a network interface) and DPMAC objects (abstracting a MAC). The dpaa2-eth driver probes on the DPNI object and connects to and configures a DPMAC object with the help of phylink.

Data connections may be established between a DPNI and a DPMAC, or between two DPNIs. Depending on the connection type, the netif_carrier_[on/off] is handled directly by the dpaa2-eth driver or by phylink.

System Message: WARNING/2 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\networking\device_drivers\ethernet\freescale\dpaa2\[linux-master][Documentation][networking][device_drivers][ethernet][freescale][dpaa2]mac-phy-support.rst, line 28)

Cannot analyze code. No Pygments lexer found for "none".

```
.. code-block:: none

  Sources of abstracted link state information presented by the MC firmware

                                                 +---------------------------------------
  +------------+                  +----------+  |                            xgmac_mdio
  | net_device |                  | phylink |--|  +-----+  +-----+  +-----+  +-----+
  +------------+                  +----------+  |  | PHY |  | PHY |  | PHY |  | PHY |
        |                               |       |  +-----+  +-----+  +-----+  +-----+
      +-----------------------------------+     |                    External MDIO bus
      |            dpaa2-eth              |     +---------------------------------------
      +-----------------------------------+
        |                                 |                                          Linux
  ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~
        |                                 |                                   MC firmware
        |                /|               V
  +-----------+          / |         +-----------+
  |           |         /  |         |           |
  |           |        |   |         |           |
  |   DPNI    |<-------|   |<--------|   DPMAC   |
  |           |        |   |         |           |
  |           |         \  |<---+    |           |
  +-----------+          \ |    |    +-----------+
                          \|    |
                                |
            +-------------------------------------+
            | MC firmware polling MAC PCS for link |
            |  +-----+  +-----+  +-----+  +-----+  |
            |  | PCS |  | PCS |  | PCS |  | PCS |  |
            |  +-----+  +-----+  +-----+  +-----+  |
            |                    Internal MDIO bus |
            +-------------------------------------+
```

Depending on an MC firmware configuration setting, each MAC may be in one of two modes:

- DPMAC_LINK_TYPE_FIXED: the link state management is handled exclusively by the MC firmware by polling the MAC PCS. Without the need to register a phylink instance, the dpaa2-eth driver will not bind to the connected dpmac object at all.
- DPMAC_LINK_TYPE_PHY: The MC firmware is left waiting for link state update events, but those are in fact passed strictly between the dpaa2-mac (based on phylink) and its attached net_device driver (dpaa2-eth, dpaa2-ethsw), effectively bypassing the firmware.

Implementation

At probe time or when a DPNI's endpoint is dynamically changed, the dpaa2-eth is responsible to find out if the peer object is a

DPMAC and if this is the case, to integrate it with PHYLINK using the dpaa2_mac_connect() API, which will do the following:

- look up the device tree for PHYLINK-compatible of binding (phy-handle)
- will create a PHYLINK instance associated with the received net_device
- connect to the PHY using phylink_of_phy_connect()

The following phylink_mac_ops callback are implemented:

- .validate() will populate the supported linkmodes with the MAC capabilities only when the phy_interface_t is RGMII_* (at the moment, this is the only link type supported by the driver).
- .mac_config() will configure the MAC in the new configuration using the dpmac_set_link_state() MC firmware API.
- .mac_link_up() / .mac_link_down() will update the MAC link using the same API described above.

At driver unbind() or when the DPNI object is disconnected from the DPMAC, the dpaa2-eth driver calls dpaa2_mac_disconnect() which will, in turn, disconnect from the PHY and destroy the PHYLINK instance.

In case of a DPNI-DPMAC connection, an 'ip link set dev eth0 up' would start the following sequence of operations:

1. phylink_start() called from .dev_open().
2. The .mac_config() and .mac_link_up() callbacks are called by PHYLINK.
3. In order to configure the HW MAC, the MC Firmware API dpmac_set_link_state() is called.
4. The firmware will eventually setup the HW MAC in the new configuration.
5. A netif_carrier_on() call is made directly from PHYLINK on the associated net_device.
6. The dpaa2-eth driver handles the LINK_STATE_CHANGE irq in order to enable/disable Rx taildrop based on the pause frame settings.

System Message: WARNING/2 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\networking\device_drivers\ethernet\freescale\dpaa2\[linux-master][Documentation][networking][device_drivers][ethernet][freescale][dpaa2]mac-phy-support.rst, line 115)

Cannot analyze code. No Pygments lexer found for "none".

```
.. code-block:: none

  +---------+               +---------+
  | PHYLINK |-------------->|  eth0   |
  +---------+           (5) +---------+
  (1) ^   |
      |   |
      |   v (2)
  +-------------------------------------+
  |             dpaa2-eth               |
  +-------------------------------------+
          |                     ^ (6)
          |                     |
          v (3)                 |
  +---------+---------------+---------+
  |  DPMAC  |               |  DPNI   |
  +---------+               +---------+
  |            MC Firmware              |
  +-------------------------------------+
          |
          |
          v (4)
  +-------------------------------------+
  |              HW MAC                 |
  +-------------------------------------+
```

In case of a DPNI-DPNI connection, a usual sequence of operations looks like the following:

1. ip link set dev eth0 up
2. The dpni_enable() MC API called on the associated fsl_mc_device.
3. ip link set dev eth1 up
4. The dpni_enable() MC API called on the associated fsl_mc_device.
5. The LINK_STATE_CHANGED irq is received by both instances of the dpaa2-eth driver because now the operational link state is up.
6. The netif_carrier_on() is called on the exported net_device from link_state_update().

System Message: WARNING/2 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\networking\device_drivers\ethernet\freescale\dpaa2\[linux-master][Documentation][networking][device_drivers][ethernet][freescale][dpaa2]mac-phy-

support.rst, line 153)

Cannot analyze code. No Pygments lexer found for "none".

```
.. code-block:: none

  +---------+                +---------+
  |  eth0   |                |  eth1   |
  +---------+                +---------+
      |  ^                       ^  |
      |  |                       |  |
  (1) v  | (6)              (6) |  v (3)
  +---------+                +---------+
  |dpaa2-eth|                |dpaa2-eth|
  +---------+                +---------+
      |  ^                       ^  |
      |  |                       |  |
  (2) v  | (5)              (5) |  v (4)
  +---------+----------------+---------+
  |  DPNI   |                |  DPNI   |
  +---------+                +---------+
  |             MC Firmware             |
  +-------------------------------------+
```

Exported API

Any DPAA2 driver that drivers endpoints of DPMAC objects should service its _EVENT_ENDPOINT_CHANGED irq and connect/disconnect from the associated DPMAC when necessary using the below listed API:

```
- int dpaa2_mac_connect(struct dpaa2_mac *mac);
- void dpaa2_mac_disconnect(struct dpaa2_mac *mac);
```

A phylink integration is necessary only when the partner DPMAC is not of TYPE_FIXED. One can check for this condition using the below API:

```
- bool dpaa2_mac_is_type_fixed(struct fsl_mc_device *dpmac_dev,struct fsl_mc_io *mc_io);
```

Before connection to a MAC, the caller must allocate and populate the dpaa2_mac structure with the associated net_device, a pointer to the MC portal to be used and the actual fsl_mc_device structure of the DPMAC.