

This example demonstrates various types of source-maps.

example.coffee

```
# Taken from http://coffeescript.org/

# Objects:
math =
  root:    Math.sqrt
  square:  square
  cube:    (x) -> x * square x

# Splats:
race = (winner, runners...) ->
  print winner, runners
```

webpack.config.js

```
var path = require("path");

module.exports = [
  "eval",
  "eval-cheap-source-map",
  "eval-cheap-module-source-map",
  "eval-source-map",
  "cheap-source-map",
  "cheap-module-source-map",
  "inline-cheap-source-map",
  "inline-cheap-module-source-map",
  "source-map",
  "inline-source-map",
  "hidden-source-map",
  "nosources-source-map"
].map(devtool => ({
  mode: "development",
  entry: {
    bundle: "coffee-loader!./example.coffee"
  },
  output: {
    path: path.join(__dirname, "dist"),
    filename: `[name]-${devtool}.js`
  },
  devtool,
  optimization: {
    runtimeChunk: true
  }
}));
```

Generated source-maps

source-map.js and source-map.js.map

```
(self["webpackChunk"] = self["webpackChunk"] || []).push([[0], [
/* 0 */
/*!*****!\
  *** .././node_modules/coffee-loader/dist/cjs.js!./example.coffee ***!
\*****/
/*! unknown exports (runtime-defined) */
/*! runtime requirements: */
****/ (() => {

// Taken from http://coffeescript.org/

// Objects:
var math, race;

math = {
  root: Math.sqrt,
  square: square,
  cube: function(x) {
    return x * square(x);
  }
};

// Splats:
race = function(winner, ...runners) {
  return print(winner, runners);
};

****/ })
],
*****/ __webpack_require__ => { // webpackRuntimeModules
*****/ var __webpack_exec__ = (moduleId) =>
( __webpack_require__(__webpack_require__.s = moduleId))
*****/ var __webpack_exports__ = (__webpack_exec__(0));
*****/ }
]);
//# sourceMappingURL=bundle-source-map.js.map
```

```
{
  "version": 3,
  "file": "./bundle-source-map.js",
  "mappings": ";;;;;;;;;AAEU;;;AAAA;;AACV,OACE;EAAA,MAAQ,IAAI,CAAC,IAAb;EACA,QAAQ,["
  "webpack:///./example.coffee"],
  "sourcesContent": [
    "# Taken from http://coffeescript.org/\n\n# Objects:\nmath =\n  root:  Math.sqrt\n  square:\n  cube:  (x) -> x * square x\n\n# Splats:\nrace = (winner, runners...) ->\n  print winner, runners\n"],
  "names": [],
  "sourceRoot": ""
}
```

hidden-source-map.js and hidden-source-map.js.map

```
(self["webpackChunk"] = self["webpackChunk"] || []).push([[0], [
/* 0 */
/*!*****!\
  !*** ../node_modules/coffee-loader/dist/cjs.js!./example.coffee ***!
  \*****/
/*! unknown exports (runtime-defined) */
/*! runtime requirements: */
****/ (() => {

// Taken from http://coffeescript.org/

// Objects:
var math, race;

math = {
  root: Math.sqrt,
  square: square,
  cube: function(x) {
    return x * square(x);
  }
};

// Splats:
race = function(winner, ...runners) {
  return print(winner, runners);
};

****/ })
],
*****/ __webpack_require__ => { // webpackRuntimeModules
*****/ var __webpack_exec__ = (moduleId) =>
(__webpack_require__(__webpack_require__.s = moduleId))
*****/ var __webpack_exports__ = (__webpack_exec__(0));
*****/ }
]);
```

```
{
  "version": 3,
  "file": "../bundle-hidden-source-map.js",
  "mappings": ";;;;;;;;;AAEU;;;AAAA;AACV,OACE;EAAA,MAAQ,IAAI,CAAC,IAAb;EACA,QAAQ,["
  "webpack:///./example.coffee",
  "sourcesContent": [
    "# Taken from http://coffeescript.org/\n\n# Objects:\nmath =\n  root:  Math.sqrt\n  square:\n  cube:  (x) -> x * square x\n\n# Splats:\nrace = (winner, runners...) ->\n  print winner, runners\n"],
  "names": [],
  "sourceRoot": ""
}
```

inline-source-map.js

```

(self["webpackChunk"] = self["webpackChunk"] || []).push([[0], [
/* 0 */
/*****\
    !*** ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee ***!
    \*****/
/! unknown exports (runtime-defined) */
/! runtime requirements: */
****/ (() => {

// Taken from http://coffeescript.org/

// Objects:
var math, race;

math = {
  root: Math.sqrt,
  square: square,
  cube: function(x) {
    return x * square(x);
  }
};

// Splats:
race = function(winner, ...runners) {
  return print(winner, runners);
};

****/ })
],
/*****/ __webpack_require__ => { // webpackRuntimeModules
/*****/ var __webpack_exec__ = (moduleId) =>
(__webpack_require__(__webpack_require__.s = moduleId))
/*****/ var __webpack_exports__ = (__webpack_exec__(0));
/*****/ }
]);
//# sourceMappingURL=data:application/json;charset=utf-
8;base64,eyJ2ZXJzYW9uIjozLCJmaWxlIjoiaW9idW5kbGUtaW5saW5ldXJjZS1tYXAuanMiLCJtYXBwaW50IjozLCJmaWxlIjoiaW9idW5kbGUtaW5saW5ldXJjZS1tYXAuanMiLCJm

```

nosources-source-map.js.map

```

{"version":3,"file":"./bundle-nosources-source-
map.js","mappings":";;;;;;;;;AAEU;;;AAAA;;AACV,OACE;EAAA,MAAQ,IAAI,CAAC,IAAb;EACA,QAAQ,
[\"webpack://./example.coffee\"],\"names\": [],\"sourceRoot\":\""}

```

eval-source-map.js

```

/*
 * ATTENTION: An "eval-source-map" devtool has been used.
 * This devtool is neither made for production nor for readable output files.
 * It uses "eval()" calls to create a separate source file with attached SourceMaps
in the browser devtools.
 * If you are trying to read the output file, select a different devtool
(https://webpack.js.org/configuration/devtool/)
 * or disable the default devtool with "devtool: false".
 * If you are looking for production-ready output files, see mode: "production"
(https://webpack.js.org/configuration/mode/).
 */
(self["webpackChunk"] = self["webpackChunk"] || []).push([[0], [
/* 0 */
/*!*****!*\
  *** ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee ***!
  \******/
/*! unknown exports (runtime-defined) */
/*! runtime requirements: */
/***/ (() => {

eval("// Taken from http://coffeescript.org/\n\n// Objects:\nvar math, race;\n\nmath
= {\n  root: Math.sqrt,\n  square: square,\n  cube: function(x) {\n    return x *
square(x);\n  }\n};\n\n// Splats:\nrace = function(winner, ...runners) {\n  return
print(winner, runners);\n};\n\n# sourceMappingURL=[module]\n\n#
sourceMappingURL=data:application/json;charset=utf-
8;base64,eyJ2ZXJzaW9uIjozLCJzb3VyY2VSb290IjoiIiwic291cmNlcyI6WyJ3ZWJwYWNrOi8vLy4vZXhhbG
sourceURL=webpack-internal:///0\n");

/***/ })
],
/*****/ __webpack_require__ => { // webpackRuntimeModules
/*****/ var __webpack_exec__ = (moduleId) =>
(__webpack_require__(__webpack_require__.s = moduleId))
/*****/ var __webpack_exports__ = (__webpack_exec__(0));
/*****/ }
});

```

eval.js

```

/*
 * ATTENTION: The "eval" devtool has been used (maybe by default in mode:
"development").
 * This devtool is neither made for production nor for readable output files.
 * It uses "eval()" calls to create a separate source file in the browser devtools.
 * If you are trying to read the output file, select a different devtool
(https://webpack.js.org/configuration/devtool/)
 * or disable the default devtool with "devtool: false".
 * If you are looking for production-ready output files, see mode: "production"
(https://webpack.js.org/configuration/mode/).

```

```

*/
(self["webpackChunk"] = self["webpackChunk"] || []).push([[0], [
/* 0 */
/*!*****!\
  !*** ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee ***!
  \*****/
/*! unknown exports (runtime-defined) */
/*! runtime requirements: */
/***/ (function() => {

eval("// Taken from http://coffeescript.org/\n\n// Objects:\nvar math, race;\n\nmath
= {\n  root: Math.sqrt,\n  square: square,\n  cube: function(x) {\n    return x *
square(x);\n  }\n};\n\n// Splats:\nrace = function(winner, ...runners) {\n  return
print(winner, runners);\n};\n\n\n//#
sourceURL=webpack:///./example.coffee?../../node_modules/coffee-
loader/dist/cjs.js");

/***/ })
],
/***/ __webpack_require__ => { // webpackRuntimeModules
/***/ var __webpack_exec__ = (moduleId) =>
(__webpack_require__(__webpack_require__.s = moduleId))
/***/ var __webpack_exports__ = (__webpack_exec__(0));
/***/ }
]);

```

eval-cheap-source-map.js

```

/*
 * ATTENTION: An "eval-source-map" devtool has been used.
 * This devtool is neither made for production nor for readable output files.
 * It uses "eval()" calls to create a separate source file with attached SourceMaps
in the browser devtools.
 * If you are trying to read the output file, select a different devtool
(https://webpack.js.org/configuration/devtool/)
 * or disable the default devtool with "devtool: false".
 * If you are looking for production-ready output files, see mode: "production"
(https://webpack.js.org/configuration/mode/).
*/
(self["webpackChunk"] = self["webpackChunk"] || []).push([[0], [
/* 0 */
/*!*****!\
  !*** ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee ***!
  \*****/
/*! unknown exports (runtime-defined) */
/*! runtime requirements: */
/***/ (function() => {

eval("// Taken from http://coffeescript.org/\n\n// Objects:\nvar math, race;\n\nmath
= {\n  root: Math.sqrt,\n  square: square,\n  cube: function(x) {\n    return x *

```

```

square(x);\n } \n};\n\n// Splats:\n\nrace = function(winner, ...runners) {\n  return
print(winner, runners);\n};\n\n// # sourceMappingURL=[module]\n\n// #
sourceMappingURL=data:application/json;charset=utf-
8;base64,eyJ2ZXJzaW9uIjozLCJmaWxlIjoiaWMC5qcyIsIm1hcHBmdzIjoiaUFBQTtBQUNBO0FBQ0E7QUFDQ
sourceURL=webpack-internal:///0\n");

/***/ })

],
/*****/ __webpack_require__ => { // webpackRuntimeModules
/*****/ var __webpack_exec__ = (moduleId) =>
( __webpack_require__(__webpack_require__.s = moduleId))
/*****/ var __webpack_exports__ = ( __webpack_exec__(0));
/*****/ }

]);

```

eval-cheap-module-source-map.js

```

/*
 * ATTENTION: An "eval-source-map" devtool has been used.
 * This devtool is neither made for production nor for readable output files.
 * It uses "eval()" calls to create a separate source file with attached SourceMaps
in the browser devtools.
 * If you are trying to read the output file, select a different devtool
(https://webpack.js.org/configuration/devtool/)
 * or disable the default devtool with "devtool: false".
 * If you are looking for production-ready output files, see mode: "production"
(https://webpack.js.org/configuration/mode/).
 */

(self["webpackChunk"] = self["webpackChunk"] || []).push([[0], [
/* 0 */

/*****/
!*****!*\
  !*** .././node_modules/coffee-loader/dist/cjs.js!./example.coffee ***!
  \*****/
/*****/ unknown exports (runtime-defined) */
/*****/ runtime requirements: */
/*****/ (() => {

eval("// Taken from http://coffeescript.org/\n\n// Objects:\n\nvar math, race;\n\nmath
= {\n  root: Math.sqrt,\n  square: square,\n  cube: function(x) {\n    return x *
square(x);\n  } \n};\n\n// Splats:\n\nrace = function(winner, ...runners) {\n  return
print(winner, runners);\n};\n\n// # sourceMappingURL=[module]\n\n// #
sourceMappingURL=data:application/json;charset=utf-
8;base64,eyJ2ZXJzaW9uIjozLCJzaW9uIjozLCJmaWxlIjoiaWMC5qcyIsIm1hcHBmdzIjoiaUFBQTtBQUNBO0FBQ0E7QUFDQ
sourceURL=webpack-internal:///0\n");

/***/ })

],
/*****/ __webpack_require__ => { // webpackRuntimeModules
/*****/ var __webpack_exec__ = (moduleId) =>
( __webpack_require__(__webpack_require__.s = moduleId))

```

```

/*****/ var __webpack_exports__ = (__webpack_exec__(0));
/*****/ }
});

```

cheap-module-source-map.js.map

```

{"version":3,"file":"./bundle-cheap-module-source-
map.js","mappings":";;;;;;;;;AAEA;;;AAAA;;AACA;AACA;AACA;AACA;AAAA;AAAA;AAFA;;;AAKA;AA
["webpack:///./example.coffee"],"sourcesContent":["# Taken from
http://coffeescript.org/\n\n# Objects:\nmath =\n  root:    Math.sqrt\n  square:
square\n  cube:    (x) -> x * square x\n\n# Splats:\n\nrace = (winner, runners...) ->\n  print winner, runners\n"],"names":[],"sourceRoot":""}

```

cheap-source-map.js.map

```

{"version":3,"file":"./bundle-cheap-source-
map.js","mappings":";;;;;;;;;AAAA;AACA;AACA;AACA;AACA;AACA;AACA;AACA;AACA;AACA;AA
["webpack:///./example.coffee"],"sourcesContent":["// Taken from
http://coffeescript.org/\n\n// Objects:\n\nvar math, race;\n\nmath = {\n  root:
Math.sqrt,\n  square: square,\n  cube: function(x) {\n    return x * square(x);\n
}\n};\n\n// Splats:\n\nrace = function(winner, ...runners) {\n  return print(winner,
runners);\n};\n"],"names":[],"sourceRoot":""}

```

webpack output

```

asset ./runtime~bundle-eval.js 5.46 KiB [emitted] (name: runtime~bundle)
asset ./bundle-eval.js 1.53 KiB [emitted] (name: bundle)
Entrypoint bundle 6.99 KiB = ./runtime~bundle-eval.js 5.46 KiB ./bundle-eval.js 1.53 KiB
chunk (runtime: runtime~bundle) ./bundle-eval.js (bundle) 256 bytes [initial]
[rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-eval.js (runtime~bundle) 2.46 KiB
[entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully

asset ./runtime~bundle-eval-cheap-source-map.js 5.46 KiB [emitted] (name:
runtime~bundle)
asset ./bundle-eval-cheap-source-map.js 2.2 KiB [emitted] (name: bundle)
Entrypoint bundle 7.66 KiB = ./runtime~bundle-eval-cheap-source-map.js 5.46 KiB

```



```

./bundle-eval-cheap-source-map.js 2.2 KiB
chunk (runtime: runtime~bundle) ./bundle-eval-cheap-source-map.js (bundle) 256 bytes
[initial] [rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-eval-cheap-source-map.js
(runtime~bundle) 2.46 KiB [entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully

asset ./runtime~bundle-eval-cheap-module-source-map.js 5.46 KiB [emitted] (name:
runtime~bundle)
asset ./bundle-eval-cheap-module-source-map.js 2.33 KiB [emitted] (name: bundle)
Entrypoint bundle 7.79 KiB = ./runtime~bundle-eval-cheap-module-source-map.js 5.46 KiB
./bundle-eval-cheap-module-source-map.js 2.33 KiB
chunk (runtime: runtime~bundle) ./bundle-eval-cheap-module-source-map.js (bundle) 256
bytes [initial] [rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-eval-cheap-module-source-map.js
(runtime~bundle) 2.46 KiB [entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully

asset ./runtime~bundle-eval-source-map.js 5.46 KiB [emitted] (name: runtime~bundle)
asset ./bundle-eval-source-map.js 2.33 KiB [emitted] (name: bundle)
Entrypoint bundle 7.79 KiB = ./runtime~bundle-eval-source-map.js 5.46 KiB ./bundle-
eval-source-map.js 2.33 KiB
chunk (runtime: runtime~bundle) ./bundle-eval-source-map.js (bundle) 256 bytes
[initial] [rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-eval-source-map.js (runtime~bundle)
2.46 KiB [entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully

asset ./runtime~bundle-cheap-source-map.js 4.97 KiB [emitted] (name: runtime~bundle) 1
related asset
asset ./bundle-cheap-source-map.js 938 bytes [emitted] (name: bundle) 1 related asset

```

```
Entrypoint bundle 5.89 KiB (4.84 KiB) = ./runtime~bundle-cheap-source-map.js 4.97 KiB
./bundle-cheap-source-map.js 938 bytes 2 auxiliary assets
chunk (runtime: runtime~bundle) ./bundle-cheap-source-map.js (bundle) 256 bytes
[initial] [rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-cheap-source-map.js (runtime~bundle)
2.46 KiB [entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully

asset ./runtime~bundle-cheap-module-source-map.js 4.98 KiB [emitted] (name:
runtime~bundle) 1 related asset
asset ./bundle-cheap-module-source-map.js 945 bytes [emitted] (name: bundle) 1 related
asset
Entrypoint bundle 5.9 KiB (4.76 KiB) = ./runtime~bundle-cheap-module-source-map.js
4.98 KiB ./bundle-cheap-module-source-map.js 945 bytes 2 auxiliary assets
chunk (runtime: runtime~bundle) ./bundle-cheap-module-source-map.js (bundle) 256 bytes
[initial] [rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-cheap-module-source-map.js
(runtime~bundle) 2.46 KiB [entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully

asset ./runtime~bundle-inline-cheap-source-map.js 10.8 KiB [emitted] (name:
runtime~bundle)
asset ./bundle-inline-cheap-source-map.js 1.62 KiB [emitted] (name: bundle)
Entrypoint bundle 12.4 KiB = ./runtime~bundle-inline-cheap-source-map.js 10.8 KiB
./bundle-inline-cheap-source-map.js 1.62 KiB
chunk (runtime: runtime~bundle) ./bundle-inline-cheap-source-map.js (bundle) 256 bytes
[initial] [rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-inline-cheap-source-map.js
(runtime~bundle) 2.46 KiB [entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully
```

```

asset ./runtime~bundle-inline-cheap-module-source-map.js 10.8 KiB [emitted] (name: runtime~bundle)
asset ./bundle-inline-cheap-module-source-map.js 1.51 KiB [emitted] (name: bundle)
Entrypoint bundle 12.3 KiB = ./runtime~bundle-inline-cheap-module-source-map.js 10.8 KiB ./bundle-inline-cheap-module-source-map.js 1.51 KiB
chunk (runtime: runtime~bundle) ./bundle-inline-cheap-module-source-map.js (bundle) 256 bytes [initial] [rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-inline-cheap-module-source-map.js (runtime~bundle) 2.46 KiB [entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully

asset ./runtime~bundle-source-map.js 4.96 KiB [emitted] (name: runtime~bundle) 1 related asset
asset ./bundle-source-map.js 932 bytes [emitted] (name: bundle) 1 related asset
Entrypoint bundle 5.88 KiB (4.86 KiB) = ./runtime~bundle-source-map.js 4.96 KiB ./bundle-source-map.js 932 bytes 2 auxiliary assets
chunk (runtime: runtime~bundle) ./bundle-source-map.js (bundle) 256 bytes [initial] [rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-source-map.js (runtime~bundle) 2.46 KiB [entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully

asset ./runtime~bundle-inline-source-map.js 10.8 KiB [emitted] (name: runtime~bundle)
asset ./bundle-inline-source-map.js 1.64 KiB [emitted] (name: bundle)
Entrypoint bundle 12.4 KiB = ./runtime~bundle-inline-source-map.js 10.8 KiB ./bundle-inline-source-map.js 1.64 KiB
chunk (runtime: runtime~bundle) ./bundle-inline-source-map.js (bundle) 256 bytes [initial] [rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-inline-source-map.js (runtime~bundle) 2.46 KiB [entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully

```

```

asset ./runtime~bundle-hidden-source-map.js 4.91 KiB [emitted] (name: runtime~bundle)
1 related asset
asset ./bundle-hidden-source-map.js 886 bytes [emitted] (name: bundle) 1 related asset
Entrypoint bundle 5.78 KiB (4.87 KiB) = ./runtime~bundle-hidden-source-map.js 4.91 KiB
./bundle-hidden-source-map.js 886 bytes 2 auxiliary assets
chunk (runtime: runtime~bundle) ./bundle-hidden-source-map.js (bundle) 256 bytes
[initial] [rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-hidden-source-map.js (runtime~bundle)
2.46 KiB [entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully

asset ./runtime~bundle-nosources-source-map.js 4.97 KiB [emitted] (name:
runtime~bundle) 1 related asset
asset ./bundle-nosources-source-map.js 942 bytes [emitted] (name: bundle) 1 related
asset
Entrypoint bundle 5.89 KiB (1.24 KiB) = ./runtime~bundle-nosources-source-map.js 4.97
KiB ./bundle-nosources-source-map.js 942 bytes 2 auxiliary assets
chunk (runtime: runtime~bundle) ./bundle-nosources-source-map.js (bundle) 256 bytes
[initial] [rendered]
  > coffee-loader!./example.coffee bundle
  ../../node_modules/coffee-loader/dist/cjs.js!./example.coffee 256 bytes [built]
[code generated]
  [used exports unknown]
  entry coffee-loader!./example.coffee bundle
chunk (runtime: runtime~bundle) ./runtime~bundle-nosources-source-map.js
(runtime~bundle) 2.46 KiB [entry] [rendered]
  > coffee-loader!./example.coffee bundle
  runtime modules 2.46 KiB 3 modules
webpack 5.51.1 compiled successfully

```