

Basic text writing, including headings, body text, lists, and more.

### When To Use

- When need to display a title or paragraph contents in Articles/Blogs/Notes.
- When you need copyable/editable/ellipsis texts.

### API

#### Typography.Text

Property	Description	Type	Default	Version
code	Code style	boolean	false	
copyable	Whether to be copyable, customize it via setting an object	boolean   <a href="#">copyable</a>	false	<a href="#">copyable</a>
delete	Deleted line style	boolean	false	
disabled	Disabled content	boolean	false	
editable	If editable. Can control edit state when is object	boolean   <a href="#">editable</a>	false	<a href="#">editable</a>
ellipsis	Display ellipsis when text overflows , can't configure expandable、 rows and onExpand by using object	boolean   <a href="#">Omit&lt;ellipsis, 'expandable'   'rows'   'onExpand'&gt;</a>	false	<a href="#">ellipsis</a>
keyboard	Keyboard style	boolean	false	4.3.0
mark	Marked style	boolean	false	
onClick	Set the handler to handle click event	(event) => void	-	
strong	Bold style	boolean	false	
italic	Italic style	boolean	false	4.16.0
type	Content type	<code>secondary</code>   <code>success</code>   <code>warning</code>   <code>danger</code>	-	success: 4.6.0
underline	Underlined style	boolean	false	

#### Typography.Title

Property	Description	Type	Default	Version
code	Code style	boolean	false	
copyable	Whether to be copyable, customize it via setting an object	boolean   <a href="#">copyable</a>	false	<a href="#">copyable</a>
delete	Deleted line style	boolean	false	
disabled	Disabled content	boolean	false	

editable	If editable. Can control edit state when is object	boolean   <a href="#">editable</a>	false	<a href="#">editable</a>
ellipsis	Display ellipsis when text overflows, can configure rows and expandable by using object	boolean   <a href="#">ellipsis</a>	false	<a href="#">ellipsis</a>
level	Set content importance. Match with <code>h1</code> , <code>h2</code> , <code>h3</code> , <code>h4</code> , <code>h5</code>	number: 1, 2, 3, 4, 5	1	5: 4.6.0
mark	Marked style	boolean	false	
onClick	Set the handler to handle click event	(event) => void	-	
italic	Italic style	boolean	false	4.16.0
type	Content type	<code>secondary</code>   <code>success</code>   <code>warning</code>   <code>danger</code>	-	success: 4.6.0
underline	Underlined style	boolean	false	

## Typography.Paragraph

Property	Description	Type	Default	Version
code	Code style	boolean	false	
copyable	Whether to be copyable, customize it via setting an object	boolean   <a href="#">copyable</a>	false	<a href="#">copyable</a>
delete	Deleted line style	boolean	false	
disabled	Disabled content	boolean	false	
editable	If editable. Can control edit state when is object	boolean   <a href="#">editable</a>	false	<a href="#">editable</a>
ellipsis	Display ellipsis when text overflows, can configure rows and expandable by using object	boolean   <a href="#">ellipsis</a>	false	<a href="#">ellipsis</a>
mark	Marked style	boolean	false	
onClick	Set the handler to handle click event	(event) => void	-	
strong	Bold style	boolean	false	
italic	Italic style	boolean	false	4.16.0
type	Content type	<code>secondary</code>   <code>success</code>   <code>warning</code>   <code>danger</code>	-	success: 4.6.0
underline	Underlined style	boolean	false	

## copyable

```

{
  text: string,
  onCopy: function,
  icon: ReactNode,
  tooltips: false | [ReactNode, ReactNode],
}

```

Property	Description	Type	Default	Version
icon	Custom copy icon: [copyIcon, copiedIcon]	[ReactNode, ReactNode]	-	4.6.0
text	The text to copy	string	-	
tooltips	Custom tooltip text, hide when it is false	[ReactNode, ReactNode]	[Copy, Copied]	4.4.0
onCopy	Called when copied text	function	-	

## editable

```

{
  icon: ReactNode,
  tooltip: boolean | ReactNode,
  editing: boolean,
  maxLength: number,
  autoSize: boolean | { minRows: number, maxRows: number },
  onStart: function,
  onChange: function(string),
  onCancel: function,
  onEnd: function,
  triggerType: ('icon' | 'text')[],
  enterIcon: ReactNode,
}

```

Property	Description	Type	Default	Version
autoSize	<code>autoSize</code> attribute of textarea	boolean   { minRows: number, maxRows: number }	-	4.4.0
editing	Whether to be editable	boolean	false	
icon	Custom editable icon	ReactNode	<EditOutlined />	4.6.0
maxLength	<code>maxLength</code> attribute of textarea	number	-	4.4.0
tooltip	Custom tooltip text, hide when it is false	boolean   ReactNode	Edit	4.6.0
onStart	Called when enter editable state	function	-	

onChange	Called when input at textarea	function(event)	-	
onCancel	Called when type ESC to exit editable state	function	-	
onEnd	Called when type ENTER to exit editable state	function	-	4.14.0
triggerType	Edit mode trigger - icon, text or both (not specifying icon as trigger hides it)	Array<icon text>	[icon]	
enterIcon	Custom "enter" icon in the edit field (passing null removes the icon)	ReactNode	<EnterOutlined />	4.17.0

## ellipsis

```
{
  rows: number,
  expandable: boolean,
  suffix: string,
  symbol: ReactNode,
  tooltip: boolean | ReactNode,
  onExpand: function(event),
  onEllipsis: function(ellipsis),
}
```

Property	Description	Type	Default	Version
expandable	Whether to be expandable	boolean	-	
rows	Max rows of content	number	-	
suffix	Suffix of ellipsis content	string	-	
symbol	Custom description of ellipsis	ReactNode	Expand	
tooltip	Show tooltip when ellipsis	boolean   ReactNode	-	4.11.0
onEllipsis	Called when enter or leave ellipsis state	function(ellipsis)	-	4.2.0
onExpand	Called when expand content	function(event)	-	

## FAQ

### How to use Typography.Link in react-router?

react-router support [customize](#) render component:

```
<Link to="/" component={Typography.Link} />
```

**Note:** This is not equivalent to the execution logic of react-router's Link [reference](#)