

# Linux Secure Attention Key (SAK) handling

**Date:** 18 March 2001  
**Author:** Andrew Morton

An operating system's Secure Attention Key is a security tool which is provided as protection against trojan password capturing programs. It is an undefeatable way of killing all programs which could be masquerading as login applications. Users need to be taught to enter this key sequence before they log in to the system.

From the PC keyboard, Linux has two similar but different ways of providing SAK. One is the ALT-SYSRQ-K sequence. You shouldn't use this sequence. It is only available if the kernel was compiled with sysrq support.

The proper way of generating a SAK is to define the key sequence using `loadkeys`. This will work whether or not sysrq support is compiled into the kernel.

SAK works correctly when the keyboard is in raw mode. This means that once defined, SAK will kill a running X server. If the system is in run level 5, the X server will restart. This is what you want to happen.

What key sequence should you use? Well, CTRL-ALT-DEL is used to reboot the machine. CTRL-ALT-BACKSPACE is magical to the X server. We'll choose CTRL-ALT-PAUSE.

In your `rc.sysinit` (or `rc.local`) file, add the command:

```
echo "control alt keycode 101 = SAK" | /bin/loadkeys
```

And that's it! Only the superuser may reprogram the SAK key.

## Note

1. Linux SAK is said to be not a "true SAK" as is required by systems which implement C2 level security. This author does not know why.
2. On the PC keyboard, SAK kills all applications which have `/dev/console` opened.  
Unfortunately this includes a number of things which you don't actually want killed. This is because these applications are incorrectly holding `/dev/console` open. Be sure to complain to your Linux distributor about this!

You can identify processes which will be killed by SAK with the command:

```
# ls -l /proc/[0-9]*/fd/* | grep console
l-wx----- 1 root    root          64 Mar 18 00:46 /proc/579/fd/0 -> /dev/console
```

Then:

```
# ps aux|grep 579
root      579  0.0  0.1 1088  436 ?        S    00:43   0:00 gpm -t ps/2
```

So `gpm` will be killed by SAK. This is a bug in `gpm`. It should be closing standard input. You can work around this by finding the `init`script which launches `gpm` and changing it thusly:

Old:

```
daemon gpm
```

New:

```
daemon gpm < /dev/null
```

Vixie `cron` also seems to have this problem, and needs the same treatment.

Also, one prominent Linux distribution has the following three lines in its `rc.sysinit` and `rc` scripts:

```
exec 3<&0
exec 4>&1
exec 5>&2
```

These commands cause **all** daemons which are launched by the `init`scripts to have file descriptors 3, 4 and 5 attached to `/dev/console`. So SAK kills them all. A workaround is to simply delete these lines, but this may cause system management applications to malfunction - test everything well.