Calendar

Display date.

Basic

:::demo Set value to specify the currently displayed month. If value is not specified, current month is displayed.

value supports two-way binding.

```
<el-calendar v-model="value">
  </el-calendar>

<script>
    export default {
        data() {
            return {
                value: new Date()
            }
        }
        </script>
```

:::

Custom Content

:::demo Customize what is displayed in the calendar cell by setting scoped-slot named dateCell . In scoped-slot you can get the date (the date of the current cell), data (including the type, isSelected, day attribute). For details, please refer to the API documentation below.

:::

Range

:::demo Set the range attribute to specify the display range of the calendar. Start time must be Monday, end time must be Sunday, and the time span cannot exceed two months.

```
<el-calendar :range="['2019-03-04', '2019-03-24']">
</el-calendar>
```

:::

Attributes

Attribute	Description	Туре	Accepted Values	Default
value / v-model	binding value	Date/string/number	_	_
range	time range, including start time and end time. Start time must be start day of week, end time must be end day of week, the time span cannot exceed two months.	Array	_	_
first-day- of-week	fisrt day of week	Number	1 to 7	1

dateCell Scoped Slot Parameters

Attribute	Description	Туре	Accepted Values	Default
date	date the cell represents	Date	_	_
data	{ type, isSelected, day}. The type property indicates which month the date belongs, optional values are prev-month, current-month, next-month. The isSelected property indicates whether the date is selected. The day property is the formatted date in the format yyyy-MM-dd	Object	_	_