

# Querying Data in Pages with GraphQL

Gatsby's **graphql** tag enables page components to query data via a GraphQL query.

In this guide, you will learn how to use the **graphql** tag in your pages, as well as go a little deeper into how the **graphql** tag works.

If you're curious, you can also read more about why Gatsby uses GraphQL.

## How to use the **graphql** tag in pages

Page components can have their own query. The query can use variables passed in when creating the page to select data for that page.

Let's do a quick tutorial on writing a simple page query.

### Add description to **siteMetadata**

Add a description to your site's metadata.

```
module.exports = {  
  siteMetadata: {  
    title: "My Homepage",  
    description: "This is where I write my thoughts.",  
  },  
}
```

### Make a basic index page

Create an home page (`src/pages/index.js`) like so:

```
import React from "react"  
  
const HomePage = () => {  
  return <div>Hello!</div>  
}  
  
export default HomePage
```

## Add the graphql query

The first thing to do is import `graphql` from Gatsby. At the top of `index.js` add:

```
import * as React from 'react'
+ import { graphql } from 'gatsby'

const HomePage = () => {
  return (
    <div>
      Hello!
    </div>
  )
}
```

Below the `HomePage` component declaration, export a new constant called `query`. The name of the constant isn't important, as Gatsby looks for an exported `graphql` string from the file rather than a specific variable. Note that you can only have one page query per file.

Then, set the `const` variable's value to be a `graphql` tagged template with the query between two backticks:

```
const HomePage = () => {
  return (
    <div>
      Hello!
    </div>
  )
}

+ export const query = graphql`
+   # query will go here
+ `
```

The first part of writing the GraphQL query is including the operation (in this case “`query`”) along with a name.

From exploring in the GraphQL IDE, GraphiQL, you've learned that one of the types that you can query is `site`, which in turn has its own `siteMetadata` field with subfields that correspond to the data provided in `gatsby-config.js`.

Putting this together, the completed query looks like:

```
export const query = graphql`
- # query will go here
+ query HomePageQuery {
+   site {
+     siteMetadata {
```

```
+         description
+       }
+     }
+   }
+ }
+`
```

### Use the query result in the `<HomePage />` component

The `data` prop contains the results of the page GraphQL query, and matches the shape of the query. With this in mind, the updated `HomePage` markup looks like:

```
import * as React from 'react'
import { graphql } from 'gatsby'

- const HomePage = () => {
+ const HomePage = ({data}) => {
  return (
    <div>
-     Hello!
+     {data.site.siteMetadata.description}
    </div>
  )
}

export const query = graphql`
  query HomePageQuery {
    site {
      siteMetadata {
        description
      }
    }
  }
}`
```

```
export default HomePage
```

After restarting `gatsby develop`, your home page will now display “This is where I write my thoughts.” from the description set in `gatsby-config.js`!

### How does the `graphql` tag work?

`graphql` is a tag function. Behind the scenes Gatsby handles these tags in a particular way:

### The short answer

During the Gatsby build process, GraphQL queries are pulled out of the original source for parsing.

### The longer answer

The longer answer is a little more involved: Gatsby borrows a technique from Relay that converts your source code into an abstract syntax tree (AST) during the build step. `file-parser.js` and `query-compiler.js` pick out your `graphql`-tagged templates and effectively remove them from the original source code.

*More information about how queries work is included in the Gatsby Internals section of the docs.*

This means that the `graphql` tag isn't executed the way that JavaScript code is typically handled. For example, you cannot use expression interpolation with Gatsby's `graphql` tag. However, it's possible to pass variables into page queries with the `context` object when creating pages.

### How to add query variables to a page query

Variables can be added to *page queries* (but not static queries) through the `context` object that is an argument of the `createPage` API.

Consider the following query:

```
export const query = graphql`
  query MdxBlogPost {
    mdx(title: { eq: "Using a Theme" }) {
      id
      title
    }
  }
`
```

The `MdxBlogPost` query will return an MDX node in a site where `gatsby-plugin-mdx` is installed and `.mdx` files have been sourced with `gatsby-source-filesystem`, so long as it matches the argument passed in for a `title` equaling (`eq`) the string `"Using a Theme"`.

In addition to hardcoding an argument directly into the page query, you can pass in a variable. The query can be changed to include a variable like this:

```
export const query = graphql`
  query MdxBlogPost($title: String) { // highlight-line
    mdx(title: {eq: $title}) { // highlight-line
      id
      title
    }
  }
`
```

```
  }  
}
```

When a page is created dynamically from this blog post template in `gatsby-node.js`, you can provide an object as part of the page's context. Keys in the context object that match up with arguments in the page query (in this case: `"title"`), will be used as variables. Variables are prefaced with `$`, so passing a `title` property will become `$title` in the query.

```
posts.forEach(({ node }, index) => {  
  createPage({  
    path: node.fields.slug,  
    component: path.resolve(`./src/templates/blog-post.js`),  
    // values in the context object are passed in as variables to page queries  
    context: {  
      title: node.title, // "Using a Theme"  
    },  
  })  
})
```

For more information, check out the docs on creating pages programmatically.