

ioctl VIDIOC_PREPARE_BUF

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]vidioc-prepare-buf.rst, line 2)

Unknown directive type "c.namespace".

```
.. c:namespace:: V4L
```

Name

VIDIOC_PREPARE_BUF - Prepare a buffer for I/O

Synopsis

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]vidioc-prepare-buf.rst, line 18)

Unknown directive type "c.macro".

```
.. c:macro:: VIDIOC_PREPARE_BUF
```

```
int ioctl(int fd, VIDIOC_PREPARE_BUF, struct v4l2_buffer *argp)
```

Arguments

fd

File descriptor returned by `:c:func:`open()``.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]vidioc-prepare-buf.rst, line 26); [backlink](#)

Unknown interpreted text role "c:func".

argp

Pointer to struct `:c:type:`v4l2_buffer``.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]vidioc-prepare-buf.rst, line 29); [backlink](#)

Unknown interpreted text role "c:type".

Description

Applications can optionally call the `:ref:`VIDIOC_PREPARE_BUF`` ioctl to pass ownership of the buffer to the driver before actually enqueueing it, using the `:ref:`VIDIOC_QBUF <VIDIOC_QBUF>` ioctl, and to prepare it for future I/O. Such preparations may include cache invalidation or cleaning. Performing them in advance saves time during the actual I/O.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]vidioc-prepare-buf.rst, line 34); [backlink](#)

Unknown interpreted text role "ref".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]vidioc-prepare-buf.rst, line 34); [backlink](#)

Unknown interpreted text role "ref".

The struct `ctype:v4l2_buffer` structure is specified in `ref:buffer`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\[linux-master] [Documentation] [userspace-api] [media] [v4l]vidioc-prepare-buf.rst, line 40); [backlink](#)

Unknown interpreted text role "ctype".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\[linux-master] [Documentation] [userspace-api] [media] [v4l]vidioc-prepare-buf.rst, line 40); [backlink](#)

Unknown interpreted text role "ref".

Return Value

On success 0 is returned, on error -1 and the `errno` variable is set appropriately. The generic error codes are described at the `ref:Generic Error Codes <gen-errors>` chapter.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\[linux-master] [Documentation] [userspace-api] [media] [v4l]vidioc-prepare-buf.rst, line 46); [backlink](#)

Unknown interpreted text role "ref".

EBUSY

File I/O is in progress.

EINVAL

The `buffer type` is not supported, or the `index` is out of bounds, or no buffers have been allocated yet, or the `userptr` or `length` are invalid.