

- Add JavaScript dependencies installation on bin/setup

Add `yarn install` to bin/setup when using esbuild, webpack, or rollout.

Carlos Ribeiro

- Use `controller_class_path` in `Rails::Generators::NamedBase#route_url`

The `route_url` method now returns the correct path when generating a namespaced controller with a top-level model using `--model-name`.

Previously, when running this command:

```
bin/rails generate scaffold_controller Admin/Post --model-name Post
```

the comments above the controller action would look like:

```
# GET /posts
def index
  @posts = Post.all
end
```

afterwards, they now look like this:

```
# GET /admin/posts
def index
  @posts = Post.all
end
```

Fixes #44662.

Andrew White

- No longer add autoloaded paths to `$LOAD_PATH`.

This means it won't be possible to load them with a manual `require` call, the class or module can be referenced instead.

Reducing the size of `$LOAD_PATH` speed-up `require` calls for apps not using `bootsnap`, and reduce the size of the `bootsnap` cache for the others.

Jean Boussier

- Remove default `X-Download-Options` header

This header is currently only used by Internet Explorer which will be discontinued in 2022 and since Rails 7 does not fully support Internet Explorer this header should not be a default one.

Harun Sabljaković

Please check [7-0-stable](#) for previous changes.