Class: ProxyAgent

Extends: undici.Dispatcher

A Proxy Agent class that implements the Agent API. It allows the connection through proxy in a simple way.

new ProxyAgent([options])

Arguments:

• options ProxyAgentOptions (required) - It extends the Agent options.

Returns: ProxyAgent

Parameter: ProxyAgentOptions

Extends: AgentOptions

• uri string (required) - It can be passed either by a string or a object containing uri as string.

Examples:

```
import { ProxyAgent } from 'undici'

const proxyAgent = new ProxyAgent('my.proxy.server')
// or

const proxyAgent = new ProxyAgent({ uri: 'my.proxy.server' })
```

Example - Basic ProxyAgent instantiation This will instantiate the ProxyAgent. It will not do anything until registered as the agent to use with requests.

```
import { ProxyAgent } from 'undici'
const proxyAgent = new ProxyAgent('my.proxy.server')
```

Example - Basic Proxy Request with global agent dispatcher

```
import { setGlobalDispatcher, request, ProxyAgent } from 'undici'

const proxyAgent = new ProxyAgent('my.proxy.server')
setGlobalDispatcher(proxyAgent)

const { statusCode, body } = await request('http://localhost:3000/foo')
console.log('response received', statusCode) // response received 200

for await (const data of body) {
```

```
console.log('data', data.toString('utf8')) // data foo
Example - Basic Proxy Request with local agent dispatcher
import { ProxyAgent, request } from 'undici'
const proxyAgent = new ProxyAgent('my.proxy.server')
const {
 statusCode,
 body
} = await request('http://localhost:3000/foo', { dispatcher: proxyAgent })
console.log('response received', statusCode) // response received 200
for await (const data of body) {
  console.log('data', data.toString('utf8')) // data foo
ProxyAgent.close()
Closes the proxy agent and waits for registered pools and clients to also close
before resolving.
Returns: Promise<void>
Example - clean up after tests are complete
import { ProxyAgent, setGlobalDispatcher } from 'undici'
const proxyAgent = new ProxyAgent('my.proxy.server')
setGlobalDispatcher(proxyAgent)
await proxyAgent.close()
ProxyAgent.dispatch(options, handlers)
Implements Agent.dispatch(options, handlers).
ProxyAgent.request(options[, callback])
See Dispatcher.request(options [, callback]).
```