

PageEmittedEvents enum

All the events that a page instance may emit.

Signature:

```
export declare const enum PageEmittedEvents
```

Enumeration Members

Member	Value	Description
Close	"close"	Emitted when the page closes.
Console	"console"	Emitted when JavaScript within the page calls one of console API methods, e.g. <code>console.log</code> or <code>console.dir</code> . Also emitted if the page throws an error or a warning.
Dialog	"dialog"	Emitted when a JavaScript dialog appears, such as <code>alert</code> , <code>prompt</code> , <code>confirm</code> or <code>beforeunload</code> . Puppeteer can respond to the dialog via Dialog.accept() or Dialog.dismiss() .
DOMContentLoaded	"domcontentloaded"	Emitted when the JavaScript DOMContentLoaded event is dispatched.
Error	"error"	Emitted when the page crashes. Will contain an <code>Error</code> .
FrameAttached	"frameattached"	Emitted when a frame is attached. Will contain a Frame .
FrameDetached	"framedetached"	Emitted when a frame is detached. Will contain a Frame .
FrameNavigated	"framenavigated"	Emitted when a frame is navigated to a new URL. Will contain a Frame .
Load	"load"	Emitted when the JavaScript load event is dispatched.
Metrics	"metrics"	Emitted when the JavaScript code makes a call to <code>console.timeStamp</code> . For the list of metrics see page.metrics .
PageError	"pageerror"	Emitted when an uncaught exception happens within the page. Contains an <code>Error</code> .
Popup	"popup"	Emitted when the page opens a new tab or window. Contains a Page corresponding to the popup window.

Request	"request"	Emitted when a page issues a request and contains a HTTPRequest .
RequestFailed	"requestfailed"	Emitted when a request fails, for example by timing out. Contains a HTTPRequest .
RequestFinished	"requestfinished"	Emitted when a request finishes successfully. Contains a HTTPRequest .
RequestServedFromCache	"requestervedfromcache"	Emitted when a request ended up loading from cache. Contains a HTTPRequest .
Response	"response"	Emitted when a response is received. Contains a HTTPResponse .
WorkerCreated	"workercreated"	Emitted when a dedicated WebWorker is spawned by the page.
WorkerDestroyed	"workerdestroyed"	Emitted when a dedicated WebWorker is destroyed by the page.