

Home > puppeteer > Page > evaluate

Page.evaluate() method

Signature:

```
evaluate<T extends EvaluateFn>(pageFunction: T, ...args: SerializableOrJSHandle[]): Promise<T>
```

Parameters

Parameter	Type	Description
pageFunction	T	a function that is run within the page
args	SerializableOrJSHandle[]	arguments to be passed to the pageFunction

Returns:

Promise<UnwrapPromiseLike<EvaluateFnReturnType<T>>>

the return value of `pageFunction`.

Remarks

Evaluates a function in the page's context and returns the result.

If the function passed to `page.evaluateHandle` returns a Promise, the function will wait for the promise to resolve and return its value.

Example 1

```
const result = await frame.evaluate(() => {
  return Promise.resolve(8 * 7);
});
console.log(result); // prints "56"
```

You can pass a string instead of a function (although functions are recommended as they are easier to debug and use with TypeScript):

Example 2

```
const aHandle = await page.evaluate('1 + 2');
```

To get the best TypeScript experience, you should pass in as the generic the type of `pageFunction`:

```
const aHandle = await page.evaluate<() => number>(() => 2);
```

Example 3

ElementHandle instances (including JSHandles) can be passed as arguments to the `pageFunction`:

```
const bodyHandle = await page.$('body');
const html = await page.evaluate(body => body.innerHTML, bodyHandle);
await bodyHandle.dispose();
```