

gatsby-telemetry

Check out: gatsby.dev/telemetry

API

captureEvent(type, tags)

Capture an event of type **type** and decorate the generated event with these tags (note: allowed tags are filtered on server side)

trackCli(type, tags)

*This one does the same thing as the **captureEvent** function described above.*

Capture an event of type **type** and decorate the generated event with these tags (note: allowed tags are filtered on server side)

trackError(type, tags)

Capture an error of type **type**. The exception maybe passed in tags and it will be sanitized to anonymize the contents.

trackBuildError(type, tags)

Capture an build error of type **type**. The exception maybe passed in tags and it will be sanitize to anonymize the contents.

setDefaultTags(tags)

Set additional tags to be included in all future events.

decorateEvent(type, tags)

Attach additional tags to the next event generated of type **type**.

setTelemetryEnabled(enabled)

Enable or disable the telemetry collection.

expressMiddleware(type)

Returns a debounced events tracker for collecting general activity information for incoming requests.

ENV Variables

- Set **GATSBY_TELEMETRY_DEBUG** to 1 to print the telemetry data instead of sending it over

- Set `GATSBY_TELEMETRY_DISABLED` to 1 to opt out of all telemetry
- Set `GATSBY_TELEMETRY_VERBOSE` to 1 to log all telemetry