

Display multiple read-only fields in groups.

## When To Use

Commonly displayed on the details page.

## API

### Descriptions

Property	Description	Type	Default	Version
bordered	Whether to display the border	boolean	false	
colon	Change default props <code>colon</code> value of <code>Descriptions.Item</code>	boolean	true	
column	The number of <code>DescriptionItems</code> in a row,could be a number or a object like <code>{ xs: 8, sm: 16, md: 24}</code> , <b>(Only set <code>bordered={true}</code> to take effect)</b>	number	3	
contentStyle	Customize content style	CSSProperties	-	4.10.0
extra	The action area of the description list, placed at the top-right	ReactNode	-	4.5.0
labelStyle	Customize label style	CSSProperties	-	4.10.0
layout	Define description layout	horizontal   vertical	horizontal	
size	Set the size of the list. Can be set to <code>middle,small, or not filled</code>	default   middle   small	-	
title	The title of the description list, placed at the top	ReactNode	-	

### DescriptionItem

Property	Description	Type	Default	Version
contentStyle	Customize content style	CSSProperties	-	4.9.0
label	The description of the content	ReactNode	-	
labelStyle	Customize label style	CSSProperties	-	4.9.0
span	The number of columns included	number	1	

The number of `span` `Description.Item`. `Span={2}` takes up the width of two `DescriptionItems`. When both `style` and `labelStyle` (or `contentStyle`) configured, both of them will work. And next one will overwrite first when conflict.