

CA_SET_DESCR

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\linux-master) (Documentation) (userspace-api) (media) (dvb) ca-set-descr.rst, line 2)

Unknown directive type "c:namespace".

```
.. c:namespace:: DTV.ca
```

Name

CA_SET_DESCR

Synopsis

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\linux-master) (Documentation) (userspace-api) (media) (dvb) ca-set-descr.rst, line 18)

Unknown directive type "c:macro".

```
.. c:macro:: CA_SET_DESCR
```

```
int ioctl(fd, CA_SET_DESCR, struct ca_descr *desc)
```

Arguments

fd

File descriptor returned by a previous call to `c:func:open()`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\linux-master) (Documentation) (userspace-api) (media) (dvb) ca-set-descr.rst, line 26); [backlink](#)

Unknown interpreted text role "c:func".

msg

Pointer to struct `c:type:ca_descr`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\linux-master) (Documentation) (userspace-api) (media) (dvb) ca-set-descr.rst, line 29); [backlink](#)

Unknown interpreted text role "c:type".

Description

CA_SET_DESCR is used for feeding descrambler CA slots with descrambling keys (referred as control words).

Return Value

On success 0 is returned.

On error -1 is returned, and the `errno` variable is set appropriately.

Generic error codes are described at the [ref:Generic Error Codes <gen-errors>](#) chapter.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\dvb\linux-master) (Documentation) (userspace-api) (media) (dvb) ca-set-descr.rst, line 45); [backlink](#)

