

Options

Customize Bootstrap with our built-in custom variables file and easily toggle global CSS preferences with new `$enable-*` Sass variables. Override a variable's value and recompile with `npm run test` as needed.

You can find and customize these variables for key global options in Bootstrap's `scss/_variables.scss` file.

<code>{{< bs-table "table text-start" >}}</code>	Variable	Values	Description
<code> \$spacer</code>	<code>1rem</code> (default), or any value <code>> 0</code>		Specifies the default spacer value to programmatically generate our [spacer utilities]({{< docsref "/utilities/spacing" >}}). <code>\$enable-rounded</code>
<code> \$enable-rounded</code>	<code>true</code> (default) or <code>false</code>		Enables predefined <code>border-radius</code> styles on various components. <code>\$enable-shadows</code>
<code> \$enable-shadows</code>	<code>true</code> or <code>false</code> (default)		Enables predefined decorative <code>box-shadow</code> styles on various components. Does not affect <code>box-shadows</code> used for focus states. <code>\$enable-gradients</code>
<code> \$enable-gradients</code>	<code>true</code> or <code>false</code> (default)		Enables predefined gradients via <code>background-image</code> styles on various components. <code>\$enable-transitions</code>
<code> \$enable-transitions</code>	<code>true</code> (default) or <code>false</code>		Enables predefined <code>transitions</code> on various components. <code>\$enable-reduced-motion</code>
<code> \$enable-reduced-motion</code>	<code>true</code> (default) or <code>false</code>		Enables the [prefers-reduced-motion media query]({{< docsref "/getting-started/accessibility#reduced-motion" >}}), which suppresses certain animations/transitions based on the users' browser/operating system preferences. <code>\$enable-grid-classes</code>
<code> \$enable-grid-classes</code>	<code>true</code> (default) or <code>false</code>		Enables the generation of CSS classes for the grid system (e.g. <code>.row</code> , <code>.col-md-1</code> , etc.). <code>\$enable-caret</code>
<code> \$enable-caret</code>	<code>true</code> (default) or <code>false</code>		Enables pseudo element caret on <code>.dropdown-toggle</code> . <code>\$enable-button-pointers</code>
<code> \$enable-button-pointers</code>	<code>true</code> (default) or <code>false</code>		Add "hand" cursor to non-disabled button elements. <code>\$enable-rfs</code>
<code> \$enable-rfs</code>	<code>true</code> (default) or <code>false</code>		Globally enables [RFS]({{< docsref "/getting-started/rfs" >}}). <code>\$enable-validation-icons</code>
<code> \$enable-validation-icons</code>	<code>true</code> (default) or <code>false</code>		Enables <code>background-image</code> icons within textual inputs and some custom forms for validation states. <code>\$enable-negative-margins</code>
<code> \$enable-negative-margins</code>	<code>true</code> or <code>false</code> (default)		Enables the generation of [negative margin utilities]({{< docsref "/utilities/spacing#negative-margin" >}}). <code>\$enable-deprecation-messages</code>
<code> \$enable-deprecation-messages</code>	<code>true</code> (default) or <code>false</code>		Set to <code>false</code> to hide warnings when using any of the deprecated mixins and functions that are planned to be removed in v6. <code>\$enable-important-utilities</code>
<code> \$enable-important-utilities</code>	<code>true</code> (default) or <code>false</code>		Enables the <code>!important</code> suffix in utility

classes. | | `$enable-smooth-scroll` | `true` (default) or `false` | Applies
`scroll-behavior: smooth` globally, except for users asking for reduced
motion through `[prefers-reduced-motion media query]`(`{{< docsref "/getting-
started/accessibility#reduced-motion" >}}`) | `{{< /bs-table >}}`