

Brief Tour of the Standard Library --- Part II

This second tour covers more advanced modules that support professional programming needs. These modules rarely occur in small scripts.

Output Formatting

The `mod:reprlib` module provides a version of `func:repr` customized for abbreviated displays of large or deeply nested containers:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 16); [backlink](#)

Unknown interpreted text role "mod".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 16); [backlink](#)

Unknown interpreted text role "func".

```
>>> import reprlib
>>> reprlib.repr(set('supercalifragilisticexpialidocious'))
{'a', 'c', 'd', 'e', 'f', 'g', ...}"
```

The `mod:pprint` module offers more sophisticated control over printing both built-in and user defined objects in a way that is readable by the interpreter. When the result is longer than one line, the "pretty printer" adds line breaks and indentation to more clearly reveal data structure:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 23); [backlink](#)

Unknown interpreted text role "mod".

```
>>> import pprint
>>> t = [[['black', 'cyan'], 'white', ['green', 'red']], [['magenta',
...     'yellow'], 'blue']]
...
>>> pprint.pprint(t, width=30)
[[['black', 'cyan'],
  'white',
  ['green', 'red']],
 [['magenta', 'yellow'],
  'blue']]
```

The `mod:textwrap` module formats paragraphs of text to fit a given screen width:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 39); [backlink](#)

Unknown interpreted text role "mod".

```
>>> import textwrap
>>> doc = """The wrap() method is just like fill() except that it returns
... a list of strings instead of one big string with newlines to separate
... the wrapped lines."""
...
>>> print(textwrap.fill(doc, width=40))
The wrap() method is just like fill()
except that it returns a list of strings
instead of one big string with newlines
to separate the wrapped lines.
```

The `mod:locale` module accesses a database of culture specific data formats. The grouping attribute of locale's format function provides a direct way of formatting numbers with group separators:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 53); [backlink](#)

Unknown interpreted text role "mod".

```
>>> import locale
>>> locale.setlocale(locale.LC_ALL, 'English_United States.1252')
'English_United States.1252'
>>> conv = locale.localeconv()          # get a mapping of conventions
>>> x = 1234567.8
>>> locale.format("%d", x, grouping=True)
'1,234,567'
>>> locale.format_string("%s%.*f", (conv['currency_symbol'],
...                               conv['frac_digits'], x), grouping=True)
'$1,234,567.80'
```

Templating

The `mod: string` module includes a versatile `class: ~string.Template` class with a simplified syntax suitable for editing by end-users. This allows users to customize their applications without having to alter the application.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 74); [backlink](#)

Unknown interpreted text role "mod".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 74); [backlink](#)

Unknown interpreted text role "class".

The format uses placeholder names formed by `$` with valid Python identifiers (alphanumeric characters and underscores). Surrounding the placeholder with braces allows it to be followed by more alphanumeric letters with no intervening spaces. Writing `$$` creates a single escaped `$`:

```
>>> from string import Template
>>> t = Template('${village}folk send $$10 to $cause.')
>>> t.substitute(village='Nottingham', cause='the ditch fund')
'Nottinghamfolk send $10 to the ditch fund.'
```

The `meth: ~string.Template.substitute` method raises a `exc: KeyError` when a placeholder is not supplied in a dictionary or a keyword argument. For mail-merge style applications, user supplied data may be incomplete and the `meth: ~string.Template.safe_substitute` method may be more appropriate --- it will leave placeholders unchanged if data is missing:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 88); [backlink](#)

Unknown interpreted text role "meth".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 88); [backlink](#)

Unknown interpreted text role "exc".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 88); [backlink](#)

Unknown interpreted text role "meth".

```
>>> t = Template('Return the $item to $owner.')
>>> d = dict(item='unladen swallow')
>>> t.substitute(d)
Traceback (most recent call last):
...
KeyError: 'owner'
>>> t.safe_substitute(d)
'Return the unladen swallow to $owner.'
```

Template subclasses can specify a custom delimiter. For example, a batch renaming utility for a photo browser may elect to use percent signs for placeholders such as the current date, image sequence number, or file format:

```
>>> import time, os.path
>>> photofiles = ['img_1074.jpg', 'img_1076.jpg', 'img_1077.jpg']
>>> class BatchRename(Template):
...     delimiter = '%'
>>> fmt = input('Enter rename style (%d-date %n-seqnum %f-format): ')
Enter rename style (%d-date %n-seqnum %f-format): Ashley_%n%f
```

```
>>> t = BatchRename(fmt)
>>> date = time.strftime('%d%b%y')
>>> for i, filename in enumerate(photofiles):
...     base, ext = os.path.splitext(filename)
...     newname = t.substitute(d=date, n=i, f=ext)
...     print('{0} --> {1}'.format(filename, newname))

img_1074.jpg --> Ashley_0.jpg
img_1076.jpg --> Ashley_1.jpg
img_1077.jpg --> Ashley_2.jpg
```

Another application for templating is separating program logic from the details of multiple output formats. This makes it possible to substitute custom templates for XML files, plain text reports, and HTML web reports.

Working with Binary Data Record Layouts

The `mod:'struct'` module provides `func:'~struct.pack'` and `func:'~struct.unpack'` functions for working with variable length binary record formats. The following example shows how to loop through header information in a ZIP file without using the `mod:'zipfile'` module. Pack codes "H" and "I" represent two and four byte unsigned numbers respectively. The "<" indicates that they are standard size and in little-endian byte order:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 135); [backlink](#)

Unknown interpreted text role "mod".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 135); [backlink](#)

Unknown interpreted text role "func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 135); [backlink](#)

Unknown interpreted text role "func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 135); [backlink](#)

Unknown interpreted text role "mod".

```
import struct

with open('myfile.zip', 'rb') as f:
    data = f.read()

start = 0
for i in range(3):
    # show the first 3 file headers
    start += 14
    fields = struct.unpack('<IIIHH', data[start:start+16])
    crc32, comp_size, uncomp_size, filenamesize, extra_size = fields

    start += 16
    filename = data[start:start+filenamesize]
    start += filenamesize
    extra = data[start:start+extra_size]
    print(filename, hex(crc32), comp_size, uncomp_size)

    start += extra_size + comp_size    # skip to the next header
```

Multi-threading

Threading is a technique for decoupling tasks which are not sequentially dependent. Threads can be used to improve the responsiveness of applications that accept user input while other tasks run in the background. A related use case is running I/O in parallel with computations in another thread.

The following code shows how the high level `mod:'threading'` module can run tasks in background while the main program continues to run:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-

main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 173); [backlink](#)

Unknown interpreted text role "mod".

```
import threading, zipfile

class AsyncZip(threading.Thread):
    def __init__(self, infile, outfile):
        threading.Thread.__init__(self)
        self.infile = infile
        self.outfile = outfile

    def run(self):
        f = zipfile.ZipFile(self.outfile, 'w', zipfile.ZIP_DEFLATED)
        f.write(self.infile)
        f.close()
        print('Finished background zip of:', self.infile)

background = AsyncZip('mydata.txt', 'myarchive.zip')
background.start()
print('The main program continues to run in foreground.')

background.join()    # Wait for the background task to finish
print('Main program waited until background was done.')
```

The principal challenge of multi-threaded applications is coordinating threads that share data or other resources. To that end, the threading module provides a number of synchronization primitives including locks, events, condition variables, and semaphores.

While those tools are powerful, minor design errors can result in problems that are difficult to reproduce. So, the preferred approach to task coordination is to concentrate all access to a resource in a single thread and then use the `mod:'queue'` module to feed that thread with requests from other threads. Applications using `class:'~queue.Queue'` objects for inter-thread communication and coordination are easier to design, more readable, and more reliable.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 202); [backlink](#)

Unknown interpreted text role "mod".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 202); [backlink](#)

Unknown interpreted text role "class".

Logging

The `mod:'logging'` module offers a full featured and flexible logging system. At its simplest, log messages are sent to a file or to `sys.stderr`:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 215); [backlink](#)

Unknown interpreted text role "mod".

```
import logging
logging.debug('Debugging information')
logging.info('Informational message')
logging.warning('Warning:config file %s not found', 'server.conf')
logging.error('Error occurred')
logging.critical('Critical error -- shutting down')
```

This produces the following output:

System Message: WARNING/2 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 227)

Cannot analyze code. No Pygments lexer found for "none".

.. code-block:: none

```
WARNING:root:Warning:config file server.conf not found
ERROR:root:Error occurred
CRITICAL:root:Critical error -- shutting down
```

By default, informational and debugging messages are suppressed and the output is sent to standard error. Other output options include routing messages through email, datagrams, sockets, or to an HTTP Server. New filters can select different routing based on message priority: `:const:~logging.DEBUG`, `:const:~logging.INFO`, `:const:~logging.WARNING`, `:const:~logging.ERROR`, and `:const:~logging.CRITICAL`.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\cpython-main) (Doc) (tutorial)stdlib2.rst, line 233); [backlink](#)

Unknown interpreted text role "const".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\cpython-main) (Doc) (tutorial)stdlib2.rst, line 233); [backlink](#)

Unknown interpreted text role "const".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\cpython-main) (Doc) (tutorial)stdlib2.rst, line 233); [backlink](#)

Unknown interpreted text role "const".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\cpython-main) (Doc) (tutorial)stdlib2.rst, line 233); [backlink](#)

Unknown interpreted text role "const".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\cpython-main) (Doc) (tutorial)stdlib2.rst, line 233); [backlink](#)

Unknown interpreted text role "const".

The logging system can be configured directly from Python or can be loaded from a user editable configuration file for customized logging without altering the application.

Weak References

Python does automatic memory management (reference counting for most objects and `term`garbage collection`` to eliminate cycles). The memory is freed shortly after the last reference to it has been eliminated.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\cpython-main) (Doc) (tutorial)stdlib2.rst, line 250): *backlink*

Unknown interpreted text role "term".

This approach works fine for most applications but occasionally there is a need to track objects only as long as they are being used by something else. Unfortunately, just tracking them creates a reference that makes them permanent. The `mod:weakref` module provides tools for tracking objects without creating a reference. When the object is no longer needed, it is automatically removed from a weakref table and a callback is triggered for weakref objects. Typical applications include caching objects that are expensive to create:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\cpython-main) (Doc) (tutorial)stdlib2.rst, line 254; [backlink](#)

Unknown interpreted text role "mod".

[illegible]

```

0
>>> d['primary']          # entry was automatically removed
Traceback (most recent call last):
  File "<stdin>", line 1, in <module>
    d['primary']          # entry was automatically removed
  File "C:/python311/lib/weakref.py", line 46, in __getitem__
    o = self.data[key]()
KeyError: 'primary'

```

Tools for Working with Lists

Many data structure needs can be met with the built-in list type. However, sometimes there is a need for alternative implementations with different performance trade-offs.

The `mod:'array'` module provides an `class:'~array.array()'` object that is like a list that stores only homogeneous data and stores it more compactly. The following example shows an array of numbers stored as two byte unsigned binary numbers (typecode "H") rather than the usual 16 bytes per entry for regular lists of Python int objects:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 295); [backlink](#)

Unknown interpreted text role "mod".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 295); [backlink](#)

Unknown interpreted text role "class".

```

>>> from array import array
>>> a = array('H', [4000, 10, 700, 22222])
>>> sum(a)
26932
>>> a[1:3]
array('H', [10, 700])

```

The `mod:'collections'` module provides a `class:'~collections.deque()'` object that is like a list with faster appends and pops from the left side but slower lookups in the middle. These objects are well suited for implementing queues and breadth first tree searches:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 308); [backlink](#)

Unknown interpreted text role "mod".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 308); [backlink](#)

Unknown interpreted text role "class".

```

>>> from collections import deque
>>> d = deque(["task1", "task2", "task3"])
>>> d.append("task4")
>>> print("Handling", d.popleft())
Handling task1

unsearched = deque([starting_node])
def breadth_first_search(unsearched):
    node = unsearched.popleft()
    for m in gen_moves(node):
        if is_goal(m):
            return m
    unsearched.append(m)

```

In addition to alternative list implementations, the library also offers other tools such as the `mod:'bisect'` module with functions for manipulating sorted lists:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 329); [backlink](#)

Unknown interpreted text role "mod".

```

>>> import bisect
>>> scores = [(100, 'perl'), (200, 'tcl'), (400, 'lua'), (500, 'python')]

```

```
>>> bisect.insort(scores, (300, 'ruby'))
>>> scores
[(100, 'perl'), (200, 'tcl'), (300, 'ruby'), (400, 'lua'), (500, 'python')]
```

The `mod:heapq` module provides functions for implementing heaps based on regular lists. The lowest valued entry is always kept at position zero. This is useful for applications which repeatedly access the smallest element but do not want to run a full list sort:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 339); [backlink](#)

Unknown interpreted text role "mod".

```
>>> from heapq import heapify, heappop, heappush
>>> data = [1, 3, 5, 7, 9, 2, 4, 6, 8, 0]
>>> heapify(data) # rearrange the list into heap order
>>> heappush(data, -5) # add a new entry
>>> [heappop(data) for i in range(3)] # fetch the three smallest entries
[-5, 0, 1]
```

Decimal Floating Point Arithmetic

The `mod:decimal` module offers a `class:~decimal.Decimal` datatype for decimal floating point arithmetic. Compared to the built-in `class:float` implementation of binary floating point, the class is especially helpful for

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 357); [backlink](#)

Unknown interpreted text role "mod".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 357); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 357); [backlink](#)

Unknown interpreted text role "class".

- financial applications and other uses which require exact decimal representation,
- control over precision,
- control over rounding to meet legal or regulatory requirements,
- tracking of significant decimal places, or
- applications where the user expects the results to match calculations done by hand.

For example, calculating a 5% tax on a 70 cent phone charge gives different results in decimal floating point and binary floating point. The difference becomes significant if the results are rounded to the nearest cent:

```
>>> from decimal import *
>>> round(Decimal('0.70') * Decimal('1.05'), 2)
Decimal('0.74')
>>> round(.70 * 1.05, 2)
0.73
```

The `class:~decimal.Decimal` result keeps a trailing zero, automatically inferring four place significance from multiplicands with two place significance. Decimal reproduces mathematics as done by hand and avoids issues that can arise when binary floating point cannot exactly represent decimal quantities.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 379); [backlink](#)

Unknown interpreted text role "class".

Exact representation enables the `class:~decimal.Decimal` class to perform modulo calculations and equality tests that are unsuitable for binary floating point:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\ (cpython-main) (Doc) (tutorial) stdlib2.rst, line 385); [backlink](#)

Unknown interpreted text role "class".

```
>>> Decimal('1.00') % Decimal('.10')
Decimal('0.00')
>>> 1.00 % 0.10
0.09999999999999995

>>> sum([Decimal('0.1')]*10) == Decimal('1.0')
True
>>> sum([0.1]*10) == 1.0
False
```

The `mod:decimal` module provides arithmetic with as much precision as needed:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\cpython-main\Doc\tutorial\cpython-main) (Doc) (tutorial) stdlib2.rst, line 399); [backlink](#)

Unknown interpreted text role "mod".

```
>>> getcontext().prec = 36
>>> Decimal(1) / Decimal(7)
Decimal('0.142857142857142857142857142857')
```