

## Precompiled Bootstrap

Once downloaded, unzip the compressed folder and you'll see something like this:

```
bootstrap/
├── css/
│   ├── bootstrap-grid.css
│   ├── bootstrap-grid.css.map
│   ├── bootstrap-grid.min.css
│   ├── bootstrap-grid.min.css.map
│   ├── bootstrap-grid.rtl.css
│   ├── bootstrap-grid.rtl.css.map
│   ├── bootstrap-grid.rtl.min.css
│   ├── bootstrap-grid.rtl.min.css.map
│   ├── bootstrap-reboot.css
│   ├── bootstrap-reboot.css.map
│   ├── bootstrap-reboot.min.css
│   ├── bootstrap-reboot.min.css.map
│   ├── bootstrap-reboot.rtl.css
│   ├── bootstrap-reboot.rtl.css.map
│   ├── bootstrap-reboot.rtl.min.css
│   ├── bootstrap-reboot.rtl.min.css.map
│   ├── bootstrap-utilities.css
│   ├── bootstrap-utilities.css.map
│   ├── bootstrap-utilities.min.css
│   ├── bootstrap-utilities.min.css.map
│   ├── bootstrap-utilities.rtl.css
│   ├── bootstrap-utilities.rtl.css.map
│   ├── bootstrap-utilities.rtl.min.css
│   ├── bootstrap-utilities.rtl.min.css.map
│   ├── bootstrap.css
│   ├── bootstrap.css.map
│   ├── bootstrap.min.css
│   ├── bootstrap.min.css.map
│   ├── bootstrap.rtl.css
│   ├── bootstrap.rtl.css.map
│   ├── bootstrap.rtl.min.css
│   └── bootstrap.rtl.min.css.map
└── js/
    ├── bootstrap.bundle.js
    ├── bootstrap.bundle.js.map
    ├── bootstrap.bundle.min.js
    ├── bootstrap.bundle.min.js.map
    ├── bootstrap.esm.js
    ├── bootstrap.esm.js.map
    ├── bootstrap.esm.min.js
    ├── bootstrap.esm.min.js.map
    ├── bootstrap.js
    ├── bootstrap.js.map
    ├── bootstrap.min.js
    └── bootstrap.min.js.map
```

This is the most basic form of Bootstrap: precompiled files for quick drop-in usage in nearly any web project. We provide compiled CSS and JS ( `bootstrap.*` ), as well as compiled and minified CSS and JS ( `bootstrap.min.*` ). [Source maps](#) ( `bootstrap.*.map` ) are available for use with certain browsers' developer tools. Bundled JS files ( `bootstrap.bundle.js` and minified `bootstrap.bundle.min.js` ) include [Popper](#).

### CSS files

Bootstrap includes a handful of options for including some or all of our compiled CSS.

CSS files	Layout	Content	Components	Utilities
<code>bootstrap.css</code> <code>bootstrap.rtl.css</code> <code>bootstrap.min.css</code> <code>bootstrap.rtl.min.css</code>	Included	Included	Included	Included
<code>bootstrap-grid.css</code> <code>bootstrap-grid.rtl.css</code> <code>bootstrap-grid.min.css</code> <code>bootstrap-grid.rtl.min.css</code>	<a href="#">}}"&gt;Only grid system</a>	—	—	<a href="#">}}"&gt;Only flex utilities</a>
<code>bootstrap-utilities.css</code> <code>bootstrap-utilities.rtl.css</code> <code>bootstrap-utilities.min.css</code> <code>bootstrap-utilities.rtl.min.css</code>	—	—	—	Included
<code>bootstrap-reboot.css</code> <code>bootstrap-reboot.rtl.css</code> <code>bootstrap-reboot.min.css</code> <code>bootstrap-reboot.rtl.min.css</code>	—	<a href="#">}}"&gt;Only Reboot</a>	—	—

### JS files

Similarly, we have options for including some or all of our compiled JavaScript.

JS files	Popper
<code>bootstrap.bundle.js</code> <code>bootstrap.bundle.min.js</code>	Included
<code>bootstrap.js</code> <code>bootstrap.min.js</code>	—

### Bootstrap source code

The Bootstrap source code download includes the precompiled CSS and JavaScript assets, along with source Sass, JavaScript, and documentation. More specifically, it includes the following and more:

```
bootstrap/  
├─ dist/  
│   ├─ css/  
│   └─ js/  
├─ site/  
│   └─ content/  
│       └─ docs/  
│           └─ 5.1/  
│               └─ examples/  
├─ js/  
└─ scss/
```

The `scss/` and `js/` are the source code for our CSS and JavaScript. The `dist/` folder includes everything listed in the precompiled download section above. The `site/docs/` folder includes the source code for our documentation, and `examples/` of Bootstrap usage. Beyond that, any other included file provides support for packages, license information, and development.