This wiki is automatically published from ohmyzsh/wiki. To edit this page, go to ohmyzsh/wiki, make your changes and submit a Pull Request.

If you're coming from the Internet, this section has been edited to only show main Oh My Zsh tricks. Documentation for each plugin can be found in each [[Plugins]] README.

Quick reference:

- Oh My Zsh's Command-Line Interface (CLI): `omz`. Run `omz --help` for available commands.
- To **update** Oh My Zsh: `omz update`.
- To **uninstall** it: `uninstall_oh_my_zsh`.
- To apply changes made to `.zshrc`: `omz reload` (this just runs `exec zsh`). **Do NOT run `source ~/.zshrc`**.

Commands

Command	Description
`alias`	List all aliases
`take` / `mkcd`	Create a new directory and change to it, will create intermediate directories as required.
`zsh_stats`	Get a list of the top 20 commands and how many times they have been run.

Directory

Alias	Command
`md`	`mkdir -p`
`rd`	`rmdir`
`cd` / `~`	`cd` to your home directory
`..`	`cd ..`
`...`	`cd ../..`
`....`	`cd ../../..`
`.....`	`cd ../../../..`
`/`	`cd /`
`d`	`dirs -v` (lists last visited directories)
`cd +n`	Switch to directory number `n`
`-`	`cd` to last visited directory
`1`	`cd -1`
`2`	`cd -2`
`3`	`cd -3`
`4`	`cd -4`

1

Alias	Command
5	`cd -5`
6	`cd -6`
7	`cd -7`
8	`cd -8`
9	`cd -9`