

Transforming the prediction target (y)

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main (doc) (modules)preprocessing_targets.rst, line 1)

Unknown directive type "currentmodule".

```
.. currentmodule:: sklearn.preprocessing
```

These are transformers that are not intended to be used on features, only on supervised learning targets. See also `ref:transformed_target_regressor`` if you want to transform the prediction target for learning, but evaluate the model in the original (untransformed) space.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main (doc) (modules)preprocessing_targets.rst, line 9); [backlink](#)

Unknown interpreted text role "ref".

Label binarization

LabelBinarizer

`class:`LabelBinarizer`` is a utility class to help create a `term:`label indicator matrix`` from a list of `term:`multiclass`` labels:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main (doc) (modules)preprocessing_targets.rst, line 20); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main (doc) (modules)preprocessing_targets.rst, line 20); [backlink](#)

Unknown interpreted text role "term".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main (doc) (modules)preprocessing_targets.rst, line 20); [backlink](#)

Unknown interpreted text role "term".

```
>>> from sklearn import preprocessing
>>> lb = preprocessing.LabelBinarizer()
>>> lb.fit([1, 2, 6, 4, 2])
LabelBinarizer()
>>> lb.classes_
array([1, 2, 4, 6])
>>> lb.transform([1, 6])
array([[1, 0, 0, 0],
       [0, 0, 0, 1]])
```

Using this format can enable multiclass classification in estimators that support the label indicator matrix format.

Warning

LabelBinarizer is not needed if you are using an estimator that already supports `term:`multiclass`` data.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main (doc) (modules)preprocessing_targets.rst, line 38); [backlink](#)

Unknown interpreted text role "term".

For more information about multiclass classification, refer to [:ref: multiclass_classification`](#).

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main) (doc) (modules)preprocessing_targets.rst, line 41); [backlink](#)

Unknown interpreted text role "ref".

MultiLabelBinarizer

In [:term: multilabel`](#) learning, the joint set of binary classification tasks is expressed with a label binary indicator array: each sample is one row of a 2d array of shape (n_samples, n_classes) with binary values where the one, i.e. the non zero elements, corresponds to the subset of labels for that sample. An array such as `np.array([[1, 0, 0], [0, 1, 1], [0, 0, 0]])` represents label 0 in the first sample, labels 1 and 2 in the second sample, and no labels in the third sample.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main) (doc) (modules)preprocessing_targets.rst, line 47); [backlink](#)

Unknown interpreted text role "term".

Producing multilabel data as a list of sets of labels may be more intuitive. The [:class: MultiLabelBinarizer`](#) `<sklearn.preprocessing.MultiLabelBinarizer>` transformer can be used to convert between a collection of collections of labels and the indicator format:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main) (doc) (modules)preprocessing_targets.rst, line 55); [backlink](#)

Unknown interpreted text role "class".

```
>>> from sklearn.preprocessing import MultiLabelBinarizer
>>> y = [[2, 3, 4], [2], [0, 1, 3], [0, 1, 2, 3, 4], [0, 1, 2]]
>>> MultiLabelBinarizer().fit_transform(y)
array([[0, 0, 1, 1, 1],
       [0, 0, 1, 0, 0],
       [1, 1, 0, 1, 0],
       [1, 1, 1, 1, 1],
       [1, 1, 1, 0, 0]])
```

For more information about multilabel classification, refer to [:ref: multilabel_classification`](#).

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main) (doc) (modules)preprocessing_targets.rst, line 69); [backlink](#)

Unknown interpreted text role "ref".

Label encoding

[:class: LabelEncoder`](#) is a utility class to help normalize labels such that they contain only values between 0 and n_classes-1. This is sometimes useful for writing efficient Cython routines. [:class: LabelEncoder`](#) can be used as follows:

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main) (doc) (modules)preprocessing_targets.rst, line 75); [backlink](#)

Unknown interpreted text role "class".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\scikit-learn-main\doc\modules\scikit-learn-main) (doc) (modules)preprocessing_targets.rst, line 75); [backlink](#)

Unknown interpreted text role "class".

```
>>> from sklearn import preprocessing
>>> le = preprocessing.LabelEncoder()
>>> le.fit([1, 2, 2, 6])
```

```
LabelEncoder()
>>> le.classes_
array([1, 2, 6])
>>> le.transform([1, 1, 2, 6])
array([0, 0, 1, 2])
>>> le.inverse_transform([0, 0, 1, 2])
array([1, 1, 2, 6])
```

It can also be used to transform non-numerical labels (as long as they are hashable and comparable) to numerical labels:

```
>>> le = preprocessing.LabelEncoder()
>>> le.fit(["paris", "paris", "tokyo", "amsterdam"])
LabelEncoder()
>>> list(le.classes_)
['amsterdam', 'paris', 'tokyo']
>>> le.transform(["tokyo", "tokyo", "paris"])
array([2, 2, 1])
>>> list(le.inverse_transform([2, 2, 1]))
['tokyo', 'tokyo', 'paris']
```