

Read/Write

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]rw.rst, line 2)

Unknown directive type "c.namespace".

```
.. c:namespace:: V4L
```

Input and output devices support the `:c:func:`read()`` and `:c:func:`write()`` function, respectively, when the `V4L2_CAP_READWRITE` flag in the `capabilities` field of struct `:c:type:`v4l2_capability`` returned by the `:ref:`VIDIOC_QUERYCAP`` ioctl is set.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]rw.rst, line 10); [backlink](#)

Unknown interpreted text role "c:func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]rw.rst, line 10); [backlink](#)

Unknown interpreted text role "c:func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]rw.rst, line 10); [backlink](#)

Unknown interpreted text role "c:type".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]rw.rst, line 10); [backlink](#)

Unknown interpreted text role "ref".

Drivers may need the CPU to copy the data, but they may also support DMA to or from user memory, so this I/O method is not necessarily less efficient than other methods merely exchanging buffer pointers. It is considered inferior though because no meta-information like frame counters or timestamps are passed. This information is necessary to recognize frame dropping and to synchronize with other data streams. However this is also the simplest I/O method, requiring little or no setup to exchange data. It permits command line stunts like this (the `vidctrl` tool is fictitious):

System Message: WARNING/2 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]rw.rst, line 26)

Cannot analyze code. No Pygments lexer found for "none".

```
.. code-block:: none
```

```
$ vidctrl /dev/video --input=0 --format=YUYV --size=352x288
$ dd if=/dev/video of=myimage.422 bs=202752 count=1
```

To read from the device applications use the `:c:func:`read()`` function, to write the `:c:func:`write()`` function. Drivers must implement one I/O method if they exchange data with applications, but it need not be this. [1] When reading or writing is supported, the driver must also support the `:c:func:`select()`` and `:c:func:`poll()`` function. [2]

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v4l\linux-master [Documentation] [userspace-api] [media] [v4l]rw.rst, line 31); [backlink](#)

Unknown interpreted text role "c:func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\[linux-master] [Documentation] [userspace-api] [media] [v41]rw.rst, line 31); [backlink](#)

Unknown interpreted text role "c:func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\[linux-master] [Documentation] [userspace-api] [media] [v41]rw.rst, line 31); [backlink](#)

Unknown interpreted text role "c:func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\[linux-master] [Documentation] [userspace-api] [media] [v41]rw.rst, line 31); [backlink](#)

Unknown interpreted text role "c:func".

[1] It would be desirable if applications could depend on drivers supporting all I/O interfaces, but as much as the complex memory mapping I/O can be inadequate for some devices we have no reason to require this interface, which is most useful for simple applications capturing still images.

[2] At the driver level `c:func:select()` and `c:func:poll()` are the same, and `c:func:select()` is too important to be optional.

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\[linux-master] [Documentation] [userspace-api] [media] [v41]rw.rst, line 46); [backlink](#)

Unknown interpreted text role "c:func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\[linux-master] [Documentation] [userspace-api] [media] [v41]rw.rst, line 46); [backlink](#)

Unknown interpreted text role "c:func".

System Message: ERROR/3 (D:\onboarding-resources\sample-onboarding-resources\linux-master\Documentation\userspace-api\media\v41\[linux-master] [Documentation] [userspace-api] [media] [v41]rw.rst, line 46); [backlink](#)

Unknown interpreted text role "c:func".