React Native plugin

This plugin adds completion for `react-native`. It also defines a few [aliases](#) for the commands more frequently used.

To enable, add `react-native` to your `plugins` array in your zshrc file:

```
plugins=(... react-native)
```

Aliases

Alias	React Native command
rn	`react-native`
rns	`react-native start`
rnlink	`react-native link`
Logging	
rnland	`react-native log-android`
rnlios	`react-native log-ios`
App Testing	
rnand	`react-native run-android`
rnios	`react-native run-ios`
iPhone	
rnios4s	`react-native run-ios --simulator "iPhone 4s"`
rnios5	`react-native run-ios --simulator "iPhone 5"`
rnios5s	`react-native run-ios --simulator "iPhone 5s"`
rnios6	`react-native run-ios --simulator "iPhone 6"`
rnios6s	`react-native run-ios --simulator "iPhone 6s"`
rnios6p	`react-native run-ios --simulator "iPhone 6 Plus"`
rnios6sp	`react-native run-ios --simulator "iPhone 6s Plus"`
rnios7	`react-native run-ios --simulator "iPhone 7"`
rnios7p	`react-native run-ios --simulator "iPhone 7 Plus"`
rnios8	`react-native run-ios --simulator "iPhone 8"`
rnios8p	`react-native run-ios --simulator "iPhone 8 Plus"`
rniosse	`react-native run-ios --simulator "iPhone SE"`

rniosx	`react-native run-ios --simulator "iPhone X"`
rniosxs	`react-native run-ios --simulator "iPhone Xs"`
rniosxsm	`react-native run-ios --simulator "iPhone Xs Max"`
rniosxr	`react-native run-ios --simulator "iPhone XʀR"`
rnios11	`react-native run-ios --simulator "iPhone 11"`
rnios11p	`react-native run-ios --simulator "iPhone 11 Pro"`
rnios11pm	`react-native run-ios --simulator "iPhone 11 Pro Max"`
iPad	
rnipad2	`react-native run-ios --simulator "iPad 2"`
rnipad5	`react-native run-ios --simulator "iPad (5th generation)"`
rnipad6	`react-native run-ios --simulator "iPad (6th generation)"`
rnipadr	`react-native run-ios --simulator "iPad Retina"`
rnipada	`react-native run-ios --simulator "iPad Air"`
rnipada2	`react-native run-ios --simulator "iPad Air 2"`
rnipada3	`react-native run-ios --simulator "iPad Air (3rd generation)"`
rnipadm2	`react-native run-ios --simulator "iPad mini 2"`
rnipadm3	`react-native run-ios --simulator "iPad mini 3"`
rnipadm4	`react-native run-ios --simulator "iPad mini 4"`
rnipadm5	`react-native run-ios --simulator "iPad mini (5th generation)"`
rnipadp9	`react-native run-ios --simulator "iPad Pro (9.7-inch)"`
rnipadp12	`react-native run-ios --simulator "iPad Pro (12.9-inch)"`
rnipadp122	`react-native run-ios --simulator "iPad Pro (12.9-inch) (2nd generation)"`
rnipadp10	`react-native run-ios --simulator "iPad Pro (10.5-inch)"`
rnipad11	`react-native run-ios --simulator "iPad Pro (11-inch)"`
rnipad123	`react-native run-ios --simulator "iPad Pro (12.9-inch) (3rd generation)"`
Apple TV	
rnatv	`react-native run-ios --simulator "Apple TV"`
rnatv4k	`react-native run-ios --simulator "Apple TV 4K"`
rnatv4k1080	`react-native run-ios --simulator "Apple TV 4K (at 1080p)"`
rnipad123	`react-native run-ios --simulator "iPad Pro (12.9-inch) (3rd generation)"`
Apple Watch	

rnaw38	`react-native run-ios --simulator "Apple Watch - 38mm"`
rnaw42	`react-native run-ios --simulator "Apple Watch - 42mm"`
rnaws238	`react-native run-ios --simulator "Apple Watch Series 2 - 38mm"`
rnaws242	`react-native run-ios --simulator "Apple Watch Series 2 - 42mm"`
rnaws338	`react-native run-ios --simulator "Apple Watch Series 3 - 38mm"`
rnaws342	`react-native run-ios --simulator "Apple Watch Series 3 - 42mm"`
rnaws440	`react-native run-ios --simulator "Apple Watch Series 4 - 40mm"`
rnaws444	`react-native run-ios --simulator "Apple Watch Series 4 - 44mm"`